

INSTRUCTIONS for OIL-FLO 141



REMOVE ADHESIVES, MASTIC, CUTBACK, ASPHALT, GLUE, ETC.

1. First remove the old flooring — tile, wood, carpet, glue-down, etc. Apply Oil-Flo 141 by spraying from a trigger sprayer, low-pressure tank-type sprayer or compressed air paint spray cup. Or pour the Oil-Flo 141 onto the floor or mop it on. For best results, brush in with a stiff broom or wire brush. Wait 5 to 30 minutes. Some thick materials may need a longer soak time.
2. Scrape up the softened material. A long-handled scraper with an angled blade works best. Sometimes it is better to absorb the liquid with an absorbent such as sawdust, oil-sorb, kitty litter, rags, or shredded newspaper.
3. Shovel or scrape waste material into bags or into plastic-lined cartons. If using 5-gallon pails of Oil-Flo, the empty pails (with lids removed) make convenient waste receptacles.
4. Rinse or mop clean with water. You will probably need to reapply for complete cleanup. Pick up water with a dustpan and brush, wet/dry vacuum, floor scrubber, carpet extractor, etc.



REMOVE FLOORING GLUE FROM FINISHED FLOORING

1. Apply Oil-Flo 141 directly to the dried adhesive.
2. Agitate with a soft brush or rag.
3. Remove the softened material.
4. Using a cloth soaked with plain water to rinse dry. Depending on the material, you can use a mop, rag, or extractor. Oil-Flo 141 needs the water to bond to so it can rinse away cleanly. You don't need a lot of water, just enough to make the quick bond.



REMOVE ADHESIVE LABELS, TAPE

You can remove markers, tape, self-adhesive labels, appliques and stickers of all kinds. Just apply Oil-Flo 141 to the adhesive and wait a few minutes. If you can pull off the vinyl face of the tape or sticker, the Oil-Flo 141 will dissolve the adhesive quickly. Otherwise you have to wait until the adhesive dissolves as the Oil-Flo 141 migrates under the plastic label face. When you apply Oil-Flo 141 to dried masking tape or paper labels, the Oil-Flo 141 will soak through to the adhesive. Give it time to work.

REMOVE CLOTHING STAINS

When you get tar, grease, oil or mastic on your clothes you can usually clean this stain by pre-spotting and washing. Simply spray Oil-Flo 141 on the stain, rub the fabric together to dissolve the stain. Then toss it in the washing machine. (If really heavy, apply Oil-Flo 141 and rinse separately under running water first. Reapply Oil-Flo 141 and then launder).



COVERAGE AND SPECIFICATIONS

Coverage: 100 to 400 square feet per gallon, approximately, depending on conditions. Description: Clear liquid, slight solvent odor with pleasant fragrance. Flash Point: 160°F. Auto-ignition Temperature: 900°F. Boiling Point: 550°F. Smokes when heated above 370°F. Weight: 7.6 lbs. per gallon. pH: 7.0 (neutral). Packaging: pints, gallon jugs, 5-gallon pails, 55-gallon drums. Sprayer information: Use solvent-resistant low pressure sprayer or low pressure air-cup from air compressor. Special solvent-resistant 16-oz trigger spray bottles are sold separately.

MATERIAL CAUTION: Test unfamiliar plastics before using Oil-Flo 141. You can use Oil-Flo 141 on acrylic (Plexiglas), polyethylene, type III PVC. On painted surfaces, carpets or dyed fabrics test for suitability in an inconspicuous place. Usually you can rub the area with a white cloth wetted with Oil-Flo 141. If any color is transferred to the cloth you should discontinue use or try diluting 1 to 1 with water and retest. In critical applications, dry the spot with a hair dryer and look for color change.

LIMITED WARRANTY: This product will be replaced if defective in manufacture, labeling or packaging for a period of one year following purchase. Because of the variations in materials to be cleaned and application techniques beyond the control of the manufacturer or seller, except for such replacement, the sale is without warranty or liability even though damage or loss is caused by negligence or other fault.

SAFETY CAUTION: Contains petroleum distillates and glycol ether EB. Do not take internally. If swallowed do not induce vomiting. Call a physician. If splashed in eyes rinse for 15 minutes with eyelids held open, Avoid prolonged skin contact as Oil-Flo 141 may dry the skin, in which case use a hand lotion. For extended use, neoprene gloves are recommended. Do not transfer Oil-Flo 141 into unmarked containers where it might be mistaken for other products. Work in a well-ventilated area. Product is combustible; keep it away from heat and open flame. Keep Oil-Flo 141 and all cleaning materials out of reach of children

