

Material Safety Data Sheet Ref. Nr.: HL-0910-SM002 Revised on October, 2009 Page **1** of 3

== Bamboo flooring ==

MATERIAL SAFETY DATA SHEET (MSDS)

1. PRODUCT AND COMPANY IDENTIFICATION

Common name: Home Legend Bamboo Flooring

Trade name: Bamboo Flooring, 5/8"

Manufacturer: Home Legend, LLC.

13825 Norton Ave,

Chino, CA 91710

Telephone: 877 630 1800

2. COMPOSITION AND INFORMATION ON INGREDIENTS

Composition: Bamboo

Ingredient Name: Formaldehyde

CAS-nr.: 50-00-0 **Free Emission:** <0.05ppm

Health: -

Risk: -

3. HAZARDS IDENTIFICATION

Installation of Home Legend Bamboo Flooring:

When cutting, make sure you operate on a steady support.

4. FIRST AID MEASURES

Installation of Home Legend Bamboo Flooring:

If bleeding should occur due to cutting, use bandage under compression to prevent further bleeding.

If bleeding doesn't stop, seek medical attention.

If eye irritation occurs due to repeated exposure of the eyes to dust from cutting, rinse immediately with plenty of water.

Cutting dust can be removed from skin by water and soap.



Material Safety Data Sheet Ref. Nr.: HL-0910-SM002 Revised on October, 2009 Page **2** of 3

5. FIRE AND EXPLOSION DATA

Home Legend Bamboo Flooring is considered hardly inflammable.

Auto ignition Temperature: Variable; typically 200 ~ 260 °C (400 ~ 500 °F)

Fire fighting media: Water, dry chemicals or foam.

6. ACCIDENTAL RELEASE MEASURES

Not applicable.

7. HANDLING AND STORAGE

Home Legend Bamboo Flooring is to be stored under roof, away from rain and snow.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Installation of Home Legend Bamboo Flooring:

When cutting with a motorized cutting tool or electrical saw, make sure to employ the personal protection outfit/equipment recommended by the tooling manufacturer (safety glasses, gloves etc.). Minimize skin contact to dust. Wear dust protective mask when ventilation is inadequate. Gloves suitable for protection against cuts from rough, sharp edges are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid material; Multi-layer Bamboo

Color: Various colors/patterns; otherwise not applicable

Odor: Not applicable

Solubility description: Insoluble in water and oil **Density:** Approx. 750~900 kg/m3

PH-value, cons. solution: Not available

10. STABILITY AND REACTIVITY

Home Legend Bamboo Flooring is considered stable and not reactive. It will not undergo any hazardous polymerization.

11. TOXICOLOGICAL INFORMATION

Home Legend Bamboo Flooring is considered not dangerous for humans.

12. ECOLOGICAL INFORMATION

Not applicable.

13. DISPOSAL CONSIDERATIONS



Material Safety Data Sheet Ref. Nr.: HL-0910-SM002 Revised on October, 2009 Page **3** of 3

Home Legend Bamboo Flooring can be left at ordinary disposal sites/containers. The Bamboo Flooring can be recycled. Please contact your local waste disposal plant for instructions how to recycle wood fiber. The packing of plastic is made out of polyethylene (PE) and can be deposited as plastic where source segregation is a part of the local waste disposal program. The boxes of cardboard are to be deposited as ordinary paper where source segregation is a part of the local waste disposal program.

14. TRANSPORT INFORMATION

Road transport: DOT Not regulated
Railway transport: RID Not regulated
Sea transport: IMDG Not regulated
Air transport: IATA Not regulated

15. OTHER REGULATORY INFORMATION

Not regulated

16. OTHER INFORMATION

MSDS Material Safety Data Sheet

CAS Chemical Abstract Services

DOT U. S. Department of Transportation

RID Regulations concerning the International Carriage of Dangerous Goods

by Rail

IMDG International Maritime Dangerous Goods

IATA International Air Travel Association

MSDS is Made of: Home Legend, LLC

13825 Norton Ave. Chino, CA91710