

The Clorox Company

1221 Broadway Oakland, CA 94612 Tel. 1-510-271-7000

Material Safety Data Sheet

		BLEACH ₁ – FRESH SC	ENI	
Description: CLEAR, PALE YE	LLOW, THIN LIQUID	WITH AN APPLE, FLOR	RAL, BLEACH ODOR	
•	Distr	ibutor	Emergency Telephone Nos.	
	The Clorox S	ales Company	For Medical Emergencies, call 1-800-446-1014.	
	1221 B	roadway CA 94612	For Transportation Emergencies, call 1-800-424-9300 (Chemtrec).	
II Health Hazard Data		III Hazardous	Ingredients	
Eye and skin irritant. Exposure to vapor or mist may irritate eyes, nose, throat, and lungs. The following medical conditions may be aggravated by exposure to high concentrations of vapor or mist: heart conditions or chronic respiratory problems such as asthma, emphysema, or obstructive lung disease.		Ingredient Sodium hypochlorite	Concentration Worker Exposure Limit 1 - 5% Not established.	
		CAS # 7681-52-9 Sodium hydroxide CAS # 1310-73-2	0.1 - 1% 2 mg/m³ - TLV-Cª 2 mg/m³ - PEL ^b	
FIRST AID:		G/10 // 1010 / 0 Z	2 mg/m - 1 LL	
EYE CONTACT: Hold eye open, and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. If irritation persists, call a doctor.		^a TLV-C = ACGIH Threshold Limit Value - Ceiling ^b PEL = OSHA Permissible Exposure Limit - Time Weighted Average		
<u>SKIN CONTACT</u> : Take off contaminated clothing. Rins with plenty of water for 15-20 minutes. If irritation develop				
<u>INGESTION</u> : Call a poison control center or doctor immediately. Have person sip a glassful of water if able to swallow. DO NOT induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.		None of the materials in this product are on the IARC, NTP, or OSF carcinogen lists.		
<u>INHALATION</u> : Move person to fresh air. If breathing doctor.	is affected, call a			
IV Special Protection and Precautions		V Transportation and Regulatory Data		
Hygienic Practices: Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods. Engineering Controls: Use local exhaust to minimize exposure to product mist. Personal Protective Equipment: Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.		DOT: Not restricted.		
		IMDG: Environmentally hazardous substance, liquid, n.o.s., UN3082 Class 9, PGIII.		
		<u>IATA:</u> Environmentally hazardous substance, liquid, n.o.s., UN3082, Class PGIII.		
		EPA - SARA Title III/CERCLA: This product is regulated under Section 311/312. This product contains no chemicals that are regulated under Section 313 and contains sodium hypochlorite and sodium hydroxide that are regulated under Section 304/CERCLA.		
		<u>TSCA 8(b)</u> : All components of this product are either on the TSCA 8 Inventory or otherwise exempt from listing.		
		TSCA 12(b): This requirements.	product is not subject to TSCA 12(b) reporting	
VI Snill Procedures/Wasta Disposal	VI Spill Procedures/Waste Disposal		VII Reactivity Data	
Ti opini i roccaure or tradic Didpodal		Stable under normal use and storage conditions.		
Spill Procedures: Absorb and containerize. Wash residu	ual down to sanitary	Stable under normal u	se and storage conditions.	
Spill Procedures: Absorb and containerize. Wash residusewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple pushould evaluate the MSDS's of the products for incompanypochlorite. Breathing protection should be worn in encl	ual down to sanitary to assure ability to roducts, responders atibility with sodium	Reacts with other house toilet bowl cleaners, r	se and storage conditions. sehold chemicals such as products containing ammonicust removers, vinegar, or acids to produce hazardouse and other chlorinated compounds.	
Spill Procedures: Absorb and containerize. Wash residusewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple pushould evaluate the MSDS's of the products for incompanypochlorite. Breathing protection should be worn in encl	ual down to sanitary to assure ability to roducts, responders atibility with sodium losed and/or poorly-	Reacts with other hous toilet bowl cleaners, r gases, such as chloring	sehold chemicals such as products containing ammonicust removers, vinegar, or acids to produce hazardouse and other chlorinated compounds. In metal, old porcelain, or worn plastic laminate may caus	
Spill Procedures: Absorb and containerize. Wash residusewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple probability is should evaluate the MSDS's of the products for incompany hypochlorite. Breathing protection should be worn in enclaventilated areas until hazard assessment is complete. Waste Disposal: Dispose of in accordance with all applied.	ual down to sanitary to assure ability to roducts, responders atibility with sodium losed and/or poorly-	Reacts with other house toilet bowl cleaners, r gases, such as chloring Prolonged contact with	sehold chemicals such as products containing ammoni rust removers, vinegar, or acids to produce hazardou e and other chlorinated compounds.	
Spill Procedures: Absorb and containerize. Wash residusewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple proposed should evaluate the MSDS's of the products for incompany hypochlorite. Breathing protection should be worn in enclopentiated areas until hazard assessment is complete. Waste Disposal: Dispose of in accordance with all application and local regulations.	ual down to sanitary to assure ability to roducts, responders atibility with sodium losed and/or poorly-	Reacts with other house toilet bowl cleaners, regases, such as chloring Prolonged contact with pitting or discoloration. IX Physical Date to the process of	sehold chemicals such as products containing ammoni rust removers, vinegar, or acids to produce hazardou e and other chlorinated compounds.	
Spill Procedures: Absorb and containerize. Wash residusewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple proposed should evaluate the MSDS's of the products for incompany hypochlorite. Breathing protection should be worn in enclopentiated areas until hazard assessment is complete. Waste Disposal: Dispose of in accordance with all application and local regulations. VIII Fire and Explosion Data	ual down to sanitary to assure ability to roducts, responders atibility with sodium losed and/or poorly-	Reacts with other house toilet bowl cleaners, regases, such as chloring Prolonged contact with pitting or discoloration. IX Physical Day	sehold chemicals such as products containing ammoni- rust removers, vinegar, or acids to produce hazardou e and other chlorinated compounds. In metal, old porcelain, or worn plastic laminate may caus	