

MATERIAL SAFETY DATA SHEET

HAZARDS IDENTIFICATION

(ANSI Section 3)

Primary route(s) of exposure: Inhalation, skin contact, eye contact, ingestion.

Effects of overexposure:

Inhalation: Irritation of respiratory tract. Prolonged inhalation may lead to dizziness and/or

lightheadedness, headache, loss of consciousness.

Skin contact: Irritation of skin. Eye contact: Irritation of eyes.

Ingestion: Not est.

Medical conditions aggravated by exposure: Eye, skin, respiratory disorders.

FIRST-AID MEASURES

(ANSI Section 4)

Inhalation: Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty.

Skin contact: Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use.

Eye contact: Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

Ingestion: If swallowed, obtain medical treatment immediately.

FIRE-FIGHTING MEASURES

(ANSI Section 5)

Fire extinguishing media: Dry chemical or foam water fog. Carbon dioxide. Closed containers may burst if exposed to extreme heat or fire. May decompose under fire conditions emitting irritant and/or

Fire fighting procedures: Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus.

Hazardous decomposition or combustion products: Carbon monoxide, carbon dioxide, formaldehyde, acrolein, methane, ethane.

ACCIDENTAL RELEASE MEASURES

(ANSI Section 6)

Steps to be taken in case material is released or spilled: Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Place collected material in proper container.

HANDLING AND STORAGE

(ANSI Section 7)

Handling and storage: Store below 100f (38c). Keep away from heat, sparks and open flame. Other precautions: Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after

handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Ground equipment when transferring to prevent accumulation of static charge.

EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

Respiratory protection: Control environmental concentrations below applicable exposure standards when using this material. When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian z94.4) Approved elastomeric sealing- surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/mist) prefilters. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR1910.134 For selection of respirators (Canadian z94.4).

Ventilation: Provide dilution ventilation or local exhaust to prevent build-up of vapors. **Personal protective equipment:** Eye wash, safety shower, safety glasses or goggles. Impervious

STABILITY AND REACTIVITY

(ANSI Section 10)

prepared 08/06/07

Under normal conditions: Stable see section 5 fire fighting measures

Materials to avoid: Oxidizers, nitric acid.

Conditions to avoid: Elevated temperatures, sparks, open flame, ignition sources.

Hazardous polymerization: Will not occur

TOXICOLOGICAL INFORMATION

(ANSI Section 11)

Supplemental health information: No additional effects are anticipated

Carcinogenicity: No carcinogenic effects are anticipated **Reproductive effects:** No reproductive effects are anticipated

Mutagenicity: No mutagenic effects are anticipated Teratogenicity: No teratogenic effects are anticipated

ECOLOGICAL INFORMATION

(ANSI Section 12)

No ecological testing has been done by ICI paints on this product as a whole.

DISPOSAL CONSIDERATIONS

(ANSI Section 13)

Waste disposal: Dispose in accordance with all applicable regulations.

REGULATORY INFORMATION

(ANSI Section 15)

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

Physical Data

(ANSI Sections 1, 9, and 14)

Product Code	Description	Wt. / Gal.	VOC gr. / ltr.	% Volatile by Volume	Flash Point	Boiling Range	HMIS	DOT, proper shipping name
3001-0000	groundworks slip resistant additive	2.50	0.00	n/d	above 200f	n/d		paint ** protect from freezing **

Ingredients

Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS. No.	3001-0000
1-propene, homopolymer	polypropylene	9003-07-0	99-100

Chemical Hazard Data

(ANSI Sections 2, 8, 11, and 15)

	ACGIH-TLV			OSHA-PEL				S.R.	S2	S3	CC						
Common Name	CAS. No.	8-Hour TWA	STEL	С	S	8-Hour TWA	STEL	С	S	Std.	32	33		H N	M N	1 1	0
polypropylene	9003-07-0	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n ı	n n	ı n	n

Footnotes:

C=Ceiling - Concentration that should not be exceeded, even instantaneously.

S=Skin - Additional exposure, over and above airborn exposure, may result from skin absorption. n/a=not applicable not est=not established CC=CERCLA Chemical ppm=parts per million mg/m3=milligrams per cubic meter Sup Conf=Supplier Confidential S2=Sara Section 302 EHS S3=Sara Section 313 Chemical S.R.Std.=Supplier Recommended Standard H=Hazardous Air Pollutant, M=Marine Pollutant P=Pollutant, S=Severe Pollutant Carcinogenicity Listed By: N=NTP, I=IARC, O=OSHA, y=yes, n=no

Form: 3001, Page 2 of 2, prepared 08/06/07