



## MATERIAL SAFETY DATA SHEET

### SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	DP 1030 Water Based Duct Sealant (Caulking)	<b>Revision Date:</b>	May 26, 2012
<b>Manufacturer Name:</b>	Design Polymerics	<b>Revision #:</b>	7.hd.2
<b>Address:</b>	11609 Martens River Circle Fountain Valley, CA 92708		
<b>Information Phone:</b>	(714) 432-0600	<b>DOT Hazard Class:</b>	Non-Hazardous
<b>24hr Emergency Phone:</b>	Chem-Tel, Inc: (800) 255-3924	<b>Shipping Name:</b>	N/A
<b>Internet Address:</b>	<a href="http://www.designpoly.com">http://www.designpoly.com</a>	<b>UN Number:</b>	N/A

### SECTION 2 – HAZARDOUS INGREDIENT INFORMATION

None Reportable

### SECTION 3 – HAZARDS IDENTIFICATION

**Emergency Overview:** May cause irritation to eyes and skin. May be harmful if swallowed.

**Potential Health Effects**

**Eyes:** May cause irritation if wiped or rubbed into eyes.

**Skin:** May cause slight irritation.

**Inhalation:** May cause temporary respiratory tract irritation.

**Ingestion:** No known ingestion hazards. Ingestion is not expected in industrial use.

**Chronic Health Effects:** Prolonged or repeated contact may cause skin irritation

**Signs/Symptoms:** May cause mild skin and/or eye irritation.

**Carcinogenicity:** No evidence.

**HMIS Codes:** **Health: 1, Fire: 0, Reactivity: 0, Personal Protection: B**

### SECTION 4 – FIRST AID MEASURES

**Eye Contact:** Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention.

**Skin Contact:** Wipe off excess material and wash skin with soap and plenty of water. Promptly remove contaminated clothing and launder before reuse.

**Inhalation:** No effects expected. If difficulty breathing occurs, remove affected person to well-ventilated area and consult physician.

**Ingestion:** If swallowed, do not induce vomiting unless directed to do so by a physician. Call physician or poison control center immediately.

### SECTION 5 – FIRE FIGHTING MEASURES

**Flash Point:** Not Applicable

**Flammable Limits in Air by Volume:** Lower: N/A Upper: N/A

**Extinguishing Media:** Use foam, carbon dioxide, dry chemical, or water spray.

**Special Fire Fighting Procedures:** Firefighters should wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.



**Unusual Fire and Explosion Hazards:** Closed containers exposed to temperatures above the boiling point may burst due to build-up of steam pressure.

**Hazardous Combustion Products:** Carbon monoxide, Carbon dioxide, unburned hydrocarbons, and hydrogen chloride.

**NFPA Codes:** **Health: 1, Fire: 0, Reactivity: 0, Personal Protection: B**

#### SECTION 6 – ACCIDENTAL RELEASE MEASURES/DISPOSAL CONSIDERATIONS

**Personal Precautions:** Use proper personal protective equipment as listed in section 8.

**Environmental Precautions:** Prevent spill from entering sewers, storm drains, streams, waterways, or other bodies of water.

**Spill Cleanup Measures:** Recover free liquid. Dike, contain or absorb remaining spilled material with inert, absorbent material (e.g., dry sand or earth), and remove for disposal.

**Regulatory Information:** Consult all regulations (federal, state, local, etc.) or a qualified waste disposal firm when characterizing waste for disposal.

**Waste Disposal:** Dispose of according to your local, state, and Federal EPA waste disposal regulations to ensure compliance.

#### SECTION 7 – HANDLING AND STORAGE

**Handling:** Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin, and clothing.

**Storage:** Store in a dry, well ventilated area at temperatures between 35°F and 110°F, and away from incompatible substances. Keep container tightly closed when not in use.

**Hygiene Practices:** Wash hands with soap and water after handling, especially before eating, or drinking. Avoid contact with eyes and skin. Avoid inhaling vapor or mist. Launder contaminated clothing before reuse.

#### SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION INFORMATION

**Eye/Face Protection:** Wear appropriate protective glasses or splash goggles as described by 29CFR 1910.133, OSHA eye and face protection regulation.

**Respiratory Protection:** Provide adequate mechanical (general and/or local) ventilation to maintain constant fresh air in workspace.

**Skin Protection:** Protective impervious gloves such as polyethylene are recommended. Wear impervious clothing.

**Other Work Practices and Protective Equipment:** Avoid rubbing eyes during handling. Use good personal hygiene practices to avoid incidental ingestion. Wash thoroughly with soap and water after use and before eating or drinking. A source of clean water should be available in the work area for flushing eyes and skin if necessary.

#### SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State/Appearance:</b>	Textured Mastic	<b>Color:</b>	White or Gray
<b>Boiling Point:</b>	212°F (100°F)	<b>Freezing Point:</b>	32°F (0°C)
<b>Solubility in Water:</b>	Miscible	<b>pH:</b>	7.5-9.0
<b>Specific Gravity (H<sub>2</sub>O=1):</b>	1.3-1.5	<b>% Volatiles by Weight:</b>	30-40
<b>Flash Point:</b>	No Data	<b>Vapor Density:</b>	Heavier Than Air
<b>Coating VOC (Excludes H<sub>2</sub>O):</b>	<7 g/l		



## SECTION 10 – STABILITY AND REACTIVITY INFORMATION

<b>Chemical Stability:</b>	Stable under normal temperatures and pressures.
<b>Hazardous Polymerization:</b>	Will not occur.
<b>Conditions to Avoid:</b>	Avoid extreme heat, flames, incompatible materials, freezing, or temperatures below 32°F (0°F).
<b>Incompatible Materials:</b>	Avoid strong acids, strong alkalis and oxidizing agents.

## SECTION 11 – REGULATORY INFORMATION

This product is considered non-hazardous under OSHA Hazard Communication Standard 29CFR 1910.2100.

<b>U.S. TSCA Inventory:</b>	All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.
<b>California Prop. 65:</b>	None listed.
<b>SARA Section 311/312 Categories (40 CFR 370):</b>	Immediate (Acute) Health Hazard.

## SECTION 12 – ADDITIONAL INFORMATION

<b>MSDS Prepared by:</b>	R&D Department
<b>Date Prepared:</b>	05/26/11

**Disclaimer:** The information contained herein is based upon data and information provided to us, and is believed to be accurate to the best of our knowledge and belief at the date of its publication. In many instances, especially when proprietary or trade secret materials are used, we must rely on hazard evaluation of such components by that products' manufacturer or importer. Since Design Polymerics has no control over the conditions of handling and use, no warranty of merchantability, fitness for any use, or any other warranty is expressed or implied, regarding the accuracy of such data or the results to be obtained from the use thereof. The information contained herein is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use and is designed only as a guide for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. It is the responsibility of the user of Design Polymerics products to comply with all applicable Federal, State and Local Laws and Regulations.

**Trademark:** The trademarks, graphics and logos used on this MSDS are registered or unregistered trademarks of Design Polymerics. All Rights Reserved.

## ADDENDUM – COMPOSITION

INGREDIENT	CAS#	WEIGHT PERCENTAGE
Water		20-40
Proprietary Polymer Emulsion		30-60
Air release agent		<1
Proprietary surfactant		<1
In Can preservative		<1



Carbon Black	1333-86-4	0-2
Proprietary Additive		2-6
Talc	14807-96-6	3-6
Calcium Carbonate	1317-65-3	40-70
Polypropylene Fiber	9003-07-0	<1
Proprietary Acrylate Dispersion		<1