Entrance Lockset Installation













E

Insert the outside unit introducing the posts of the unit through the holes of the dead locking latch as shown.

Inside unit spindle
The square Spindle of the outside unit should be inserted into the square cavity of the inside unit.

Adjust the lock to the door by screwing the mounting screws.
Note:do not use excessive force

Install the rose of the inside unit by screwing it to the inside mounting plate thread.

Install the inside knob/lever:
Check the position of the turn button and align it with the security bar.
Insert the inside knob/lever making sure the knob/lever catch slot is aligned with the knob/lever catch of the lock.

Secure the latch by screwing the latch screws to the door.
Note:do not use excessive force

ES

Inserte la unidad exterior introduciendo los postes de esta unidad por las ranuras del pestillo como se muestra en la imagen.

Alineamiento de la unidad interior.
La barra cuadrada de la unidad exterior deberá de ser insertada en la cavidad cuadrada de la unidad interior.

Ajuste la cerradura a la puerta, mediante la fijación de tornillos al mecanismo de la cerradura.
Nota: no exceda en fuerza al fijar los tornillos.

Instale la roseta de la unidad interior atornillándola (girándola) sobre la placa de montaje roscada.

Instalación de la Perilla o Manija
Primero alinie la parte interior del botón con la barra de seguridad.
Inserte la perilla o manija asegurándose que la ranura de la cuña esté alineada con la cuña de la cerradura, empuje hasta que escuche un "click".

Asegure el pestillo atornillándolo a la puerta.
Nota: no se exceda en la fuerza al atornillar.

F

Faire entrer l'unité extérieure en introduisant les tiges à travers les trous de la serrure, comme sur l'illustration .

Alignement de l'unité intérieure
La tige carrée de l'unité extérieure doit loger dans la cavité carrée de l'unité intérieure.

Réglez la serrure sur la porte en visant les vis de montage (ne pas trop serrer)

Installez la rosace de la partie intérieure en visant sur la plaque de montage intérieure

Posez la poignée/bec-de-cane intérieure: Vérifiez la position du bouton tournant de retient et aligner avec la tige de sécurité
Faites entrer la poignée/ bec-de-cane intérieure en vous assurant que la fente du logement de la poignée/bec-de-cane est bien alignée avec le logement de la poignée de la serrure.

Fixer la têtière en visant ses vis sur la porte (ne pas trop serrer

WARNING: Always use protective eyewear and gloves when installing the lockset on the door

Lifetime Limited Mechanical Warranty.
This warrants to the original consumer purchaser that this product is free from mechanical defects for the lifetime of it as long as the original consumer purchaser owns this product.
Exclusions from warranty.
1. This warranty is not transferable. No transferee is covered by this warranty.
2. Any product having a defect caused by neglect, misuse, abuse, or unreasonable or extraordinary use or maintenance is not covered by this warranty.
3. Any product that has been modified is not covered by this Warranty.
4. Any product which has been damaged as a result of installation contrary to written installation instructions is not covered by this warranty.
5. This Warranty does not cover the finish of this product.
6. All final decisions concerning quality remain exclusively in the discretion of The Company.

Lifetime Limited Finish Warranty.
THIS WARRANTY WILL ONLY APPLY TO PRODUCTS WITH PVD FINISH.
This warrants to the original consumer purchaser that this product is free from defects in material and workmanship from tarnishing, flaking, pitting, and discoloring for the lifetime of it as long as the original consumer purchaser owns this product.
Exclusions from warranty.
1. This warranty is not transferable. No transferee is covered by this warranty.
2. Any product having a defect caused by neglect, misuse, abuse, or unreasonable or extraordinary use or maintenance is not covered by this warranty.
3. Any product that has been modified is not covered by this Warranty.
4. Any product which has been damaged as a result of installation contrary to written installation instructions is not covered by this warranty.
5. Products are manufactured with the highest standards in the industry. Products are susceptible to small surface indentations and imperfections due to the malleability of the material and the crafting of the product. These conditions are not consider a defect, therefore the warranty does not apply in this cases. All final decisions concerning quality remain exclusively in the discretion of The Company.

REMEDIES (FOR BOTH WARRANTIES). If a claim is made under this warranty and, after investigation by The Company, proves to be valid, The Company will, at its sole option, either repair or replace the defective product or refund the original purchase price. Upon such a repair or replacement, the original remaining warranty period will continue in effect and be applicable to the repaired or replaced product. If this product or any part covered by this warranty has been discontinued at the time of repair or replacement or if The Company determines, in its sole discretion, that such repair or replacement is inappropriate, The Company reserves the right to refund the original consumer purchase price of the product. Except as expressly provided in the warranty to the contrary, The Company SHALL NOT BE OBLIGATED OR LIABLE FOR LABOR OR OTHER COSTS RELATED TO INSTALLATION, REPAIR OR REPLACEMENT OF ANY OF ITS PRODUCTS OR LOSS OF, OR DAMAGE TO, ANY MATERIAL WHICH IS NOT SOLD BY The Company.
WARRANTY CLAIMS (FOR BOTH WARRANTIES). All claims and other communications under this warranty must be made to the claimant's dealer or retailer. Each claim must be in writing, briefly describe the defect, and be accompanied by a proof of purchase that shows the claimant is the original consumer purchaser. The claimant must provide to his or her dealer or retailer other information and evidence reasonably required by The Company and, if requested, must permit inspection of the product by The Company or its representatives. If, after investigation, The Company determines that the claim is valid, the remedy will be performed by or on behalf of The Company in accordance with the above heading, "Remedies".
LIMITATION OF LIABILITIES (FOR BOTH WARRANTIES). Except as expressly provided in this warranty to the contrary, The Company MAKES NO, AND DISCLAIMS ALL,WARRANTIES, REPRESENTATIONS AND GUARANTEES (WHETHER EXPRESS, IMPLIED OR STATUTORY), INCLUDING,(BUT NOT LIMITED TO,ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE . SOME STATES DO NOT ALLOW EXCLUSION OF IMPLIED WARRANTIES, EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LIMITATION ON THE LENGTH OF AN IMPLIED WARRANTY, AND THEREFORE SOME OR ALL OF THE LAST SENTENCE UNDER THE ABOVE HEADING, "REMEDIES," AND THE IMMEDIATELY PRECEDING TWO SENTENCES MAY NOT APPLY. This warranty is the only express warranty provided by The Company. No employee, representative or agent of The Company, nor any other person, has authority to assume or incur on behalf of The Company any obligation or liability in place of or in addition to this warranty. This warranty provides specific legal rights, and other rights, which vary from State to State.

ENTRY LOCKSET

E Installation instructions
ES Instructivo de instalación
F Mode d´installation



Exploded Views Entrance Lock
Despiece de Cerradura de Entrada
Éclaté des Serrures d'entrée

Packaging Dismount

E

Dismount knob/lever by pushing the inside knob/lever catch using the tool provided Then pull the knob/lever outside of the lock.

Dismount the inside rose by unscrewing it from the lock.
Dismount the lock from the package by unscrewing the mounting screws of the lock.

ES

Desmonte la perilla/manija mediante la opresión de la cuña con el instrumento proporcionó Jale la perilla/manija de la cerradura.

Desmonte la roseta interior de la cerradura girándola.
Desmonte la cerradura del empaque mediante la remoción de los tornillos de la cerradura.

F

Démontez la poignée/bec-de-cane en poussant leverrou au moyen l'outil a fourni Sortez la poignée/bec-de-cane de la serrure.

Désmontez la rosace intérieure de la serrure en la faisant tourner.
Déttachez la serrure de la garbiture en enlevant les vis de la serrure.

WARNING: Always use protective eyewear and gloves when installing the lockset on the door

Door Preparation (if required)

E

Fold the template on the line and locate on door at desired height (about 40" from the floor). If the door is beveled, place folded edge on low side of bevel as shown in illustration. Mark door.

Caution: Re-check bore hole locations before drilling. Drill the face bore 2 1/8" and edge bore 1" as indicated on the template.

Insert the latch into the edge of the door. Trace an outline of the faceplate onto the door edge. Mark screw hole center and drill with 1/8" driller.Remove latch.

Chisel out the area previously marked to a depth of 5/32" or until faceplate is flush with door edge. You may now proceed to Strike Installation.

ES

Doble la plantilla sobre la línea marcada y coloque en el canto de la puerta a la altura adecuada (40" del piso). Si su puerta es biselada, coloque la plantilla en el lado mas bajo del bisel como se muestra. Marque.

Precaución: Revise la marca de perforaciones antes de taladrar. Perfore las circunferencias de puerta 2 1/8" y canto 1" como se indica.

Coloque el pestillo en el canto de la puerta. Copie el borde del frente del pestillo sobre el canto. Marque las perforaciones de los tornillos de 1/8". Retire el pestillo.

Remueva el area marcada del frente del pestillo con una profundidad de 5/32" o hasta que el mismo este al ras del canto. Proceda a instalar la contra.

F

Pliez le gabarit sur la ligne y placez le sur la porte à la hauteur souhaitée (près de 40" du sol). Si la porte est bisautée, placer le bord plié sur la partie inférieure du biseau comme l'indique l'illustration. Faites le tracé sur la porte.

Attention. Vérifier à nouveau l'emplacement du trou percé. Percez le trou de face 2 1/8" et de bord 1" indiqués sur le gabarit.

Introduisez le verrou dans le bord de la porte. Faites le tracé de la têtière sur le bord de porte. Marquez le centre des trous des vis et percez avec une perceuse d' 1/8".

Ciselez la zone tracée à une profondeur de 5/32" ou jusqu'à ce que la têtière se trouve au même niveau que le bord de porte. Vous pouvez commencer à installer la gâche.

Strike Installation

E

Using the strike portion of the marking template, locate and mark strike mounting screws and centering points for your door thickness.

Align the strike and trace outline onto the door frame using mounting screw marks for location.

At screw marks, drill two 1/8" dia. pilot holes for the screws. Bore 7/8" dia. x 3/4" deep hole.

Chisel area previously marked until strike is flush with the door frame.

Install strike.
You may now proceed to Latchbolt preparation and Latchset Installation.

ES

Utilice la parte marcada para la contra en la plantilla, localice y marque los tornillos, además de centrar las marcas contra el ancho de la puerta.

Alinie la contra y trace el borde sobre el marco de la puerta utilizando las marcas de los tornillos como guias.

En las marcas de los tornillos perfore hoyos de 1/8" de diámetro. Al centro una perforación de 7/8" de diámetro x 3/4" de profundidad.

Remueva la silueta previamente marcada hasta que la contra quede al ras del marco.

Instale la contra.
Ahora proceda preparar e instalar el pestillo de seguridad.

F

En utilisant la partie de la gâche du gabarit, tracez l'emplacement des vis de montage de la gâche et centrez les points conformément à l'épaisseur de la porte.

Aligner la gâche et et faites un tracé sur le chambranle en utilisant les marques des vis de montage pour vous y répérer.

Percez deux trous guide d' 1/8" de diamètre sur les marques de vis. Percez ensuite un trou de 7/8" de diamètre sur 3/4" de profondeur.

Ciselez la zone tracée au pas 2 jusqu'à ce que la gâche se trouve au même niveau que le chambranle.

Installer la gâche. Vous pouvez commencer à installer le verrou.

Preparing Latchbolt

This latchbolt is adjustable. To adjust the backset, just pull the square cam to the 2 3/4" position.

Este pestillo es ajustable. Para ajustarlo a la posición de 2 3/4", jale la leva cuadrada hasta que llegue a la posición de 2 3/4".

Le pêne est ajustable.
En départ d'usine il se trouve préparé à 2 3/8".
Pour le mener à 2 3/4" tirer le récepteur carré jusqu'à atteindre 2 3/4".

Entrance Lockset Installation

Slide the dead locking latch into the door as shown.
Note: Do not fix the latch at this stage. (do not screw at this stage).

Correct position of the lock:
The knob/lever catch, must be facing the latch of the lock. (On both units outside and inside).

Deslice el pestillo de seguridad a la puerta como se muestra en la imagen. Nota : en esta etapa todavía no asegure el pestillo a la puerta (no atornillar).

Oriente la cerradura en su posición correcta. Las cuñas de la cerradura (knob/lever catch) deben de apuntar en la misma dirección del pestillo.

Encastrez le verrou dans la porte tel que dans l'illustration. Ne pas fixer le verrou à ce stade.

Corrigez la position de la serrure:
Le logement de la poignée/bec-de-cane doit se trouver en regard de la têtière (à l'intérieur et à l'extérieur)

Packaging Dismount (Only required for Visual Pack)







E

Loosen the Allen screw from the knob/lever using included Allen wrench. (Do no extract the Allen screw).

Remove the rose.

Remove the package adapter and throw away the packaging spindle. Repeat the dismounting sequence for the other unit.

ES

Afloje el tornillo Allen de la perilla/manija usando la llave Allen incluída. (no extraiga el tornillo Allen totalmente).

Retire la roseta.

Retire el adaptador del empaque y deseche el eje del empaque. Repita la secuencia para la otra unidad.

F

Dévisez la vis Allen de la poignée/bec-de-cane au moyen de la clé livrée Allen avec. (ne pas le sortir Allen compétement).

Enlevez la rosace.

Sortez l'adapteur de la garniture et jetez l'axe de la garniture. Répétez la même démarche pour l'autre unité.

WARNING: Always use protective eyewear and gloves when installing the lockset on the door

Door Preparation (if required)









E

Fold the template on the line and locate on door at desired height (about 40" from the floor). If the door is beveled, place folded edge on low side of bevel as shown in illustration. Mark door.

Caution: Re-check bore hole locations before drilling. Drill the face bore 2 1/8" and edge bore 1" as indicated on the template.

Insert the latch into the edge of the door. Trace an outline of the faceplate onto the door edge. Mark screw hole center and drill with 1/8" driller.

Chisel out the area previously marked to a depth of 5/32" or until faceplate is flush with door edge. You may now proceed to Strike installation.

ES

Doble la plantilla sobre la línea marcada y coloque en el canto de la puerta a la altura adecuada (40" del piso). Si su puerta es biselada, coloque la plantilla en el lado mas bajo del bisel como se muestra. Marque.

Precaución: Revise la marca de perforaciones antes de taladrar. Perfore las circunferencias de puerta 2 1/8" y canto 1" como se indica.

Coloque el pestillo en el canto de la puerta. Copie el borde del frente del pestillo sobre el canto. Marque las perforaciones de los tornillos de 1/8".

Remueva el area marcada del frente del pestillo con una profundidad de 5/32" o hasta que el mismo este al ras del canto. Instale la contra.

F

Pliez le gabarit sur la ligne y placez le sur la porte à la hauteur souhaitée (près de 40" du sol). Si la porte est bisautée, placer le bord plié sur la partie inférieure du biseau comme l'indique l'illustration. Faites le tracé sur la porte.

Attention. Vérifier à nouveau l'emplacement du trou percé. Percez le trou de face 2 1/8" et de bord 1" indiqués sur le gabarit.

Introduisez le verrou dans le bord de la porte. Faites le tracé de la têtière sur le bord de porte. Marquez le centre des trous des vis et percez avec une perceuse d' 1/8".

Ciselez la zone tracée à une profondeur de 5/32" ou jusqu'à ce que la têtière se trouve au même niveau que le bord de porte. Vous pouvez commencer à installer la gâche.

Strike Installation











E

Using the strike portion of the marking template, locate and mark strike mounting screws and centering points for your door thickness.

Align the strike and trace outline onto the door frame using mounting screw marks for location.

At screw marks, drill two 1/8" dia. pilot holes for the screws. Bore 7/8" dia. x 3/4" deep hole.

Chisel area marked until strike is flush with the door frame.

Install strike. You may now proceed to Latchbolt Installation.

ES

Utilice la parte marcada para la contra en la plantilla, localice y marque los tornillos, además de centrar las marcas contra el ancho de la puerta.

Alinie la contra y trace el borde sobre el marco de la puerta utilizando las marcas de los tornillos como guias.

En las marcas de los tornillos perfore hoyos de 1/8" de diámetro. Al centro una agujero de 7/8" de diámetro x 3/4" de profundidad.

Remueva la silueta marcada hasta que la contra quede al ras del marco.

Instale la contra. Ahora proceda a instalar el pestillo.

F

En utilisant la partie de la gâche du gabarit, tracez l'emplacement des vis de montage de la gâche et centrez les points conformément à l'épaisseur de la porte.

Aligner la gâche et et faites un tracé sur le chambranle en utilisant les marques des vis de montage pour vous y répérer.

Percez deux trous guide d' 1/8" de diamètre sur les marques de vis. Percez ensuite un trou de 7/8" de diamètre sur 3/4" de profondeur.

Ciselez la zone tracée au pas 2 jusqu'à ce que la gâche se trouve au même niveau que le chambranle.

Installer la gâche. Vous pouvez commencer à installer le verrou.

Preparing Latchbolt



E

If you have purchased a privacy lockset, the latchbolt should be installed so that the threaded stud is on the inside (or locking side) of the door. The curved side of the latchbolt must face the jamb. The latchbolt can be reversed by simply rotating the latchbolt one half turn.

ES

Si adquirió una cerradura de Privacía, el pestillo debe instalarse de manera que la parte recta este al interior (o lado hacia donde cierra) de la puerta. El lado curvo del pestillo debe de mirar hacia el marco de la puerta. El pestillo puede cambiarse de abatimiento (reversible) con solo rotarlo media vuelta.

F

Si vous avez acheté un set de sécurité, le verrou devrait être installé de sorte que le boulon fileté se trouve à l'intérieur (ou côté fermeture) de la porte. Le côté courbé du verrou doit se trouver en regard du chambranle, Le verrou peut être inversé simplement en faisant tourner le verrou un tour.

Passage and Privacy Lockset Installation















E

Place the latch support into the face bore preparation, then slide the latch into the door, making sure the latch is introduced into the latch support as shown. (this part has two sides, make sure it is placed properly). For a privacy set, the threaded stud should be on the inside. Slide the face plate over the latchbolt and secure with two wood screws.

Follow the direction of stamped arrow, insert spindle through the square hole of latch from external side of door. The split line of spindle should be located in center of latch. The pre-cut groove on both sides of spindle must face downward.

Install the inside adapter. To determine the inside adapter, there is countersunk on screw mounting hole to receive the head of screw.

Install the outside adapter and tighten the screws.

Snap roses onto adapters. For a Passage or Privacy set, make sure the privacy hole in the roses are towards the edge of door. (The rose installed on the inside door should be with a larger hole for privacy button). Screw in the privacy button.

Put plastic washers on shank of knob/levers. Slide the internal knob/lever onto spindle, push the spindle from external side at the same time. Make sure there is no gap between knob/lever and rose. Tighten set screw with Allen wrench provided.

Slide the remaining knob/lever onto the spindle. Make sure there is no gap between the knob/lever and rose. Tighten set screw.

ES

Coloque el soporte de pestillo dentro de la perforación hecha previamente, deslice el pestillo dentro de la puerta en posición correcta e introdúzcalo en el soporte de pestillo (este soporte tiene dos posiciones, asegúrese de colocarlo correctamente, ver fig.) Para cerraduras de Privacía, el botón de privacía del pestillo deberá mirar hacia el interior. Deslice el frente del pestillo sobre este y atornille.

Siga la dirección indicada por la flecha grabada sobre el cuadrillo y páselo a traves de la perforación cuadrada del pestillo desde el lado exterior de la puerta. La línea marcada al centro del cuadrillo deberá coincidir con el centro del pestillo. Los cortes diagonales en ambas orillas del poste deben estar hacia abajo.

Instale el adaptador interior. Para reconocer el adaptador interior, las perforaciones para los tornillos tienen avellanados o desbastados para alojar completamente las cabezas de los tornillos.

Instale el adaptador exterior y atornille.

Coloque a presión las rosetas. Para cerradura de Paso o Privacía, verifique que la perforación de privacidad en las rosetas este hacia el canto de la puerta. (La roseta del interior tiene una perforación mayor). Atornille el botón de privacidad.

Coloque las rondanas de plastico alineadas al poste de la perilla o manija. Deslice la perilla/manija interior sobre la barra, al mismo tiempo presione esta por el exterior. Asegúrese de no dejar espacios entre la perilla/manija y la roseta. Apriete los tornillos Allen.

Deslice la perilla/manija restante en la barra. Asegúrese de no dejar espacio entre la perilla/manija y la roseta. Atornille.

F

Placez le logement du verrou dans la face percée au cours, préparation de la porte, ensuite glissez le verrou dans la porte et le soutien du verrou comme sur l'illustration (ou côté verrouillage) de la porte. Dans le cas du set de sécurité, le boulon fileté doit se trouver à l'intérieur. Glissez la têtière sur le verrou et fixez à l'aide de deux vis à bois.

Suivez la direction de la flèche et introduisez le rouleau à travers le trou quarré du verrou du côté extérieur de la porte. La ligne de division du rouleau doit se trouver au centre du verrou. Les encoches prégravées des deux côtés du rouleau doivent regarder vers le bas.

Installez l'adapteur intérieur. Afin de définir l'adapteur intérieur, le trou de montage de la vis est fraisé afin de loger la tête de la vis.

Installez l'adapteur extérieur et fixez les vis.

Introduisez des rosettes dans les adapteurs. Pour le set de sécurité, assurez-vous que le trou de sécurité des rosettes se trouve vers le bord de porte. (La rosette mise en place à l'intérieur de la porte doit avoir un trou plus large pour loger le bouton de sécurité). Fixez le bouton de sécurité.

Placez des rondelles sur la tige de la poignée. Glisser la poignée intérieure dans le rouleau, poussez le rouleau simultanément à partir de l'extérieur. Assurez-vous de ne pas laisser d'interstice entre la poignée et la rosette. Fixez la vis d'arrêt à l'aide d'une clé allen (qui est comprise dans le set).

Glissez la poignée dans le rouleau. Assurez-vous de ne pas laisser d'interstice entre la poignée et la rosette. Fixez la vis.

Lifetime Limited Mechanical Warranty.

This warrants to the original consumer purchaser that this product is free from mechanical defects for the lifetime of it as long as the original consumer purchaser owns this product.

Exclusions from warranty.

1. This warranty is not transferable. No transferee is covered by this warranty.
2. Any product having a defect caused by neglect, misuse, abuse, or unreasonable or extraordinary use or maintenance is not covered by this warranty.
3. Any product that has been modified is not covered by this Warranty.
4. Any product which has been damaged as a result of installation contrary to written installation instructions is not covered by this warranty.
5. This Warranty does not cover the finish of this product.
6. All final decisions concerning quality remain exclusively in the discretion of The Company.

Lifetime Limited Finish Warranty.

THIS WARRANTY WILL ONLY APPLY TO PRODUCTS WITH PVD FINISH.

This warrants to the original consumer purchaser that this product is free from defects in material and workmanship from tarnishing, flaking, pitting, and discoloring for the lifetime of it as long as the original consumer purchaser owns this product.

Exclusions from warranty.

1. This warranty is not transferable. No transferee is covered by this warranty.
2. Any product having a defect caused by neglect, misuse, abuse, or unreasonable or extraordinary use or maintenance is not covered by this warranty.
3. Any product that has been modified is not covered by this Warranty.
4. Any product which has been damaged as a result of installation contrary to written installation instructions is not covered by this warranty.
5. Products are manufactured with the highest standards in the industry. Products are susceptible to small surface indentations and imperfections due to the malleability of the material and the crafting of the product. These conditions are not considered as defects, therefore the warranty does not apply in these cases. All final decisions concerning quality remain exclusively in the discretion of The Company.

REMEDIES (FOR BOTH WARRANTIES). If a claim is made under this warranty and, after investigation by The Company, proves to be valid, The Company will, at its sole option, either repair or replace the defective product or refund the original purchase price. Upon such a repair or replacement, the original remaining warranty period will continue in effect and be applicable to the repaired or replaced product. If this product or any part covered by this warranty has been discontinued at the time of repair or replacement or if The Company determines, in its sole discretion, that such repair or replacement is inappropriate, The Company reserves the right to refund the original consumer purchase price of the product. Except as expressly provided in the warranty to the contrary, The Company SHALL NOT BE OBLIGATED OR LIABLE FOR LABOR OR OTHER COSTS RELATED TO INSTALLATION, REPAIR OR REPLACEMENT OF ANY OF ITS PRODUCTS OR LOSS OF, OR DAMAGE TO, ANY MATERIAL WHICH IS NOT SOLD BY The Company.

WARRANTY CLAIMS (FOR BOTH WARRANTIES). All claims and other communications under this warranty must be made to the claimant's dealer or retailer. Each claim must be in writing, briefly describe the defect, and be accompanied by a proof of purchase that shows the claimant is the original consumer purchaser. The claimant must provide to his or her dealer or retailer other information and evidence reasonably required by The Company and, if requested, must permit inspection of the product by The Company or its representatives. If, after investigation, The Company determines that the claim is valid, the remedy will be performed by or on behalf of The Company in accordance with the above heading, "Remedies".

LIMITATION OF LIABILITIES (FOR BOTH WARRANTIES). Except as expressly provided in this warranty to the contrary, The Company MAKES NO, AND DISCLAIMS ALL,WARRANTIES, REPRESENTATIONS AND GUARANTEES (WHETHER EXPRESS, IMPLIED OR STATUTORY), INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE , SOME STATES DO NOT ALLOW EXCLUSION OF IMPLIED WARRANTIES, EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LIMITATION ON THE LENGTH OF AN IMPLIED WARRANTY, AND THEREFORE SOME OR ALL OF THE LAST SENTENCE UNDER THE ABOVE HEADING, "REMEDIES," AND THE IMMEDIATELY PRECEDING TWO SENTENCES MAY NOT APPLY. This warranty is the only express warranty provided by The Company. No employee, representative or agent of The Company, nor any other person, has authority to assume or incur on behalf of The Company any obligation or liability in place of or in addition to this warranty. This warranty provides specific legal rights, and other rights, which vary from State to State.

PASSAGE HALL and PRIVACY DECORATIVE LOCKSET

E Installation instructions

ES Instructivo de instalación

F Mode d´installation



Exploded Views Passage and Privacy Locksets

Despiece de Cerradura de Paso y Privacía

Éclaté des Serrures de Süretè