

TECHNICAL SPECIFICATIONS

GOAL ZERO
YETI150 SOLAR GENERATOR

Technical Specifications

Product:	Yeti 150
Charge times:	
Wall charger (45W)	6 hrs
Car charger (30W)	8 hrs
GOAL ZERO Nomad 13	26-52 hrs
GOAL ZERO Nomad 26	13-26 hrs
GOAL ZERO Boulder 15 v2	22-44 hrs
Battery:	
Cell type	AGM Lead Acid
Pack capacity	168Wh (12V, 14Ah)
Lifecycles	hundreds of cycles
Shelf-life	charge every 3 months
Fuses	none
Management system	Charging and low-battery protection built-in
Ports:	
USB port (output)	5V, up to 2A (10W max), regulated
6mm port (output, 6mm, green, hexagon)	12V, up to 10A (120W max)
12V car port (output)	12V, up to 10A (120W max)
AC inverter US (output, 60Hz, modified sine wave)	110V, 0.7A (80W continuous, 160W surge max)
AC inverter Int (output, 50Hz, modified sine wave)	220V, 0.4A (80W continuous, 160W surge max)
charging port (input, 8mm, blue, circle)	14-29V, up to 5A (60W max)
General:	
Chainable	no
Weight	12 lbs (5.4 kg)
Dimensions	7.75 x 5.75 x 6.75 in (19.7 x 14.6 x 17.2 cm)
Operating usage temp.	32-104 F (0-40 C)
Certs: (display as icons)	CE, FCC, ROHS
Warranty	6 months