KAPER INDUSTRIAL LTD.
基霸實業有限公司
UNIT 5A-B 16TH FL.,
WELL FUNG INDUSTRIAL CENTRE
68 TA CHUEN PING STREET,
KWAI CHUNG, HONG KONG.
TEL:(852)24220838/FAX:(852)24237736

Material Safety Data Sheet

This material safety data sheet (MSDS) is provided in response to customer request. This product is not regulated under, and a MSDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

SECTION 1: GENERAL INFORMATION

PRODUCT NAME:

41-4296

SECTION 2: INGREDIENTS

Ingredient	C.A.S. No.	% by Wt
41-4296	none	Not Applicable

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

General Physical Form: Solid

Immediate health, physical, and environmental hazards: The environmental properties of this product present a low environmental hazard. This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

KAPER INDUSTRIAL LTD.
基霸實業有限公司
UNIT 5A-B 16TH FL.,
WELL FUNG INDUSTRIAL CENTRE
68 TA CHUEN PING STREET,
KWAI CHUNG, HONG KONG.
TEL:(852)24220838/FAX:(852)24237736

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: No need for first aid is anticipated.

Skin Contact: No need for first aid is anticipated.

Inhalation: No need for first aid is anticipated.

If Swallowed: No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature: Not Applicable

Flash Point: Not Applicable

Flammable Limits – LEL: Not Applicable

Flammable Limits – UEL: Not Applicable

5.2 EXTINGUISHING MEDIA

Use extinguishing agents suitable for surrounding fire, such as water spray, foam, dry powder, or CO2.

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards are anticipated.

Hazardous Decomposition Products: CO, CO_2

SECTION 6: REACTIVITY DATA

Stability: Stable

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. User is responsible for determining whether the product is fit for a

KAPER INDUSTRIAL LTD.
基霸實業有限公司
UNIT 5A-B 16TH FL.,
WELL FUNG INDUSTRIAL CENTRE
68 TA CHUEN PING STREET,
KWAI CHUNG, HONG KONG.
TEL:(852)24220838/FAX:(852)24237736

particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.