

# TECHNICAL SPECIFICATIONS

## GOAL ZERO **YETI**400 SOLAR GENERATOR

### Technical Specifications

<b>Product:</b>	<b>Yeti 400</b>
<b>Charge times:</b>	
Wall charger (75W)	5 hrs
Car charger (30W)	13 hrs
GOAL ZERO Boulder 30	20-40 hrs
GOAL ZERO Nomad 26	30-60 hrs
<b>Battery:</b>	
Cell type	AGM Lead Acid
Pack capacity	396Wh (12V, 33Ah)
Lifecycles	hundreds of cycles
Shelf-life	charge every 3 months
Fuses	none
Management system	Charging and low-battery protection built-in
<b>Ports:</b>	
USB port (output)	5V, up to 1.5A (7.5W max), regulated
6mm port (output, 6mm, green, hexagon)	12V, up to 10A (120W max)
12V car port (output)	12V, up to 10A (120W max)
AC inverter US (output, 60Hz, pure sine wave)	110V, 2.6A (300W continuous, 600W surge max)
AC inverter Int (output, 50Hz, pure sine wave)	220V, 1.4A (300W continuous, 600W surge max)
charging port (input, 8mm, blue, circle)	14-29V, up to 10A (120W max)
<b>General:</b>	
Chainable	yes
Weight	29 lbs (13.2 kg)
Dimensions	10.25 x 8 x 8 in (26 x 20.3 x 20.3 cm)
Operating usage temp.	32-104 F (0-40 C)
Certs: (display as icons)	CE, FCC, ROHS
Warranty	6 months