

# How to Apply Elastomeric Roof Coatings



## STEP 1: PREPARE THE SURFACE

- **Clear roof surface** of loose debris including dirt, gravel, sticks, etc. using a push broom or blower
- **Clean** with Gardner Power Kleen™ or a pressure washer.
- **Patch and repair** cracks, blisters and other problem areas using **Black Jack White Acrylic Roof Patch**, following label directions. Reinforce repairs with **Sta-Kool Stress Block™ reinforcement fabric**.

## RECOMMENDED SURFACES

- Metal
- Urethane/polystyrene foam
- Concrete roofs
- Aged rolled roofing and aluminum coatings
- Flat and barrel cement tile



## STEP 2: APPLY ELASTOMERIC COATING

On a clear, warm, sunny day, roll, brush or spray Black Jack®, Gardner™ or STA-KOOL® White Elastomeric Roof Coating to a dry roof surface. Follow all label directions.

## RECOMMENDED APPLICATORS

Roof brush, ¾" nap roller, or airless spray in 10"-12" pattern, 2000 psi, .021 to .025 spray tip

## COVERAGE RATES: TWO COATS RECOMMENDED

Metal	80 to 100 sq. ft. per a gallon
Foam	50 to 75 sq. ft. per a gallon
Concrete tile	50 to 75 sq. ft. per a gallon