

# ZVC30LSS GE Monogram<sup>®</sup> 30" Custom Hood Insert



The custom canopy must be sized to fit the insert sleeve. Construct the canopy with an opening that is:  $26"W \times 13-3/16"D$ 

The opening must be constructed of 3/4" thick material to allow the sleeve locking clips to engage.

#### The Supplied Liner



A stainless steel liner is shipped with each hood insert. This non-combustible liner protects the underside of the canopy. **Custom Liner** 


If you are not using the supplied liner, you may construct a custom non-combustible liner. Use the supplied liner as a template. The opening must be  $26"W \times 13-3/16"D$ . 3/4" thick material must surround the opening to allow the sleeve locking clips to engage. The insert sleeve inside the cabinet should be positioned 1/2" from the rear wall so that the center of the 8" duct is 5-1/2" from the rear wall.

For answers to your Monogram,<sup>®</sup> GE Profile<sup>™</sup> or GE<sup>®</sup> appliance questions, visit our website at ge.com or call GE Answer Center<sup>®</sup> service, 800.626.2000.




imagination at work

Dimensions and Specifications (in inches) Outside Dimensions




The Insert Sleeve



The bottom edge of the insert sleeve has a 7/8" wide flange on the sides and a 1/2" wide flange on the front and back.

### **Remote Location for the Control**

The control may be removed from the hood and installed into a wall or countertop. A 30-ft length of wire is supplied to accommodate most installations. A blanking plate covers the opening when the controls are removed. The overall size of the control is 4-1/4" wide and 2-1/4" deep.



We recommend that the cutout in granite or other hard surfaces be made before the countertop is installed.

## ZVC30LSS GE Monogram<sup>®</sup> 30" Custom Hood Insert

### **Features and Benefits**

- Patented Installation Process Makes the insert ideally suited to a wide variety of custom hood applications; with easy and secure connection to the ventilation duct
- Single-Blower Ventilation with 640 CFM and 4 Fan Speeds - Provides the power necessary to capture smoke and fumes produced by high-performance cooking equipment
- Control with ADA Compliant Remote-Mount Option -Can be removed and relocated to a more convenient location, such as a wall or countertop
- Blower, Liner and Filters Included No additional components or accesssory kits required
- Two Halogen Lights Provide four levels of illumination over the cooking surface
- Two Stainless Steel Mesh Filters Trap airborne grease particles and can easily be removed for dishwasher-safe cleaning
- Model ZVC30LSS 30" Wide Stainless Steel Hood Insert

