



Pine Mountain®

- YOUR MOUNTAIN RETREAT BEGINS® -

**ExtremeStart™**  
firestarter

## ALL-PURPOSE FIRESTARTING MADE EASY

### GRILLS



1. Place one firestarter flat on grate
2. Arrange 2 lbs. of charcoal into a neat mound leaving arrows exposed†
3. Light the firestarter wrapper at each arrow



Coals are ready when most of the charcoal is grey

† Use one firestarter per 2 lbs. of charcoal

### FIRES



1. Place 2 or 3 pieces of split wood in fireplace or fire pit
2. Place 1 firestarter between wood††
3. Light the firestarter wrapper at each arrow



Allow 15 minutes to achieve full flame

†† Use up to 2 more firestarters when lighting larger amount of wood

## **SAFETY INSTRUCTIONS:**

- 1. Only add one firestarter(s) when the first fire is out.**
- 2. Always open damper before starting a fire and ensure adequate air supply.**
- 3. Ensure you have no downdraft and that your chimney and burn area is clean.**
- 4. Not for use in wood stoves or air tight stoves.**
- 5. Do not use without a grate and a firescreen.**
- 6. Do not add additional wood until the firestarter has been consumed or at least 30 minutes after lighting.**
- 7. This firestarter can become extremely volatile if agitated while burning – do not move, poke, or break up a burning firestarter or wood which has been placed on top of firestarter as it may flare up.**
- 8. If necessary, extinguish with a dry chemical fire extinguisher (UL or ULC Listed Class B) or douse flames with sand.**
- 9. Do not use flammable liquids or fireplace gas log lighters to ignite firelog.**
- 10. Use only to ignite or start charcoal or wood fires.**
- 11. Adult supervision required. Never leave children, disabled persons or pets alone near fire/firelog; nor leave fire unattended.**
- 12. Close damper when ashes are cool. Dispose of ashes properly in a metal can.**
- 13. Clean chimney regularly.**

For United States, this firestarter has been tested by Underwriters Laboratories Inc. for use in factory-built fireplaces. For Canada, this firelog has been designed for brick or heavy gauge metal lined masonry fireplaces, UL or cUL or ULC listed fireplaces, and fireplace inserts having minimum burning areas of 400 sq. in. (0.258 sq. m.). Use in smaller appliances may be hazardous.

This firestarter is made from recycled biomass product such as wood sawdust, ground tree nutshells, and blended wax.

**CALIFORNIA PROPOSITION 65 WARNING:** Combustion of this manufactured product results in the emissions of carbon monoxide, soot, and other combustion by-products which are known by the State of California to cause cancer, birth defects, or reproductive harm.

This product complies with South Coast Air Quality Management District Rule 1174, Ref. C251-JHB-15S  
Use of this and other solid fuels may be restricted at times by law.

Please check 1-877-4NO-BURN or <http://www.8774NOBURN.ORG> before burning.

If your fireplace is functioning properly, emissions of this product should be vented outdoors. A properly installed and maintained fireplace and chimney will dramatically reduce the likelihood of combustion by-products entering your home. An inadequate air supply or a downdraft could cause a fireplace malfunction. If you suspect that your unit is not functioning properly, a qualified contractor should be consulted.

©2015 Hearthmark, LLC dba Jarden Home Brands. All rights reserved.

Distributed by Hearthmark, LLC dba Jarden Home Brands, Fishers, IN 46037.

Hearthmark is a subsidiary of Jarden Corporation (NYSE: JAH).

Learn more about Pine Mountain® Firelogs at [PineMountainFire.com](http://PineMountainFire.com) or call us toll-free at (877)402-5185.