

# Bare Copper



## Soft Drawn Bare Copper Wire

**Meets or Exceeds  
ASTM-B3, ASTM-B8,  
or ASTM-B787**

### APPLICATIONS

For use in overhead transmission and distribution applications. Also for use in grounding applications.

### CONDUCTORS

Solid conductors uncoated copper per ASTM-B3

Stranded conductors 8 AWG - 2 AWG and 250 MCM - 750 MCM uncoated copper per ASTM-B3 and ASTM-B8

Stranded conductors 1 AWG - 4/0 AWG - uncoated copper conductors per ASTM B3 and ASTM-B787

### INDUSTRY STANDARDS

ASTM B3

ASTM B8

ASTM-B787

RoHS Compliant

©2010, Cerro Wire LLC  
All Rights Reserved



MADE IN THE USA

**cerrowire**<sup>®</sup>

Electrical Division: 800.523.3869 | FAX 877.877.9563  
Consumer Markets Division: 866.572.3776 | FAX 812.793.2626  
www.cerrowire.com

A Marmon Wire & Cable/  
Berkshire Hathaway Company

# Bare Copper

## Soft Drawn Bare Copper Wire

PRODUCT CODE NUMBER	AWG SIZE	CLASS B STRAND		APPROX. OVERALL DIAM. INCHES	APPROX. NET WT. LBS./M FT.	UPC CODE
		NO. OF STRANDS	DIAM. EACH INCHES			
050-1600S	12	SOLID	.0795	.0795	19.28	048243334100
050-1800S	10	SOLID	.1002	.0795	30.63	048243334209
050-2000J	8	SOLID	.1285	.1285	50	048243334308
050-2000P	8	SOLID	.1285	.1285	50	048243334360
050-2215I	6	SOLID	.1620	.1620	79	048243334407
050-2200A	6	SOLID	.1620	.1620	79	048243694440
050-2200K	6	SOLID	.1620	.1620	79	048243334438
050-2200P	6	SOLID	.1620	.1620	79	048243334483
050-2400A	4	SOLID	.2043	.2043	126	048243334549
050-2400H	4	SOLID	.2043	.2043	126	048243334544
050-2400J	4	SOLID	.2043	.2043	126	048243334520
050-2400K	4	SOLID	.2043	.2043	126	048243334537
050-2600D	2	SOLID	.2576	.2576	201	048243334605
050-4000J	8	7	.0486	.146	50	048243335008
050-4000K	8	7	.0486	.146	50	048243335237
050-4200K	6	7	.0612	.184	80	048243335138
050-4400H	4	7	.0772	.232	127	048243335206
050-4400K	4	7	.0772	.232	127	048243335237
050-4600D	2	7	.0974	.292	202	048243335404
050-4600K	2	7	.0974	.292	202	048243335435
050-5000K	1/0	19	.0807, .0591	.360	323	048243337637
050-5000J	1/0	19	.0807, .0591	.360	323	048243337620
050-5200J	2/0	19	.0906, .0663	.404	404	048243337729
050-5200K	2/0	19	.0906, .0663	.404	404	048243337736
050-5400J	3/0	19	.1017, .0745	.454	509	048243337828
050-5400K	3/0	19	.1017, .0745	.454	509	048243337835
050-5600J	4/0	19	.1142, .0836	.510	643	048243337927
050-5600K	4/0	19	.1142, .0836	.510	643	048243337934

# Bare Copper

## Soft Drawn Bare Copper Wire

PACKAGE CODE	D	H	I	J	K	P	X*
AWG SIZE	125' SPOOL	200' SPOOL	315' SPOOL	500' SPOOL	1,000' SPOOL	5,000' SPOOL	SPEC CUT REEL
8 SOLID		X				X	X
6 SOLID			X		X	X	X
4 SOLID		X		X	X		X
2 SOLID	X						X
8-7 STR				X	X		X
6-7 STR			X		X		X
4-7 STR		X			X		X
3-7 STR							X
2-7 STR	X				X		X
1-19							X
1/0-19 STR				X	X		X
2/0-19 STR				X	X		X
3/0-19 STR				X	X		X
4/0-19 STR				X	X		X
250-37 STR							X
300-37 STR							X
350-37 STR							X
400-37 STR							X
500-37 STR							X
600-61 STR							X
750-61 STR							X

\* No special cuts less than 50'