



Flex-Vent[®]

MC Air Connector



Non-Insulated Duct

Thermaflex[®] is a global leader in the flexible duct product industry for both commercial and residential HVAC applications.

Flex-Vent MC non-insulated and economically priced flexible connectors are ideal for use in medium to low-pressure A/C systems and in air venting and drying applications. The corrosion resistant spring steel wire helix is laminated with multiple layers of clear and metallized polyester film, fully laminated with adhesive. Oversized for quick installation.

- Reduced total installation cost - fast, economical installation.
- Meets UL 181 and NFPA 90A-90B Fire Codes.
- Easily shaped to fit over all inlets and quickly connects to fast fittings.
- Unique construction will not unravel when cut.



Specifications

Diameter	3-20 inches ID	
Pressure Rating	(WG)	
Positive	10 inches (3"-20" ID)	
Negative	1 inch (3"-12" ID)	1/2 inch (14"-20" ID)
Velocity	5000 FPM	
Temp. Range	-20°F ; 250°F	

Increase productivity and profitability with innovative products by Thermaflex. Contact us today at 1-800-459-4822.



National Sales Headquarters & Customer Service Department
381 Carwellyn Rd. • Abbeville, SC 29620 • 1-800-459-4822 • thermaflex.net