



GREAT STUFF™ BIG GAP FILLER INSULATING FOAM SEALANT

**CRACK DOWN ON ENERGY LOSS.
IMPROVE COMFORT.**



The average home has a half mile of gaps and cracks¹ where air and moisture can enter. Air sealing and insulating projects around the home can typically save homeowners up to 30% on home energy costs, according to the Residential Energy Services Network (RESNET).

Seal out energy loss and improve comfort with GREAT STUFF™ Big Gap Filler Insulating Foam Sealant.²

Reduces air leaks and energy costs.

GREAT STUFF™ Big Gap Filler Insulating Foam Sealant is a ready-to-use, expanding polyurethane insulating foam sealant that fills, seals and insulates gaps up to 3 inches. This specially formulated sealant:

- fills, seals and insulates gaps up to 3 inches
- expands to take the shape of gaps, creating a long-lasting, airtight and water-resistant seal
- helps improve energy efficiency by forming an airtight seal in gaps and cracks
- is a simple way to minimize unwanted air flow and reduce moisture condensation

GREAT STUFF™ Big Gap Filler is a polyurethane foam gap/crack filler for use all around the home.

¹Source: www.energystar.gov

²Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

³Skin of cured foam can discolor if exposed to natural light. Paint or coat foam for best results.

⁴70°F ± 5°F and 50 ± 5% RH, 1 inch bead diameter, 6 inch length. Cure rate is dependant on temperature, humidity and size of foam bead.

Features and benefits at a glance

- Fills, seals and insulates gaps up to 3 inches
- Ready-to-use (straw applicator)
- Forms a long-lasting weathertight seal to minimize drafts
- Forms airtight, water-resistant seal
- Interior/exterior use³
- Adheres to wood, metal, masonry, glass and most plastics
- Tack free in 10-15 minutes⁴; Trims in one hour
- Cures rigid
- Paintable, stainable and sandable
- Cream colored foam
- All-direction dispensing
- UL Classified
- CCMC 13074-L



Where to Use GREAT STUFF™ Big Gap Filler

Use GREAT STUFF™ Big Gap Filler Insulating Foam Sealant to seal gaps up to 3 inches to insulate around common areas of energy loss such as rim joist/sill plate, plumbing, HVAC, etc.



Electrical openings



Hard to reach corners



Sill plate



Pipe penetrations



Rim joist

GREAT STUFF™ Big Gap Filler Insulating Foam Sealant is Cost Effective

- One 12 oz. can = up to 19 tubes of caulk*
- One 20 oz. can = up to 35 tubes of caulk*

*Calculated caulk equivalence based on 10.2 oz tubes of caulk.

Greatness comes in many forms

Did you know that the average home has a 1/2 mile of gaps and cracks?*** Seal them all with GREAT STUFF™

Each GREAT STUFF™ Insulating Foam Sealant* is specially formulated to seal gaps, cracks and holes to block air, moisture and even pests. Our comprehensive line of ready-to-use sealants is a simple, inexpensive money-saving solution for any do-it-yourself homeowner.

- **GREAT STUFF™ Gaps & Cracks*** — Foam sealant that expands to seal and insulate gaps up to one inch.
- **GREAT STUFF™ Window & Door*** — Minimally expanding foam that seals between a window or door and its rough opening.
- **GREAT STUFF™ Fireblock*** — Impedes spread of fire and smoke through service penetrations.***
- **GREAT STUFF™ Big Gap Filler*** — Foam sealant that expands to seal and insulate gaps up to three inches.
- **GREAT STUFF™ Pestblock*** — Blocks pests out of the home by eliminating points of entry.



In the United States

The Dow Chemical Company Dow Building Solutions

200 Larkin Center
Midland, MI 48674

In Canada

Dow Chemical Canada ULC Dow Building Solutions

450 – 1st St. SW
Suite 2100
Calgary, AB T2P 5H1

For Technical Information:

1-866-583-BLUE (2583) (English)
1-800-363-6210 (French)

dowgreatstuff.com

dowgreatstuff.ca

dowbuildingsolutions.com

For Sales Information:

1-800-232-2436 (English)
1-800-565-1255 (French)

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS), call Dow at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood-burning stoves, gas stoves and gas dryers, are properly vented to the outside. In Canada visit: <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>.

GREAT STUFF™ Insulating Foam Sealants contain isocyanate and a flammable blowing agent. Read all instructions and (M)SDS carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and goggles or safety glasses. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as between walls and under tub surrounds.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

* Read all instructions and (Material) Safety Data Sheet ((M)SDS) carefully before use.

** www.energystar.gov

*** Intended for use in residential applications to maintain the continuity of an approved fire block material.

©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

Printed in the U.S.A.