

HIGH DEFINITION 1080p SECURITY CAMERA



VIEW YOUR WORLD IN TRUE HD

Keep an eye on your home or business day or night with this high definition 1080p security camera with long range night vision.

FEATURES:

- True HD 1080p Image Sensor ¹
- Infrared cut filter ensures accurate color representation
- Night vision range up to 130ft (40m) in ambient lighting & 90ft (28m) in total darkness ²
- Close up recognition in the dark with SmartIR
- Anti-glare feature ensures clear images under strong lighting conditions
- ClearNight imaging for superior low light performance, improving recording efficiency

130/90FT Night Vision 1080P Resolution Indoor/outdoor

- Split glass design minimizes IR reflection
- Weatherproof for outdoor & indoor installation (IP66 Rated) ³
- Extreme temperature performance (-22° ~ 140°F / -30° ~ 60°C)
- 90° field of view
- Vandal resistant design with cable pass-through bracket
- Lightweight and durable polycarbonate housing
- Versatile ceiling or wall mounting options
- Residential and business friendly compact design

LBV2521 Series

40/28_м

www.lorextechnology.com



HIGH DEFINITION 1080p SECURITY CAMERA


Product Information

LBV2521	6-95529-00497-6	Image Sensor
Package Weight:	1.7lbs / 0.8kg	Video Format
Package Dimensions:	12.4 × 4.5 × 4.1	Effective Pixels
(W x D x H)	315 × 115 × 103mm	Resolution
Package Cube:	0.1cft / 0.004cbm	Scan System
Contents:	1 × indoor / outdoor camera, 1 × mounting kit, 1 × 60ft (18m) UL-compliant BNC / power extension cable, 1 × NA power adapter	Sync System S/N Ratio
LBV2521B	6-95529-00287-3	Iris
Package Weight:	1.7lbs / 0.8kg	AES Shutter Speed
Package Dimensions:	9.1 × 5.7 × 4.8"	Min. Illumination
(W x D x H)	230 × 145 × 123mm	· Video Output
Package Cube:	0.1cft / 0.004cbm	Lens / Lens Type
Contents:	1 × indoor / outdoor camera, 1 × mounting kit, 1 × 60ft (18m) UL-compliant BNC / power extension cable, 1 × NA power adapter	Field of view (Diagonal)
LBV2521P	6-95529-00509-6	: Termination
Package Weight:	1.7lbs / 0.8kg	· IR LED Qty / Type
Package Dimensions:	12.4 × 4.5 × 4.1	Night Vision Range
(W x D x H)	315 × 115 × 103mm	Power Requirement
Package Cube:	0.1cft / 0.004cbm	Power Consumption
Contents:	1 × indoor / outdoor camera, 1 × mounting kit, 1 × 60ft (18m) UL-compliant BNC / power extension cable, 1 × EU/UK power adapter	Operating Temp. Range
		Operating Humidity Rang
LBV2521PK2B	6-95529-00575-1	Environmental Rating
Package Weight:	3.0lbs / 1.3kg	Weight (including stand)
Package Dimensions: (W x D x H)	10.3 × 7.0 × 5.8" 260 × 178 × 146mm	Installation
Package Cube:	0.24cft / 0.03cbm	ווזגומנומנוטו
Contents:	2 × indoor / outdoor cameras, 2 × mounting kits, 2 × 60ft (18m) UL-compliant BNC / power extension cables, 2 × NA power adapters	BNC Termination
LBV2521PK4B	6-95529-00288-0	
Package Weight:	5.9lbs / 2.7kg	··· P
Package Dimensions: (W x D x H)	13.4 × 6.7 × 7.6" 340 × 170 × 193mm	
Package Cube:	0.4cft / 0.01cbm	Dimension
Contents:	4 × indoor / outdoor cameras, 4 × mounting kits, 4 × 60ft (18m) UL-compliant BNC / power extension cables, 1 × NA multi-camera	


Specifications

mage Sensor	1/2.7" 1080p, 2 Megapixel Image Sensor
/ideo Format	NTSC / PAL ⁴
Effective Pixels	H: 1930 V: 1088
Resolution	1080p @ 30FPS/25FPS
Scan System	Progressive
Sync System	Internal
S/N Ratio	53dB (AGC Off)
ris	AES
AES Shutter Speed	1/60 (1/50) ~ 1/100,000 Sec.
1in. Illumination	0.2 Lux without IR LED / 0 Lux with IR LED
/ideo Output	MPX
ens / Lens Type	3.6mm F2.1 / Fixed
Field of view (Diagonal)	90°
Termination	BNC Type
R LED Qty / Type	12 pieces / 850nm
light Vision Range	130ft (40m) / 90ft (28m)
Power Requirement	12V DC ±10%
Power Consumption	Max. 220mA (with IR)
Operating Temp. Range	–22° ~ 122°F / –30° ~ 50°C
Operating Humidity Range	< 95% RH
Environmental Rating	IP66 (Indoor / Outdoor) ³
Neight (including stand)	0.3lbs/0.1kg

nstallation Diagram



Dimensions



Disclaimers

- 1. 1080p MPX cameras are compatible with 1080p MPX DVR recorders only. For a list of compatible recorders please visit lorextechnology.com/support.
- 2. Stated IR illumination range is based on ideal conditions in typical outdoor night time ambient lighting and in total darkness. Actual range and image clarity depends on installation location, viewing area, and light reflection / absorption level of object. In low light, the camera will switch to black and white.
- 3. Not intended for submersion in water. Installation in a sheltered location recommended.
- 4. NTSC (LBV2521 / LBV2521B / LBV2521PK2B / LBV2521PK4B); PAL (LBV2521P).

power adapter

Lorex Corporation, a division of FLIR Commercial Systems Inc.

Canada L3R 3S1

21075 USA

www.lorextechnology.com

© 2015 Lorex Corporation