



## Bathroom Sink Installation Instructions

### Before you Start

- ECOSINKS products should be installed by professional installers.
- All sinks are hand crafted, dimensions may vary; we recommend using the actual basin for the cut-out.
- We recommend making a template out of Kraft paper and testing the template prior to marking cutting.
- Use 100% Silicone (non-water based) for all installations.
- Make sure a watertight seal exists on all drain connections.
- **Please do not use any abrasive cleaners on ECOSINKS products. Non-Antibacterial soap and water is recommended. Review Cleaning and Care manual for further detail.**

### Under-Mount or Drop-In Installation

- Use the actual sink as template. Place sink upside down on paper template and trace edge of sink. Leave space for Faucets or other accessories.
- Attach a pencil to a long stick. With sink still face down on paper trace inside edge of sink thru drain hole.
- **Cut out paper Template and test to insure accuracy.**
- Choose your installation type: Drop-In or Under-Mount
  - Drop-In
    - With sink upside down, place cut out template on sink and verify fit. Maximum gap should be ¼.
    - Once template is acceptable trace line on countertop and cut to line.
    - Temporarily place basin in hole to verify tight fit.
    - Apply silicone inside hole on inside corner and place sink in hole.
  - Under-Mount
    - With sink right side up, place cutout template on sink and verify fit.
    - Once template is acceptable trace line on countertop and cut to line.
    - Apply silicone around hole on the underside of countertop and position sink.
    - Use under-mount clips if needed
- Unsure that sink is level in all areas, and press down to secure sink.
- Remove any excess silicone
- Let sit for 24 hours
- Install drain; follow drain installation instructions

### Vessel Installation

- Measure outside perimeter of drain opening and mark countertop
- Cut countertop for drain opening
- Place basin on top of countertop and make sure that the drain hole is sitting down inside countertop.
- Make sure sink is level at all points, front to back and side to side
- The hold down nut of the drain pipe will secure the sink to the countertop
- Recommend placing a small bead of silicone to seal in-between the outside edge of the sink where it is mounted to the countertop.

**Please to not use abrasive chemicals when cleaning up after installation. Use Soap, Water and soft cloth to clean sink surface.**