

Sprinkler HEAD PATCH

DESCRIPTION (Speed, Perfection and Longevity)	Patented PVC fiber composite material patches that is 5 inches in diameter, .011". Head Patch is packaged in bags of 20 per bag 5 bags per case, 100 per case and 100 per box 5 boxes per case. Head Patch is a drywall patch used for sprinkler head relocation and repair. Pre-cut to fit standard sprinkler head receptacles for easy use. Head Patch makes repairs strong, fast and easy. Same high-tech composite material as Strait-Flex.
ADVANTAGES	<ul style="list-style-type: none"> • Fast, durable and low cost • Easy installation, material is pre-cut to fit standard sprinkler head receptacles for easy adjustments • Will not sag • Material is not affected by water and damp conditions • Material can be second coated immediately • Requires very light fill coat to finish product • Will not fuzz-up during sanding like competitive fiber-glass-metal patches • Waterproof, rustproof • Average time for patch is 5-7 minutes
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
DIRECTIONS	<ul style="list-style-type: none"> • Prepare surface by cleaning and lightly sand area around sprinkler pipe. • Apply 1/4" of quick set or drywall compound directly to Head Patch. Flip over patch and position Head Patch around copper Head and wipe down, removing excess compound between patch and drywall. Compound remains on back side of Head Patch in damaged or mis-cut areas makes Head Patch very rigid. • Apply second coat, let dry and sand. Head Patch will not fuzz up during sanding like competitive fiber glass-metal patches
STORAGE	Store in dry place protected from moisture

Submittal Approvals:

Job Name:	
Contractor:	Date: