




# Window & Door/All-Purpose Sealants



## DAP® 3.0™ All-Purpose Advanced Sealant with Kwik Dry® Technology

**Description:** DAP® 3.0™ is an advanced, low-VOC all-purpose sealant specially formulated with Kwik Dry® Technology allowing it to be exposed to water after just 3 hours without washing out. It won't crack or shrink and provides excellent adhesion, flexibility and durability for a permanently waterproof seal.

**Applications:** Ideal for sealing windows, door frames, corner joints, siding, trim, butt joints, baseboards, molding, pipes, ducts and vents.

**Adheres to:** Wood, metal, brick, glass, vinyl, aluminum, concrete, masonry, plaster, drywall, stucco, stone and painted surfaces.

**Water Exposure:** 3 hours

**Clean Up:** Solvent

**Paintable:** Yes

**Use:** Interior & exterior

**Flexibility:** Best

**Application Temperature Range:**

-35°F to 140°F

**Resists Mildew:** Cured sealant is mold & mildew resistant



## DYNAFLEX 230® Premium Indoor/Outdoor Sealant

DAP® DYNAFLEX 230® Premium Waterproof & Paintable Sealant combines outstanding durability, adhesion and flexibility with easy tooling, paintability, low odor and water clean up. Exceeds ASTM Specification C 920, Class 25 & ASTM C 834, Type C, Grade NS.

Ideal for caulking & sealing windows, doors, corner joints, siding, trim and molding.

Wood, metal, brick, aluminum, glass, concrete, vinyl, masonry, most plastics, plaster, drywall, stucco, stone and painted surfaces.

**Water Exposure:** 24 hours

**Clean Up:** Water clean up

**Paintable:** Yes

**Use:** Interior & exterior

**Flexibility:** Best

**Application Temperature Range:** 40°F to 100°F

**Resists Mildew:** Cured sealant is mold & mildew resistant



## DAPTEx® Plus™ Window & Door Foam Sealant

DAPTEx® Plus™ Window & Door Foam Sealant is designed to meet the tough standards demanded by professional installations while effectively sealing large cracks, gaps and voids without over expanding. This high-performance sealant is formulated with CoVinyl-X9000® for superior weather resistance plus added toughness and durability. When applied properly, this patented formula helps reduce energy loss and damage that can be caused by rain and pest infiltration.

For sealing, filling & insulating cracks & gaps around windows, doors, ducts, pipes, vents and electrical box perimeters.

Wood, concrete, brick, vinyl, steel and aluminum.

**Water Exposure:** Not applicable

**Clean Up:** Water clean up

**Paintable:** Yes

**Use:** Interior & exterior

**Flexibility:** Yes

**Application Temperature Range:** 45°F to 105°F

**Resists Mildew:** Not applicable



\* **Note:** For applications on masonry, brick & concrete, surface must be dry to obtain maximum adhesion. Please read product label and Technical Data Bulletins for additional information and instructions.

**QUESTIONS:** For more information call the DAP Help Line at 888-DAP-TIPS or visit [www.dap.com](http://www.dap.com).



You'll find us in all the right places.®

An RPM Company