







DAP® 3.0™ Window, Door, Trim & Siding

High Performance Sealant

DYNAFLEX 230®

Premium Indoor/Outdoor Sealant

Alex Fast Dry®

Acrylic Latex Caulk Plus Silicone Sealant

Description: The newly formulated DAP® 3.0TM Window, Door, Trim & Siding sealant is paintable in 30 minutes which helps complete the job faster and saves time. In addition, DAP® 3.0™ is 100% waterproof and is water resistant in 30 minutes which reduces the risk of ruining the caulk job by getting it wet too early from incidental rain or water contact. For exterior projects, you can seal up gaps and cracks just 30 minutes before rain is forecasted. Also, DAP® 3.0™ offers extreme temperature use so it can be applied in temperatures ranging from 20°F to 120°F. It's available in White and Crystal Clear, which offers superior clarity that allows the beauty of the surface to shine through the sealant.

DAP® DYNAFLEX 230® Premium Waterproof & Paintable Sealant combines outstanding durability, adhesion and flexibility with easy tooling, paintability, low odor and water clean up. Exceeds ASTM Specification C920, Class 25 & ASTM C834, Type C, Grade NS.

For a professional-looking paint job, caulk before you paint, and when time is short, reach for ALEX Fast Dry®. It's ready to paint in 40 minutes. No need to worry about paint cracking; this durable, flexible sealant is made to last and comes with a 35 Year Durability Guarantee. Easy water clean-up. Interior/exterior use. Exceeds ASTM **Specification C834.**

Applications: Ideal for sealing windows, door frames, corner joints, siding, trim, butt joints, baseboards,

molding, pipes, ducts and vents.

Ideal for caulking & sealing windows. doors, corner joints, siding, trim and molding.

Ideal for caulking and sealing window and door frames, eaves, baseboards, pipes, molding, vents, siding/trim, corner joints and ducts.

Adheres to: Wood, metal, brick, glass, vinyl, aluminum, concrete,

masonry, plaster, drywall, stucco, stone and painted surfaces.

Wood, metal, brick, aluminum, glass, concrete, vinyl, masonry, most plastics, plaster, drywall, stucco, stone and painted surfaces.

Wood, brick, drywall, metal, painted surfaces. concrete/stone, glass, plaster and most common building materials.

Water Exposure: 30 minutes

Clean Up: Solvent Paintable: Yes (30 minutes)

Yes **Use: Interior & exterior**

Water clean up Water clean up Yes (40 minutes)

Interior & exterior Interior & exterior

Flexibility: Best **Application**

Temperature Range: 20°F to 120°F

40°F to 100°F

24 hours


Best

Resists Mildew: Cured sealant is mold & mildew resistant **Cured sealant is mold & mildew resistant**

40°F to 100°F

24 hours

Best










Cured sealant is mold & mildew resistant

QUESTIONS: For more information call the DAP Help Line at 888-DAP-TIPS or visit www.dap.com.



^{*} Note: For applications on masonry, brick & concrete, surface must be dry to obtain maximum adhesion. Please read product label and Technical Data Bulletins for additional information and instructions.