



## Deck Wash

No. 61

- Safe for All Deck Finishes
- Ready-To-Use
- Ideal for Wood & Composite Surfaces

**CAUTION:** Stained surfaces may become slippery when wet. Use Caution.

### WHERE TO USE

- Ideal for the Maintenance Cleaning of Exterior Wood, Vinyl or Composite Decks, Porches, Fences & Siding.

### PREPARATION† (The following steps are recommended for best results.)

- Dampen grass, plants, & other vegetation with water. Wear old clothing, protective eyewear & rubber gloves.
- One quart of product will clean 500-600 sq. ft. (46-56 m<sup>2</sup>).

### APPLICATIONS

- Remove tab, turn nozzle to "WATER" position and wet entire surface to be cleaned. Turn nozzle to "ON" and apply product liberally.
- Allow product to work for at least five minutes. Do not allow product to dry on the surface.
- Rinse thoroughly with water.
- Scrubbing may be required on severely stained surfaces. (Mildewed areas may require BEHR® No. 62 Premium Mildew Stain Remover.)
- Prevent rinse solution from entering storm drain.

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets Behr's manufacturing specifications when applied in accordance with the label directions. If this product fails to meet these specifications, Behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. This warranty is made to the original residential product purchaser and is not transferable. **This guarantee excludes (1) labor and the costs of labor for the application or removal of any product and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) 2.5 WT. % • REV. 2/08

**CAUTION! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING.** If you experience eye watering, headaches or dizziness, increase fresh air and use a properly fitted respirator (NIOSH approved for organic vapor with P Series particulate prefilter). Obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.  
**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



## Premium, Deck, Fence & Siding Mildew Stain Remover

No. 62

- Removes Severe Stains Caused By Mold,
- Mildew, Algae & Fungus Without Damaging Wood
- Biodegradable & Easy Water Clean-Up

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

##### EXTERIOR:

- Use on stains caused by mold, mildew, algae & fungus. Does not contain bleach and will not damage wood surfaces.
- Use full strength on: Exterior Mildewed Surfaces of all types including Wood, Concrete, Masonry, Stucco, Stone, Brick, Vinyl and Aluminum Siding, Composite, Tile, Plastic, Fiberglass and Roofing materials.
- Use BEHR® NO. 63 PREMIUM 2-IN-1 WOOD PREP after application to remove mill glaze, condition the wood surface prior to applying a stain or finish, and to neutralize and restore natural wood color. Follow all label instructions.

##### INTERIOR:

- Use a diluted solution on: Interior Mildew Stained Surfaces, Bathroom and Kitchen areas, and Woodwork.

**CAUTION:** Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

#### PREPARATION† (The following steps are recommended for best results.)

- Dampen the work surface prior to application.
- Shake thoroughly before use.
- Wear protective clothing, goggles and chemical resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge.
- Protect clothing from contact with liquid.
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Test a small area, rinse and let dry before continuing.
- Prevent all rinse solution from entering storm drains.

#### APPLICATIONS

##### EXTERIOR:

- Use product at full strength.
- Apply using a pump sprayer, brush, mop, or roller. Scrub the surface using a stiff bristle broom or scrub brush. One gallon of product will treat 200-250 sq. ft. (19-23 m<sup>2</sup>).
- Allow product to work for at least one minute to remove mildew stains.
- Do not allow product to dry on surface.

- Rinse surface and surrounding area thoroughly with water from garden hose using nozzle at normal pressure, or use pressure washer at low setting (500-1200 PSI). DO NOT USE HIGH PRESSURE as this may harm wood. Prolonged exposure on painted surfaces may damage finish.

##### INTERIOR:

- Product must be diluted with one part BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER to three parts water (1:3 dilution).
- DO NOT USE FULL STRENGTH.
- Avoid contact with clothing, carpet and fabrics.
- Apply using a clean cloth or sponge.
- Thoroughly rinse the surface with fresh water. Prolonged exposure on painted surface may damage finish.

#### CLEAN UP AND STORAGE

- Rinse all equipment with water before storage or reuse.
- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection. Do not transfer to food and beverage containers.

**\*LIMITED WARRANTY:** BEHR PROCESS CORPORATION warrants that this product meets behr's manufacturing specifications. If this product does not meet these specifications, behr will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**CAUTION. IRRITANT.** MAY CAUSE EYE AND SKIN IRRITATION. PROLONGED INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. **FIRST AID:** In case of eye or skin contact, flush immediately with water for 20 minutes. In case of ingestion, do not induce vomiting. Drink plenty of water and get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN—DO NOT TAKE INTERNALLY.**



## Premium, Deck, Fence & Siding 2-in-1 Wood Prep

No. 63

- Cleans & Brightens Wood Surfaces
- Removes Stains caused by Mold, Mildew, Algae & Fungus
- Biodegradable & Easy Water Clean-Up

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Exterior Wood & Composites, Siding, Shakes, Shingles, Fences and Patio Furniture, Vinyl and Aluminum Siding, Masonry, Stucco and Concrete.
- Brightens and conditions exterior wood.
- Removes stains caused by mold, mildew, algae and fungus.
- Removes rust & red clay stains.
- Neutralizes wood surface to restore natural color.
- Removes mill glaze on new wood.
- Extremely effective in removing discoloration caused by tannin bleed. Must be applied after BEHR® NO. 64 PREMIUM STAIN & FINISH STRIPPER when removal of old finish is required.

**CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

#### PREPARATION† (The following steps are recommended for best results.)

- Be sure to have the following: source for tap water, garden hose with nozzle, large plastic mixing container, stiff bristle broom or brush and protective plastic drop cloths. Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge.
- Use BEHR NO. 62 Premium MILDEW STAIN REMOVER where severe stains caused by mildew, algae, or fungus are present and cannot be removed with BEHR NO. 63 Premium 2-In-1 Wood Prep. Follow all label instructions.
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Prevent all rinse solution from entering storm drains.

#### APPLICATIONS

- Shake product thoroughly.
- Be sure that the plastic mixing container is large enough to hold up to 5 gallons of diluted solution. **DO NOT MIX IN METAL CONTAINER.**
- Dilute one part BEHR NO. 63 Premium 2-In-1 Wood Prep with 4 parts tap water (1:4 dilution) in a clean plastic container. One gallon of diluted solution will clean, brighten and condition up to 200 sq. ft. (19 m<sup>2</sup>).
- For best results on wood surfaces prone to tannin bleed, such as redwood and cedar, use a 1:1 diluted solution.
- **To remove rust, red clay stains and for extremely hard to clean weathered wood surfaces, use product full strength.**

- Test solution in a small, hidden area before applying to see its effectiveness.
- Do not apply product if surface and air temperatures are below 50°F (10°C) or above 90°F (32°C).
- Dampen surfaces with water prior to cleaning.
- Apply solution liberally with a plastic container pump sprayer, brush, mop or roller.
- Keep the surface wet for 10-15 minutes.
- Re-apply solution as needed to keep the surface wet. Scrub surface using a stiff bristle broom or brush. The solution will foam.
- After the 10-15 minute cleaning period, rinse thoroughly with water from garden hose at normal pressure, or use a pressure washer at low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm the wood. Surfaces other than wood may be dulled if not rinsed off quickly.
- On new wood use NO. 63 to remove mill glaze and open the pores of the wood.

#### CLEAN UP AND STORAGE

- Rinse all equipment with water before storage or reuse.
- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection. Do not transfer to food and beverage containers.

**\*LIMITED WARRANTY:** BEHR PROCESS CORPORATION warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**DANGER! CORROSIVE. WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED.** CONTAINS OXALIC ACID SOLUTION (LESS THAN 10%). MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. NOTICE: Do not mix BEHR NO. 63 Premium 2-In-1 Wood Prep with chlorine bleach or with any other household or industrial cleaning product or detergent. Mix only in plastic containers. Use with adequate ventilation. Only use this product outdoors. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **First Aid:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) 1 WT. % • REV. 2/08



## Premium Deck, Fence & Siding Stain & Finish Stripper

No. 64

- Removes Oil & Latex Finishes, Including Sealers, Waterproofers and 100% Acrylic Stains
- Biodegradable
- Easy Water Clean-Up

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Exterior latex, oil-based and 100% acrylic coatings on Wood Decks, Siding, Fences, Shakes and Shingles.
- Removes loose wood fibers without sanding.
- Ideal for unsightly stains caused by oil or rusty water on uncoated Tile, Concrete, Masonry, Stucco, Stone, and Brick.  
Not for interior use or on aluminum surfaces. May harm bare metal or painted surfaces

**CAUTION:** Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

#### PREPARATION† (The following steps are recommended for best results.)

- STIR OR SHAKE WELL BEFORE USE. DO NOT THIN PRODUCT.
- Be sure to have the following: source for tap water, garden hose with nozzle, plastic sprayer or disposable brush, stiff bristle broom or brush and BEHR® NO. 63 Premium 2-IN-1 WOOD PREP.
- Surface must be dry. Do not apply in direct sunlight or on hot surfaces. Use product when air and surface temperatures are between 50-90°F (10-32°C).
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge.
- Test in a small area for effectiveness, rinse and let dry before continuing.
- Prevent all rinse solution from entering storm drains.

#### APPLICATIONS

- Apply BEHR NO. 64 PREMIUM STAIN & FINISH STRIPPER liberally using a nylon/poly brush or roller. Natural bristle brushes or lambs wool applicators are not recommended.
- Do not allow product to dry on wood; keep surface wet by misting with water and re-apply BEHR NO. 64 PREMIUM STAIN & FINISH STRIPPER if drying occurs. Finish will begin to lift from the surface. Repeat process as needed to keep the surface wet during the removal period. Most deteriorated finishes will start to lift after about 5-45 minutes. The coating should easily rinse off when ready.
- When the finish starts to lift, lightly scrub the surface using a stiff bristle broom or brush.

- Rinse thoroughly with water from garden hose using nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm the wood.
- If some of the old finish remains on the surface, repeat application procedure or spot sand as needed.
- Use at a rate of approximately 50-150 sq. ft. (4-14m<sup>2</sup>) per gallon, depending on porosity and condition of surface.
- Some woods may darken after stripping. Use BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP on all wood surfaces to remove stains caused by mildew, rejuvenate natural wood color and neutralize the stripping action. Follow all label instructions. This provides stability for reapplication of a new finish or sealer.
- Surface dry time will vary, depending on air & surface temperature.
- Make sure surface is visually and completely dry to touch prior to recoating.

#### DRY TIME

- Before applying a coating, allow a minimum of 24 hours in warm, dry weather or longer in cool temperatures and/or high humidity.
- Surfaces must be thoroughly dry before applying any type of new finish, except those finishes that can be applied to dampened wood.

#### CLEAN UP AND STORAGE

- Rinse all equipment with water before storage or reuse.
- Clean with soap & water.
- Properly dispose of all soiled rags and protect unused product from freezing.
- To recycle or properly dispose of product in your community call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

† **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**\*LIMITED WARRANTY:** BEHR Process Corporation warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**DANGER! CORROSIVE. WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS SODIUM HYDROXIDE. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION.** Only use this product outdoors. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**





## Concrete & Masonry Cleaner/Degreaser

No. 990-N

- Powerful Multi-Purpose Cleaner
- Removes Severe Household Stains
- Biodegradable & Easy Water Clean-Up
- Makes Up To 5 Gallons

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Use on Interior/Exterior surfaces such as: Garage Floors, Driveways, Patios, Walkways, Porches, Basement Floors and Pool/Cool Decks. Great on Concrete, Brick, Stone, Asphalt and Exposed Aggregate.
- Extremely effective when used full strength to remove greasy, oily stains such as transmission fluid and anti-freeze caused by automobiles, motorcycles and bicycles. Use a diluted solution on lightly stained and soiled areas.
- Ideal for removing algae stains, mildew stains, dirt and most fluids from concrete surfaces.

**CAUTION:** Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

#### PREPARATION† (The following steps are recommended for best results.)

- Wipe up all excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on surface.
- **Test Patch:** Conduct a small test patch in an inconspicuous area to ensure product performance.
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Prevent all rinse solution from entering storm drains.

#### MIXING

- Do not mix BEHR® NO. 990-N CONCRETE & MASONRY CLEANER/DEGREASER with bleach, household or industrial cleaning products or detergents. Mix only in plastic containers.
- DO NOT MIX IN A METAL CONTAINER. Use a plastic mixing container, large enough to hold up to 5 gallons of diluted solution.
- Use BEHR® CONCRETE & MASONRY CLEANER/DEGREASER full strength for tough stains. For general cleaning, add 1 quart cleaner in 1 gallon of water (1:4 dilution). For cleaning previously painted surfaces, add 1 cup cleaner in 1 gallon of water (1:16 dilution). Stir diluted solution thoroughly. Avoid splashing.

#### APPLICATION

- Wear protective clothing, goggles and acid resistant rubber gloves & boots.
- One gallon of diluted solution will clean and degrease up to 500 sq. ft. (47 m<sup>2</sup>) and one gallon of full strength will cover 150 sq. ft. (14 m<sup>2</sup>). Actual coverage will depend on method of application, texture and surface porosity.

**LIMITED WARRANTY:** BEHR PROCESS CORPORATION warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) 3.7 WT. % • REV. 2/08

- Wet the surface first by spraying with a garden hose. Then apply the product (full strength for tough stains, diluted for general cleaning) and work into the surface with a stiff bristled, non-metal brush or broom.
- For best results, use a plastic watering can or plastic pump sprayer to evenly distribute product.
- Allow product to stand for 10-20 minutes then scrub vigorously.  
**NOTE:** Heavily stained areas or older stains may require an additional application.
- After application, be sure to thoroughly saturate surrounding grass and plants with fresh water.
- Rinse surface thoroughly with fresh water while scrubbing at the same time to properly remove all remaining residue. Pressure wash for best results. Remove excess water with a non-metal squeegee or mop.

#### CLEAN UP

- Thoroughly rinse all surfaces, clothing and tools with fresh water after use.
- If product accidentally comes in contact with painted or finished surfaces, rinse immediately with fresh water. It will damage automobile finishes if not rinsed.
- For disposal of empty containers and unused product call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**DANGER! CORROSIVE! WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED.** CONTAINS POTASSIUM HYDROXIDE. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**



## Concrete & Masonry Cleaner/Etcher

No. 991-N

- Prepares Surface for Painting or Staining
- Removes Grease, Oil & Auto Fluid Stains
- Biodegradable & Easy Water Clean-Up
- Removes Rust & Red Clay Stains

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Use on Interior/Exterior uncoated surfaces such as: Garage Floors, Driveways, Walkways, Patios, Pool/Cool Decks, Basement Floors and Concrete Walls.
- Removes grease, oil, auto fluids, rust and red clay stains.
- DO NOT USE ON MARBLE, GRANITE, TERRAZZO, COLORED CONCRETE, BRASS, BRONZE or COPPER.
- NOTE: If etching is not desired, use BEHR® NO. 990-N CONCRETE & MASONRY CLEANER/DEGREASER.

**CAUTION:** Sealed surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

#### PREPARATION† (The following steps are recommended for best results.)

- New concrete must cure for a minimum of 30 days.
- Wipe up all excess oil and grease spills.
- Scrape and sweep away dirt and loose contaminants on the surface.
- Completely strip all existing coatings prior to use. Be sure to rinse thoroughly before treating with BEHR NO. 991-N CONCRETE & MASONRY CLEANER/ETCHER.
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Prevent all rinse solution from entering storm drains.

#### MIXING

- DO NOT MIX IN A METAL CONTAINER. Use a plastic mixing container, large enough to hold up to 2 gallons of diluted solution.
- Use full strength on hard to clean interior/exterior stained surfaces and smooth concrete. Always work in a well-ventilated area.
- For new and lightly stained concrete or to etch galvanized metal, use a diluted solution of 1 part NO. 991-N to 1 part water (1:1 dilution).
- Stir diluted solution thoroughly. Avoid splashing.

#### APPLICATION

- Wear protective clothing, goggles and acid resistant rubber gloves & boots.
- Avoid splashing. Spraying is not recommended.
- One gallon of full strength product will etch and clean 150-200 sq. ft. (14-18 m<sup>2</sup>). One gallon of diluted solution will etch and clean 300-400 sq. ft. (28-37 m<sup>2</sup>). Actual coverage depends on porosity and severity of surface.
- For best results, use a plastic watering can to evenly distribute product or spread product using a stiff bristled, non-metal brush or broom.
- On sloped surfaces, start at the lowest point working up to the highest point.
- **Apply BEHR NO. 991-N CONCRETE & MASONRY CLEANER/ETCHER to a dry surface for best results.**
- Allow product to stand for 10-20 minutes then scrub vigorously.
- Do not let product dry on the surface.
- Rinse surface thoroughly with fresh water while scrubbing at the same time to properly remove all remaining residue. Pressure wash for best results. Remove excess water with a non-metal squeegee or mop.  
**NOTE:** Heavily stained areas or older stains may require an additional application.
- The surface is ready when it feels like medium grit sandpaper and no residue or loose concrete remains on the surface.

#### CLEAN UP

- Thoroughly rinse all surfaces, clothing and tools with fresh water after use.
- For disposal of empty containers and unused product call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).
- If product comes in contact with painted or finished surfaces, rinse immediately with fresh water.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**LIMITED WARRANTY** BEHR PROCESS CORPORATION warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V) 0 WT. % • REV. 2/08

**DANGER! CORROSIVE! WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED.** CONTAINS ORGANIC SALT. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.  
**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY**