



## PREMIUM PLUS® Exterior Flat No.4050



Exterior Flat is a traditional matte sheen that is the perfect choice for all climatic conditions. This 100% acrylic latex, mildew-resistant finish offers improved hiding for greater coverage, is ideal for wood siding, vinyl, aluminum, masonry, brick, stucco, fences and garage doors. The ultimate in durability and backed by a lifetime guarantee\*.

### Where To Use

Previously painted or primed Exterior surfaces. Ideal for Wood Siding, Vinyl, Aluminum, Brick, Masonry, Stucco, Fences & Garage Doors.

### Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Etch galvanized metal, rinse thoroughly. Wash and rinse all other bare metal, allow to dry.

Powerwash exterior surfaces to remove chalk.

Remove all dust with a damp cloth, allow to dry.

Allow new stucco, plaster and masonry to cure for 30 days before priming.

### Prime

Use a product such as BEHR WATER-BASED PRIMER & SEALER NO. 436 or a product such as BEHR OIL-BASED PRIMER & SEALER NO. 434. For optimal color development, better hide and to reduce the number of topcoats with deep colors denoted with a dagger (†) on the color chip, apply a custom tinted primer.

### Application

Use product when the surface and air temperatures are between 50-90°F (10-32°C).

Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity.

Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip).

Coverage is 250-400 sq. ft. (23-37 m<sup>2</sup>) per gallon depending on the surface texture, porosity and application method.

Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

Certain colors may require more than one coat for complete hide.

### Dry Time

Dries to touch in 2 hours at 77°F (25°C) and 50% humidity, re-coat in 4 hours.

Darker colors may require additional dry time between coats.

Longer dry time required in cooler temperatures and in higher humidity.

After 2-4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

Dry paint film is mildew resistant.

### Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

**\*LIMITED LIFETIME GUARANTEE**  
BEHR PROCESS CORPORATION GUARANTEES THAT THIS PAINT MEETS THE FOLLOWING STANDARDS WHEN APPLIED AND CARED FOR ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PAINT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

**Ultimate Durability** – The dried paint film resists peeling, blistering, fading and mildew growth, providing a scrubbable and washable finish from which you can easily remove stains and dirt. **Outstanding Hide and Coverage** – Assured when applied according to label directions. **Complete Color Selection** – Specifically formulated to achieve a full range of pure, clean colors available through computerized color matching. If this paint fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new paint to you, or refund the purchase price of this product. This guarantee excludes (1) labor and costs of labor for the application or removal of any paint and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Exterior Paint Guide for additional tips or visit us at [www.behr.com](http://www.behr.com) for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**





## PREMIUM PLUS® Exterior Satin Enamel No.9050

Formulated with 100% acrylic latex, Exterior Satin Enamel features a pearl-like sheen, making it ideal for wood siding, doors, trim, railing, shutters, overhangs and outdoor furniture. This mildew-resistant finish offers improved hiding for greater coverage and provides ultimate durability. Backed by a lifetime guarantee\*, it is the perfect choice for all climatic conditions.



### Where To Use

Previously painted or primed Exterior surfaces. Ideal for Wood Siding, Vinyl, Aluminum, Brick, Masonry, Stucco, Doors, Windows, Trim, Shutters, Fences, Garage Doors and Outdoor Furniture.

### Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Etch galvanized metal, rinse thoroughly. Wash and rinse all other bare metal, allow to dry.

Powerwash exterior surfaces to remove chalk.

Remove all dust with a damp cloth, allow to dry.

Allow new stucco, plaster and masonry to cure for 30 days before priming.

### Prime

Use a product such as BEHR WATER-BASED PRIMER & SEALER NO. 436 or a product such as BEHR OIL-BASED PRIMER & SEALER NO. 434. For optimal color development, better hide and to reduce the number of topcoats with deep colors denoted with a dagger (†) on the color chip, apply a custom tinted primer.

### Application

Use product when the surface and air temperatures are between 50-90°F (10-32°C).

Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity.

Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip).

Coverage is 250-400 sq. ft. (23-37 m²) per gallon depending on the surface texture, porosity and application method.

Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

Certain colors may require more than one coat for complete hide.

### Dry Time

Dries to touch in 2 hours at 77°F (25°C) and 50% humidity, re-coat in 4 hours.

Darker colors may require additional dry time between coats.

Longer dry time required in cooler temperatures and in higher humidity.

After 2-4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

Dry paint film is mildew resistant.

### Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

#### \*LIMITED LIFETIME GUARANTEE

BEHR PROCESS CORPORATION GUARANTEES THAT THIS PAINT MEETS THE FOLLOWING STANDARDS WHEN APPLIED AND CARED FOR ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PAINT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

**Ultimate Durability** – The dried paint film resists peeling, blistering, fading and mildew growth, providing a scrubbable and washable finish from which you can easily remove stains and dirt. **Outstanding Hide and Coverage** – Assured when applied according to label directions. **Complete Color Selection** – Specifically formulated to achieve a full range of pure, clean colors available through computerized color matching. If this paint fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new paint to you, or refund the purchase price of this product. This guarantee excludes (1) labor and costs of labor for the application or removal of any paint and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Exterior Paint Guide for additional tips or visit us at [www.behr.com](http://www.behr.com) for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.





## PREMIUM PLUS® Exterior Semi-Gloss Enamel No.5050

Exterior Semi-Gloss is a radiant, sleek sheen that is the perfect choice for all climatic conditions. It's ideal for accenting siding, trim, porch pillars, railing, shutters, doors, wood siding, overhangs, vinyl, aluminum, outdoor furniture and garage doors. This 100% acrylic latex, mildew-resistant finish offers improved hiding for greater coverage, provides the ultimate in durability and is backed by a lifetime guarantee\*.



### Where To Use

Previously painted or primed Exterior surfaces. Ideal for Wood Siding, Vinyl, Aluminum, Doors, Windows, Trim, Shutters, Garage Doors and Outdoor Furniture.

### Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Etch galvanized metal, rinse thoroughly. Wash and rinse all other bare metal, allow to dry.

Powerwash exterior surfaces to remove chalk.

Remove all dust with a damp cloth, allow to dry.

Allow new stucco, plaster and masonry to cure for 30 days before priming.

### Prime

Use a product such as BEHR WATER-BASED PRIMER & SEALER NO. 436 or a product such as BEHR OIL-BASED PRIMER & SEALER NO. 434. For optimal color development, better hide and to reduce the number of topcoats with deep colors denoted with a dagger (†) on the color chip, apply a custom tinted primer.

### Application

Use product when the surface and air temperatures are between 50-90°F (10-32°C).

Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity.

Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip).

Coverage is 250-400 sq. ft. (23-37 m²) per gallon depending on the surface texture, porosity and application method.

Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

Certain colors may require more than one coat for complete hide.

### Dry Time

Dries to touch in 2 hours at 77°F (25°C) and 50% humidity, re-coat in 4 hours.

Darker colors may require additional dry time between coats.

Longer dry time required in cooler temperatures and in higher humidity.

After 2-4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

Dry paint film is mildew resistant.

### Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

#### \*LIMITED LIFETIME GUARANTEE

BEHR PROCESS CORPORATION GUARANTEES THAT THIS PAINT MEETS THE FOLLOWING STANDARDS WHEN APPLIED AND CARED FOR ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PAINT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

**Ultimate Durability** – The dried paint film resists peeling, blistering, fading and mildew growth, providing a scrubbable and washable finish from which you can easily remove stains and dirt. **Outstanding Hide and Coverage** – Assured when applied according to label directions. **Complete Color Selection** – Specifically formulated to achieve a full range of pure, clean colors available through computerized color matching. If this paint fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new paint to you, or refund the purchase price of this product. This guarantee excludes (1) labor and costs of labor for the application or removal of any paint and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Exterior Paint Guide for additional tips or visit us at [www.behr.com](http://www.behr.com) for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.







## PREMIUM PLUS® Interior/Exterior Hi-Gloss Enamel No.8050

This brilliant, durable, glass-like sheen is the perfect choice when exceptional wearability and easy stain removal is desired. Hi-Gloss Enamel is excellent for highlighting trim, railing, shutters and moulding. This 100% acrylic latex, mildew-resistant finish offers improved hiding for greater coverage, ultimate durability and is backed by a lifetime guarantee\*.



### Where To Use

Previously painted or primed Interior or Exterior surfaces. Ideal for Kitchens, Bathrooms, Ceilings, Cabinets, Shutters, Doors, Furniture, Garage Doors, Windows and Trim.

### Preparation†

Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Etch galvanized metal, rinse thoroughly. Wash and rinse all other bare metal, allow to dry.

Powerwash exterior surfaces to remove chalk.

Remove all dust with a damp cloth, allow to dry.

Allow new stucco, plaster and masonry to cure for 30 days before priming.

### Prime

Interior: Use a product such as BEHR ENAMEL UNDERCOATER PRIMER & SEALER NO. 75. For optimal color development, better hide and to reduce the number of topcoats with deep colors denoted with a dagger (†) on the color chip, apply a custom tinted primer.

Exterior: Use a product such as BEHR WATER-BASED PRIMER & SEALER NO. 436 or a product such as BEHR OIL-BASED PRIMER & SEALER NO. 434. For optimal color development, better hide and to reduce the number of topcoats with deep colors denoted with a dagger (†) on the color chip, apply a custom tinted primer.

### Application

Use product when the surface and air temperatures are between 50-90°F (10-32°C).

Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity.

Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip).

Coverage is 250-400 sq. ft. (23-37 m²) per gallon depending on the surface texture, porosity and application method.

Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

Certain colors may require more than one coat for complete hide.

### Dry Time

Dries to touch in 2 hours at 77°F (25°C) and 50% humidity, re-coat in 4 hours.

Darker colors may require additional dry time between coats.

Longer dry time required in cooler temperatures and in higher humidity.

After 4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

Dry paint film is mildew resistant.

### Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

### \*LIMITED LIFETIME GUARANTEE

BEHR PROCESS CORPORATION GUARANTEES THAT THIS PAINT MEETS THE FOLLOWING STANDARDS WHEN APPLIED AND CARED FOR ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PAINT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

Ultimate Durability – The dried paint film resists peeling, blistering, fading and mildew growth, providing a scrubbable and washable finish from which you can easily remove stains and dirt. Outstanding Hide and Coverage – Assured when applied according to label directions. Complete Color Selection – Specifically formulated to achieve a full range of pure, clean colors available through computerized color matching. If this paint fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new paint to you, or refund the purchase price of this product. This guarantee excludes (1) labor and costs of labor for the application or removal of any paint and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Interior or Exterior Paint Guide for additional tips or visit us at [www.behr.com](http://www.behr.com) for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

