



## PREMIUM PLUS® Water-Based Exterior Primer & Sealer No.436

This universal, multi-purpose, stain-blocking primer promotes the ultimate adhesion of exterior paint topcoats. It's ideal for new or painted exterior surfaces such as wood, masonry, stucco, galvanized metal, vinyl and aluminum. It is 100% acrylic latex and fast drying, has excellent adhesion to difficult surfaces, is mildew-resistant and is backed by a lifetime guarantee\*.



### Where To Use

New or painted Exterior surfaces such as Wood, Masonry, Stucco, Galvanized Metal, Vinyl and Aluminum. Also ideal to seal stains.

### Preparation†

Remove loose paint. Powerwash off chalk, dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62.

New, uncoated wood or after the use of No. 62, use a product such as BEHR 2-IN-1 WOOD PREP NO. 63.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Remove all dust with a damp cloth, allow to dry.

Wash bare metal. Etch galvanized metal with a product such as BEHR CONCRETE & MASONRY CLEANER/ETCHER NO. 991. Follow label instructions.

Allow new stucco, plaster and masonry to cure for 30 days before priming.

### Application

Use product when the surface and air temperatures are between 50-90°F (10-32°C).

Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip).

Coverage is 250-400 sq. ft. (23-37 m<sup>2</sup>) per gallon depending on the surface texture, porosity and application method.

Stir primer occasionally. DO NOT THIN if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

Two coats may be needed over stains and woods that contain tannins.

Spot prime patched areas first, follow with a complete primer coat. Topcoat within 30 days.

Bright or deep colors require a tinted primer. Have primer tinted close to topcoat color with no more than 4 ounces of colorant per gallon.

### Dry Time

Dries to touch in 1 hour at 77°F (25°C) and 50% humidity. Lightly stained surfaces; topcoat in 4 hours, heavy stained surfaces; topcoat in 12-16 hours. Longer dry time required in cooler temperatures and in higher humidity.

Dried paint film is mildew resistant.

### Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

#### \*LIMITED LIFETIME GUARANTEE

BEHR PROCESS CORPORATION GUARANTEES THAT THIS PRODUCT MEETS BEHR'S MANUFACTURING SPECIFICATIONS WHEN IT IS APPLIED TO A PROPERLY PREPARED SURFACE ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PRODUCT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

If this product fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you, or refund the purchase price of this product. This guarantee excludes (1) labor and the costs of labor for the application or removal of any product and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Exterior Paint Guide for additional tips or visit us at [www.behr.com](http://www.behr.com) for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.





## PREMIUM PLUS® Interior/Exterior Oil-Based Primer & Sealer No.434

This universal undercoat promotes the ultimate adhesion of interior and exterior topcoats. It is ideal for use on exterior wood, trim, shakes, shingles, fences, unprimed hardboard, aluminum and wrought iron before painting. It blocks common wood stains and promotes optimum adhesion of latex and oil-based topcoats, helps inhibit rust and is backed by a lifetime guarantee\*.



### Where To Use

Interior/Exterior surfaces such as Wood, Well-bonded Wallpaper, Aluminum and Wrought Iron. Also ideal to seal heavy stains and tannin bleed.

As a vapor barrier, this product has a Perm Rating of less than (1.0). Apply 2 coats.

### Preparation†

Remove loose paint, wash off chalk, dirt and grease with detergent, remove mildew stains with a product such as BEHR® MILDEW STAIN REMOVER NO. 62.

New or uncoated wood, use a product such as BEHR 2-IN-1 WOOD PREP NO. 63.

Scuff sand glossy surfaces.

Countersink nailheads, repair imperfections and sand smooth.

Remove all dust with a damp cloth, allow to dry.

Wash bare metal. Rinse and allow to dry.

### Application

Use when the surface and air temperatures are between 45-90°F (7-32°C).

Stir primer occasionally. DO NOT THIN. Product is formulated for use at package consistency only.

Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip).

Coverage is 250-400 sq. ft. (23-37 m<sup>2</sup>) per gallon depending on the surface texture, porosity and application method.

Spot prime patched areas first, follow with a complete primer coat. Topcoat within 30 days.

Two coats may be required.

Bright or deep colors require a tinted primer. Have primer tinted close to topcoat color with no more than 4 ounces of colorant per gallon.

### Dry Time

Dries to the touch in 4-6 hours at 77°F (25°C) and 50% humidity. Topcoat in 12-24 hours. Longer dry time required in cooler temperatures and in higher humidity.

### Clean Up & Storage

Use turpentine or mineral spirits.

Clean dried spills with lacquer thinner or paint remover.

Protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

#### \*LIMITED LIFETIME GUARANTEE

BEHR PROCESS CORPORATION GUARANTEES THAT THIS PRODUCT MEETS BEHR'S MANUFACTURING SPECIFICATIONS WHEN IT IS APPLIED TO A PROPERLY PREPARED SURFACE ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PRODUCT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

If this product fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you, or refund the purchase price of this product. This guarantee excludes (1) labor and the costs of labor for the application or removal of any product and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Interior or Exterior Paint Guide for additional tips or visit us at [www.behr.com](http://www.behr.com) for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

DANGER! COMBUSTIBLE LIQUID AND VAPOR. CONTAINS: PETROLEUM DISTILLATES AND MODIFIED ALKYD. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain or nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and flame. Do not smoke. Close container after each use.

USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. Do not use in an unventilated area. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If swallowed, do not induce vomiting. Call a physician immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

IMPORTANT! STORAGE AND DISPOSAL: DANGER! Rags, steel wool and waste soaked with BEHR PREMIUM PLUS NO. 434 may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

