

ACRYLIC MORTAR ADMIX

- Mix with Custom® standard thin-set mortars
- Increases bond strength and performance
- Improves water resistance
- Mix with PremiumPlus®, MasterBlend™, CustomBlend® or Wall Tile Thin-Set Mortars

PRODUCT DESCRIPTION

Acrylic Mortar Admix is a liquid polymer designed to be used in place of water to increase performance and bond strength of PremiumPlus, MasterBlend, CustomBlend or Wall Tile Thin-Set Mortars, non-polymer modified grouts or Portland cement mortar mixes. It adds water resistance and improves shock absorption. Pre-measured containers allow for easy mixing with Custom Standard thin-set mortars. Increases performance of unmodified thin-set mortars for setting dense tile and setting over hard-to-bond-to surfaces.

USES

- Add to PremiumPlus, MasterBlend or CustomBlend Thin-Set Mortars
- To meet ANSI A118.4 and A118.11 installation requirements
- Use when setting impervious porcelain tile, glass mosaics or when higher bond strength is desired
- Interior and exterior floors, walls, countertops
- Areas subject to freeze-thaw cycles
- Exterior grade plywood (interior residential and light commercial dry areas)
- Existing ceramic tile
- Sheet vinyl flooring, VCT
- Plastic laminates
- Cutback adhesive

FOR USE AS AN ADMIX WITH CUSTOM STANDARD THIN-SET MORTARS

Refer to individual product instructions for details.

FOR USE WITH UNMODIFIED PORTLAND CEMENT MORTARS

Acrylic Mortar Admix may be used by masonry setters, especially when installing mini-brick, as a fortifying admix to mortars. Mix 1 part AMA with 1 part clean water and use as a direct replacement for the water requirement in any mortar mix.

FOR USE AS AN UNMODIFIED TILE GROUT ADMIX

When installing tile over wood substrates and when increased tensile and flexural grout qualities are necessary, use Acrylic Mortar Admix with water. Mix 1 part clean water with 1 part AMA prior to mixing liquid with Portland cement grout. Remove excess grout from surface of tile as soon as possible after grouting, as acrylic-fortified grout becomes extremely difficult to remove when dry. Not for use with Custom's Polyblend® Grout.

COVERAGE

Refer to individual Custom® Thin-Set Mortars.

CLEAN-UP

Clean with water before material dries.

STORAGE

Keep from freezing. Close container after each use.

SAFETY

Do not take internally. Avoid eye and skin contact. If eye contact occurs, immediately flush with water for 15 minutes and consult a physician.

ORDERING INFORMATION

	ITEM CODE	SIZE	PACKAGE
USA	AMA1	1 1/4 gallon (4.73 L)	Bottle
USA	AMA2	2 1/2 gallon (9.46 L)	Bottle
USA	AMA3	3 quart (2.84 L)	Bottle
USA	AMA5	5 gallon (18.93 L)	Pail
USA	AMA55	55 gallon (208.19 L)	Drum
Canada	CAMA1	1 1/4 gallon (4.73 L)	Bottle
Canada	CAMA2	2 1/2 gallon (9.46 L)	Bottle
Canada	CAMA5	5 gallon (18.93 L)	Pail



CUSTOM[®]
BUILDING PRODUCTS