

## **The Clorox Company** 1221 Broadway Oakland, CA 94612

Tel. 1-510-271-7000

I Product: LIQUID-PLUMR® INDUSTRIAL STRENGTH GEL CLOG REMOVER				
Description: CLEAR, FAINT YELLOW, VISCOUS LIQUID WITH A CHARACTERISTIC BLEACH ODOR				
Other Designations	Distr	ibutor	Emergency Telephone Nos.	
Drain Cleaner Drain Opener	1221 B	es Company roadway CA 94612	For Medical Emergencies, call 1-800-446-1014. For Transportation Emergencies, call 1-800-424-9300 (Chemtrec).	
II Health Hazard Data		III Hazardous Ingredients		
CAN CAUSE BURNS ON CONTACT. Injures eyes, skin, and mucous membranes on contact. Harmful if swallowed; nausea, vomiting, and burning sensation of the mouth and throat may occur. No adverse health effects are expected with recommended use. Occasional clinical reports suggest a low potential for sensitization upon exaggerated exposure to sodium hypochlorite if skin damage (e.g. irritation) occurs during exposure. However, clinical tests conducted on intact skin with Liquid-Plumr found no sensitization in the test subjects. Although not expected, heart conditions or chronic respiratory problems such		Ingredient Sodium hypochlorite CAS #7681-52-9 Sodium hydroxide CAS #1310-73-2	<u>Concentration</u> 5 - 10% 0.5 - 2%	<u>Worker Exposure Limit</u> Not established. 2 mg/m <sup>3</sup> - TLV-C <sup>a</sup> 2 mg/m <sup>3</sup> - PEL <sup>b</sup>
as asthma, chronic bronchitis, or obstructive lung disease may be aggravated by exposure to high concentrations of vapor or mist.		<sup>a</sup> TLV-C = ACGIH Threshold Limit Value-Ceiling limit.		
FIRST AID:		<sup>b</sup> PEL = OSHA Permissible Exposure Limit - Time Weighted Average		
<u>EYE CONTACT</u> : Immediately flush eyes with water for 15 minutes. If wearing contact lenses, remove after first 5 minutes. Contact a physician.		None of the ingredients in this product are on the IARC, OSHA, or NTP carcinogen lists.		
<u>INGESTION</u> : Drink a glassful of water. <u>DO NOT</u> induce vomiting. Immediately contact a physician or Poison Control Center.				
<u>SKIN CONTACT</u> : Remove contaminated clothing. Flush skin with water. Contact a physician if irritation or discomfort persists.				
INHALATION: Remove from exposure to fresh air.				
IV Special Protection and Precautions		V Transportation and Regulatory Data		
<u>Hygienic Practices</u> : Wear safety glasses and gloves. The availability of an eyewash and shower is recommended in a manufacturing environment.		DOT/IATA/IMDG: Not restricted. <u>EPA - SARA TITLE III/CERCLA</u> : This product is not reportable under Sections 311/312 and contains no chemicals reportable under Section 313.		
Engineering Controls: Use general ventilation to minimize exposure to vapors. <u>Work Practices</u> : Avoid splashing, eye and skin contact and inhalation of vapor or mist.		This product does contain chemicals (sodium hydroxide and sodium hypochlorite) that are regulated under Section 304/CERCLA.		
		his product does hypochlorite) that are	regulated under Section 304	m hydroxide and sodium 4/CERCLA.
	t and inhalation of	hypochlorite) that are TSCA/DSL STATUS:	regulated under Section 304 All components of this pro	m hydroxide and sodium 4/CERCLA. oduct are on the U.S. TSCA
	hing, particularly in basins containing ot use Liquid-Plumr ers. Do not reuse	hypochlorite) that are	regulated under Section 304 All components of this pro	4/CERCLA.
vapor or mist. KEEP OUT OF REACH OF CHILDREN. Avoid all splas eyes, on skin and clothing. Keep children away from Liquid-Plumr. Do not use plunger with Liquid-Plumr. Do n with ammonia, toilet bowl cleaners or other drain open	hing, particularly in basins containing ot use Liquid-Plumr ers. Do not reuse	hypochlorite) that are TSCA/DSL STATUS:	regulated under Section 304 All components of this pro an DSL.	4/CERCLA.
vapor or mist. KEEP OUT OF REACH OF CHILDREN. Avoid all splass eyes, on skin and clothing. Keep children away from Liquid-Plumr. Do not use plunger with Liquid-Plumr. Do no with ammonia, toilet bowl cleaners or other drain open empty container. Rinse container and replace cap before of <b>VI Spill Procedures</b> : Absorb and containerize. Wash residu sewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple pr should evaluate the MSDSs of the products for incompa hypochlorite. Breathing protection should be worn in end ventilated areas until hazard assessment is complete.	hing, particularly in basins containing ot use Liquid-Plumr ers. Do not reuse discarding. al down to sanitary to assure ability to roducts, responders atibility with sodium osed and/or poorly-	hypochlorite) that are <u>TSCA/DSL STATUS</u> : Inventory and Canadi <b>VII Reactivity</b> Stable under norma household chemicals	regulated under Section 304 All components of this pro an DSL. <b>Data</b> al use and storage condi s such as toilet bowl cleane	4/CERCLA.
vapor or mist. KEEP OUT OF REACH OF CHILDREN. Avoid all splass eyes, on skin and clothing. Keep children away from Liquid-Plumr. Do not use plunger with Liquid-Plumr. Do n with ammonia, toilet bowl cleaners or other drain opene empty container. Rinse container and replace cap before <b>VI Spill Procedures/Waste Disposal</b> <u>Spill Procedures</u> : Absorb and containerize. Wash residu sewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple pi should evaluate the MSDSs of the products for incompa hypochlorite. Breathing protection should be worn in encl	hing, particularly in basins containing ot use Liquid-Plumr ers. Do not reuse discarding. al down to sanitary to assure ability to roducts, responders atibility with sodium osed and/or poorly-	hypochlorite) that are <u>TSCA/DSL STATUS</u> Inventory and Canada <b>VII Reactivity</b> Stable under norma household chemicals openers to produce h	regulated under Section 304 All components of this pro an DSL. <b>Data</b> al use and storage condi s such as toilet bowl cleane	4/CERCLA. oduct are on the U.S. TSCA tions. Reacts with other rs, ammonia, or other drain
vapor or mist. KEEP OUT OF REACH OF CHILDREN. Avoid all splass eyes, on skin and clothing. Keep children away from Liquid-Plumr. Do not use plunger with Liquid-Plumr. Do n with ammonia, toilet bowl cleaners or other drain open- empty container. Rinse container and replace cap before of <b>VI Spill Procedures</b> : Absorb and containerize. Wash residu sewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple pi should evaluate the MSDSs of the products for incompa hypochlorite. Breathing protection should be worn in encl ventilated areas until hazard assessment is complete. <u>Waste Disposal</u> : Dispose of in accordance with all applied	hing, particularly in basins containing ot use Liquid-Plumr ers. Do not reuse discarding. al down to sanitary to assure ability to roducts, responders atibility with sodium osed and/or poorly-	hypochlorite) that are <u>TSCA/DSL STATUS</u> Inventory and Canada <b>VII Reactivity</b> Stable under norma household chemicals openers to produce h	regulated under Section 304 All components of this pro- ian DSL. <b>Data</b> al use and storage condi such as toilet bowl cleane hazardous gases, such as ch	4/CERCLA. oduct are on the U.S. TSCA tions. Reacts with other rs, ammonia, or other drain