



Specialty Sealants



DAP® Roof Watertight Asphalt Filler & Sealant

Description: High performance, asphalt-based sealant for sealing roof gaps and joints, spotting shingles and repairing minor roof leaks. Forms a durable, flexible, weather-resistant and watertight seal. Can be used for both wet and dry applications. Will not run or bubble. Exterior use.

Applications: Ideal for sealing corrugated roofing, asphalt surfaces, chimneys, roof/pipe flashing, copings, gable joints, shingles/gutters, spotting shingle tabs, repairing minor roof leaks.

Adheres to: Wood, masonry, fiberglass, metal and asphalt.

Water Exposure: 1 hour

Clean Up: Mineral spirits

Paintable: Yes

Use: Exterior

Flexibility: Best

Application Temperature Range: 40°F to 120°F

Resists Mildew: Cured sealant is mold & mildew resistant



DAP® Seal n' Peel Removeable Weatherstrip Caulk

Unique removable weatherstrip caulk provides a watertight and weatherproof seal to temporarily seal out drafts and save energy. Peels away easily when removal is desired. Won't damage painted surfaces. Interior/exterior use.

Ideal for use on window and door frames, patio doors, vents and fans and air conditioners.

Glass, wood, metal, painted surfaces (fully dried, no cracking), fiberglass, porcelain, ceramics, drywall, aluminum and concrete.

Water Exposure: Not applicable

Clean Up: Solvent

Paintable: Not applicable

Use: Interior & exterior

Flexibility: Best

Application Temperature Range: 40°F to 100°F

Resists Mildew: Not applicable



DAP® 3.0™ Self-Leveling Concrete & Masonry High Performance Sealant

The newly formulated DAP® 3.0™ Self-Leveling Concrete sealant is 100% waterproof and offers a self-leveling formula so no tooling is required. The product withstands foot and vehicle traffic after fully cured and is water resistant in just 3 hours. This sealant is paintable, low odor, meets ASTM C920 and offers outstanding adhesion. It can be applied in extreme temperatures from 20°F to 120°F and offers a shrink and crackproof guarantee.

Ideal for filling and sealing horizontal cracks in sidewalks, concrete driveways, above-ground foundations, patios, concrete steps, garage floors and other concrete surfaces.

Concrete, masonry, mortar, stone, brick, wood and other construction materials.

Water Exposure: 3 hours

Clean Up: Solvent

Paintable: Yes

Use: Exterior

Flexibility: Best

Application Temperature Range: 20°F to 120°F

Resists Mildew: Cured sealant is mold & mildew resistant



* **Note:** For applications on masonry, brick & concrete, surface must be dry to obtain maximum adhesion. Please read product label and Technical Data Bulletins for additional information and instructions.

QUESTIONS: For more information call the DAP Help Line at 888-DAP-TIPS or visit www.dap.com.



You'll find us in all the right places.®

An RPM Company