



PREMIUM PLUS ULTRA™ Exterior Flat No.4850

With advanced NANO GUARD® technology, this product is a paint & primer in one. Creates a STAYS LOOKING NEW LONGER™ matte sheen finish on wood, vinyl, aluminum, fiber cement siding, brick, masonry, stucco, fences and garage doors. Also ideal for painting rusted metals, tannic woods and drastic color changes. An extra-protective shell shields against damage from sunlight, moisture, stains and dirt. The perfect choice for all weather climates, even for application at 35°F (2°C). Backed by a lifetime guarantee*.



Where To Use

Properly prepared coated or uncoated Exterior surfaces. Ideal for Wood, Vinyl, Aluminum, Fiber Cement Siding, Brick, Masonry, Stucco, Fences and Garage Doors.

Preparation† & Prime

Countersink nailheads. Fill and sand smooth.

Remove rust, loose or peeling paint, repair imperfections and sand smooth.

Wash off any dirt, grease and chalk with mild detergent and/or powerwash.

Remove mildew stains with a product such as BEHR® MULTI-SURFACE MILDEW STAIN REMOVER NO. 62. Follow label instructions.

Prepare new or weathered wood with a product such as BEHR 2-IN-1 WOOD PREP NO. 63.

Etch bare metals with a product such as BEHR CONCRETE & MASONRY CLEANER/ETCHER NO. 991. Follow label instructions.

Caulk windows, doors and other openings.

Allow new stucco, plaster and masonry to cure 30 days before applying product.

Use BEHR PREMIUM PLUS ULTRA™ as a primer for repaired or uncoated surfaces, including woods that contain tannins (two primer coats required for redwood and cedar), and heavily stained areas. Lock in stains with the first primer coat; if necessary, apply a second primer coat of BEHR PREMIUM PLUS ULTRA.

For drastic color changes, apply a primer coat of BEHR PREMIUM PLUS ULTRA if needed.

For optimal color development, with deep colors denoted with a dagger (†) on the color chip, apply a custom tinted primer coat of BEHR PREMIUM PLUS ULTRA. Primer coat will provide hide and reduce the number of topcoats required.

Application

Use product on dry substrates when both air and surface temperatures are above 35°F (2°C). Surface temperatures must remain above 35°F (2°C) for 4 hours after applying.

Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity.

On semi-smooth surfaces, use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip). On rough surfaces, use a high quality 3/4-1" nap roller cover.

Typical coverage is 250-400 sq. ft. (23-37 m²) per gallon depending on surface texture, porosity and application method. Do not thin if using a

roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

More than one topcoat may be required for complete hide.

Dry Time

Dries to the touch in 2 hours at 77°F (25°C) and 50% humidity. Allow at least 4 hours of dry time between coats.

Dries to the touch in 4 hours at 35°F (2°C) to 45°F (7°C) and 50% humidity. Allow at least 8 hours of dry time between coats.

On heavy stains and woods that contain tannins, allow 12-16 hours of dry time between coats.

Longer dry time required in cooler temperatures and in higher humidity.

Darker colors may require additional dry time between coats.

After 2-4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

Dry paint film is mildew resistant.

Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

*LIMITED LIFETIME GUARANTEE

BEHR PROCESS CORPORATION GUARANTEES THAT THIS PAINT MEETS THE FOLLOWING STANDARDS WHEN APPLIED AND CARED FOR ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PAINT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

Ultimate Durability – The dried paint film resists peeling, blistering, fading and mildew growth, providing a scrubbable and washable finish from which you can easily remove stains and dirt. Outstanding Hide and Coverage – Assured when applied according to label directions. Complete Color Selection – Specifically formulated to achieve a full range of pure, clean colors available through computerized color matching. If this paint fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new paint to you, or refund the purchase price of this paint. This guarantee excludes (1) labor and the costs of labor for the application or removal of any paint and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Exterior Paint Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Warning! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.





PREMIUM PLUS ULTRA™ Exterior Satin Enamel No.9850

This pearl-like sheen is formulated with advanced NANOGUARD® technology. It is a paint & primer in one that offers a mildew resistant finish and protection against damage from sunlight, moisture, stains and dirt. Ideal for use on wood, vinyl, aluminum, fiber cement siding, brick, masonry, stucco, doors, windows, trim, shutters, fences, garage doors, outdoor furniture, railing and wrought iron. Perfect for painting rusted metals, tannic woods and drastic color changes in all weather climates, even for application at 35°F (2°C). Includes a lifetime guarantee*.



Where To Use

Properly prepared coated or uncoated Exterior surfaces. Ideal for Wood, Vinyl, Aluminum, Fiber Cement Siding, Brick, Masonry, Stucco, Doors, Windows, Trim, Shutters, Fences, Garage Doors, Outdoor Furniture, Railing and Wrought Iron.

Preparation† & Prime

Countersink nailheads. Fill and sand smooth.

Remove rust, loose or peeling paint, repair imperfections and sand smooth.

Wash off any dirt, grease and chalk with mild detergent and/or powerwash.

Remove mildew stains with a product such as BEHR® MULTI-SURFACE MILDEW STAIN REMOVER NO. 62. Follow label instructions.

Prepare new or weathered wood with a product such as BEHR 2-IN-1 WOOD PREP NO. 63.

Etch bare metals with a product such as BEHR CONCRETE & MASONRY CLEANER/ETCHER NO. 991. Follow label instructions.

Caulk windows, doors and other openings.

Allow new stucco, plaster and masonry to cure 30 days before applying product.

Use BEHR PREMIUM PLUS ULTRA™ as a primer for repaired or uncoated surfaces, including woods that contain tannins (two primer coats required for redwood and cedar), and heavily stained areas. Lock in stains with the first primer coat; if necessary, apply a second primer coat of BEHR PREMIUM PLUS ULTRA.

For drastic color changes, apply a primer coat of BEHR PREMIUM PLUS ULTRA if needed.

For optimal color development, with deep colors denoted with a dagger (†) on the color chip, apply a custom tinted primer coat of BEHR PREMIUM PLUS ULTRA. Primer coat will provide hide and reduce the number of topcoats required.

Application

Use product on dry substrates when both air and surface temperatures are above 35°F (2°C). Surface temperatures must remain above 35°F (2°C) for 4 hours after applying.

Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity.

On semi-smooth surfaces, use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip). On rough surfaces, use a high quality 3/4-1" nap roller cover.

Typical coverage is 250-400 sq. ft. (23-37 m²) per gallon depending on surface texture, porosity and application method. Do not thin if using a

roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

More than one topcoat may be required for complete hide.

Dry Time

Dries to the touch in 2 hours at 77°F (25°C) and 50% humidity. Allow at least 4 hours of dry time between coats.

Dries to the touch in 4 hours at 35°F (2°C) to 45°F (7°C) and 50% humidity. Allow at least 8 hours of dry time between coats.

On heavy stains and woods that contain tannins, allow 12-16 hours of dry time between coats.

Longer dry time required in cooler temperatures and in higher humidity.

Darker colors may require additional dry time between coats.

After 2-4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

Dry paint film is mildew resistant.

Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

*LIMITED LIFETIME GUARANTEE

BEHR PROCESS CORPORATION GUARANTEES THAT THIS PAINT MEETS THE FOLLOWING STANDARDS WHEN APPLIED AND CARED FOR ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PAINT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

Ultimate Durability – The dried paint film resists peeling, blistering, fading and mildew growth, providing a scrubbable and washable finish from which you can easily remove stains and dirt. Outstanding Hide and Coverage – Assured when applied according to label directions. Complete Color Selection – Specifically formulated to achieve a full range of pure, clean colors available through computerized color matching. If this paint fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new paint to you, or refund the purchase price of this paint. This guarantee excludes (1) labor and the costs of labor for the application or removal of any paint and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Exterior Paint Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Warning! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.





PREMIUM PLUS ULTRA™ Semi-Gloss Enamel No.5850

NANO GUARD® technology adds an extra-protective shell for protection against damage from sunlight, moisture, stains and dirt. This paint and primer in one creates a tough STAYS LOOKING NEW LONGER™ radiant, sleek finish. Perfect for use in all weather climates, even for application at 35°F (2°C). Backed by a lifetime guarantee*, it can be used on wood, vinyl, aluminum, fiber cement siding, doors, windows, trim, shutters, garage doors, outdoor furniture, railing and wrought iron.



Where To Use

Properly prepared coated or uncoated Exterior surfaces. Ideal for Wood, Vinyl, Aluminum, Fiber Cement Siding, Doors, Windows, Trim, Shutters, Garage Doors, Outdoor Furniture, Railing and Wrought Iron.

Preparation† & Prime

Countersink nailheads. Fill and sand smooth.

Remove rust, loose or peeling paint, repair imperfections and sand smooth.

Wash off any dirt, grease and chalk with mild detergent and/or powerwash.

Remove mildew stains with a product such as BEHR® MULTI-SURFACE MILDEW STAIN REMOVER NO. 62. Follow label instructions.

Prepare new or weathered wood with a product such as BEHR 2-IN-1 WOOD PREP NO. 63.

Etch bare metals with a product such as BEHR CONCRETE & MASONRY CLEANER/ETCHER NO. 991. Follow label instructions.

Caulk windows, doors and other openings.

Allow new stucco, plaster and masonry to cure 30 days before applying product.

Use BEHR PREMIUM PLUS ULTRA™ as a primer for repaired or uncoated surfaces, including woods that contain tannins (two primer coats required for redwood and cedar), and heavily stained areas. Lock in stains with the first primer coat; if necessary, apply a second primer coat of BEHR PREMIUM PLUS ULTRA.

For drastic color changes, apply a primer coat of BEHR PREMIUM PLUS ULTRA if needed.

For optimal color development, with deep colors denoted with a dagger (†) on the color chip, apply a custom tinted primer coat of BEHR PREMIUM PLUS ULTRA. Primer coat will provide hide and reduce the number of topcoats required.

Application

Use product on dry substrates when both air and surface temperatures are above 35°F (2°C). Surface temperatures must remain above 35°F (2°C) for 4 hours after applying.

Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity.

On semi-smooth surfaces, use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015 spray tip). On rough surfaces, use a high quality 3/4-1" nap roller cover.

Typical coverage is 250-400 sq. ft. (23-37 m²) per gallon depending on surface texture, porosity and application method. Do not thin if using a

roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.

More than one topcoat may be required for complete hide.

Dry Time

Dries to the touch in 2 hours at 77°F (25°C) and 50% humidity. Allow at least 4 hours of dry time between coats.

Dries to the touch in 4 hours at 35°F (2°C) to 45°F (7°C) and 50% humidity. Allow at least 8 hours of dry time between coats.

On heavy stains and woods that contain tannins, allow 12-16 hours of dry time between coats.

Longer dry time required in cooler temperatures and in higher humidity.

Darker colors may require additional dry time between coats.

After 2-4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

Dry paint film is mildew resistant.

Clean Up & Storage

Use soap and water.

Properly dispose of all soiled rags and protect unused product from freezing.

To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

*LIMITED LIFETIME GUARANTEE

BEHR PROCESS CORPORATION GUARANTEES THAT THIS PAINT MEETS THE FOLLOWING STANDARDS WHEN APPLIED AND CARED FOR ACCORDING TO LABEL DIRECTIONS. THIS GUARANTEE SHALL BE EFFECTIVE FOR SO LONG AS YOU RESIDE IN YOUR HOME AND IS MADE TO THE ORIGINAL RESIDENTIAL CONSUMER PAINT PURCHASER. THIS GUARANTEE IS NOT TRANSFERABLE.

Ultimate Durability – The dried paint film resists peeling, blistering, fading and mildew growth, providing a scrubbable and washable finish from which you can easily remove stains and dirt. Outstanding Hide and Coverage – Assured when applied according to label directions. Complete Color Selection – Specifically formulated to achieve a full range of pure, clean colors available through computerized color matching. If this paint fails to perform as specified above, Behr will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new paint to you, or refund the purchase price of this paint. This guarantee excludes (1) labor and the costs of labor for the application or removal of any paint and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This guarantee gives you specific legal rights and you may also have other rights, which vary from state to state.

Refer to the BEHR Exterior Paint Guide for additional tips or visit us at www.behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A.

†WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Warning! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

