



Solid Color Concrete Stain

- Interior/Exterior
- Helps Hide Unsightly Imperfections
- Revives Ordinary Dull Concrete With An Attractive Solid Color Finish
- Flat Finish

No. 800 White

No. 830 Deep Base

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.
FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

WHERE TO USE

- Properly prepared Interior or Exterior surfaces such as: Concrete, Masonry Walls, Basements, Patios, Sidewalks, Driveways*, Garage Floors*, Pool/Cool Decks**, Tennis Courts, Cement Blocks, Pillars and Brick. Not for use on surfaces subject to hydrostatic pressure.
- * Driveways and Garage Floors - Lack of proper surface preparation and/or over-application can lead to automobile tires lifting the product from the surface.
- ** Light and pastel colored concrete stains should be used over pool deck surfaces. DARK COLORS RETAIN HEAT.

CAUTION: Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present. Use BEHR® NO. 970 NON-SKID to help prevent slipping.

PREPARATION† (The following steps are recommended for best results.)

New and Uncoated Concrete or Masonry Surfaces:

- New concrete must cure for a minimum of 30 days.
- For proper penetration and adhesion of topcoat, use BEHR® NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch the surface. Remove mildew stains with BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER. Follow all label instructions.
- Apply BEHR NO. 880 CONCRETE & MASONRY BONDING PRIMER to increase adhesion of topcoat to the surface. Follow all label instructions.

Painted, Stained or Sealed Concrete:

- **Option 1-** To completely strip the entire surface, use BEHR NO. 992 Concrete & Masonry Paint Stripper. Follow all label instructions.
- **Option 2-** To recoat over an existing coating, remove any loose or peeling paint and scuff sand the surface.
- Use BEHR NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER to clean previously coated surfaces in sound condition.
- Use BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch any bare concrete surface. Follow all label instructions.
- Spot prime all uncoated areas with BEHR NO. 880 CONCRETE & MASONRY BONDING PRIMER to increase adhesion of topcoat to the surface. Follow all label instructions.

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 2/08

APPLICATIONS

- DO NOT THIN. Intermix all cans of same product to ensure color uniformity. Stir stain before and occasionally during application.
- Use product when air and surface temperatures are between 50-90°F (10-32°C).
- Apply a thin, even coat using a 1/4"-3/8" nap roller cover, pad applicator or a nylon/polyester brush at a spread rate of 400-600 sq. ft. (37-56 m²) per gallon. Use long, even strokes in one direction to avoid lap lines.
- Since concrete varies in texture/porosity, two coats may be required for uniform color appearance. Apply a second coat (in a criss-cross direction) if uniformity is needed. Recoat after 24 hours. Periodic touch-ups may be necessary.

DRY TIME

- Allow 24 hours for light foot traffic. Allow 72 hours before subjecting surface to automotive tires, repositioning planters or furniture. Park tires on corrugated cardboard for 14 days after applying stain. After two weeks, dry stained surface may be cleaned with a mild, non-abrasive liquid detergent.

CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



Semi-Transparent Concrete Stain

No. 850 Tint Base

- Interior/Exterior
- Accentuates the natural variation and texture of concrete
- Achieve various unique decorative looks
- Flat Finish

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.
FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

WHERE TO USE

- For uncoated and unsealed, properly prepared Interior or Exterior Patios, Pavers, Driveways*, Walkways*, Garage Floors*, Pool Decks** and other concrete floors.
- * The composition of concrete varies; therefore, the lack of proper surface preparation and/or over application can lead to automobile tires lifting the product from the surface.
- ** Only light and pastel colored concrete stains should be used. DARK COLORS RETAIN HEAT.

CAUTION: Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
DO NOT use on areas subject to hydrostatic pressure.

PREPARATION† (The following steps are recommended for best results.)

- New concrete must cure for a minimum of 30 days.
- Remove old coating or sealer, if present, using BEHR NO. 992 CONCRETE & MASONRY PAINT STRIPPER. Follow all label instructions.
- Test: Sprinkle a few drops of water onto the surface. If water is quickly absorbed, the surface is ready. If not absorbed, re-etch.
- For proper penetration and adhesion of topcoat, use BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch the surface. Follow all label instructions.
- Remove mildew stains with BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER. Follow all label instructions.
- Apply BEHR NO. 880 CONCRETE & MASONRY BONDING PRIMER to increase adhesion of topcoat to the surface. Follow all label instructions.

APPLICATIONS

- Do not thin. Intermix cans of same products to ensure color uniformity. STIR thoroughly before and during application. Use product when temperature is between 50–90°F (10–32°C). Do not apply in direct sunlight. Apply to dry concrete. Do not apply if rain or heavy dew is expected within 24 hours.
- Apply stain in small concrete sections approximately 4' by 4' (1.2 m x 1.2 m). Work quickly and feather edges. Apply with a high quality pump sprayer at a fine spray setting using a circular motion. Immediately after spraying, back-roll with a 3/8" nap roller or pad applicator to achieve a

more even appearance. Apply at a spread rate of 175-250 sq. ft. (16-23 m²) per gallon depending on the porosity and texture of the surface.

- Allow first coat to dry for 4 hours before deciding if a second coat is necessary. An additional coat will provide a darker and more uniform color. Apply second coat at a spread rate of 250-350 sq. ft. (23-32 m²) per gallon. Note: Horizontal surfaces may be subject to premature wear. Periodic touch-ups may be necessary.

OPTIONAL TOPCOAT

- For added protection, use BEHR NO. 985 WET-LOOK SEALER for a high-gloss finish or BEHR NO. 986 LOW-LUSTRE SEALER for a low-gloss finish. Allow stain at least 4 hours to dry before topcoating. Follow all label instructions.

DRY TIME

- Dries to touch in 1 hour. Longer dry time required in cooler temperatures and in higher humidity.
- Surfaces may be subjected to light foot traffic after 24 hours. Allow 72 hours before subjecting surface to heavy foot traffic, repositioning furniture or automotive traffic. Park tires on corrugated cardboard for 7 days after applying stain. After 30 days, clean as needed with a mild, non-abrasive liquid detergent.

CLEAN UP AND STORAGE

- Clean with soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of product in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 2/08



Concrete & Masonry Bonding Primer

No. 880 Clear

- Easy to Apply
- Fast Drying
- Promotes a Uniform Topcoat Finish
- Epoxy Fortified

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

WHERE TO USE

- Use on uncoated Interior or Exterior surfaces such as: Concrete, Masonry, Stucco, Cinder Block and any Porous Stone or Brick. Not designed for use on wood, metal or silicone treated surfaces. Do not use on coated surfaces. Use only on porous surfaces.

NOTE: SOME SURFACES MAY APPEAR SLIGHTLY DARKER AFTER PRODUCT DRIES.

CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

PREPARATION† (The following steps are recommended for best results.)

- New concrete must cure for a minimum of 30 days.
- Patch all holes and cracks and allow to dry. For touch-ups where surface coatings have failed, completely remove any loose or peeling paint.
- Do not apply over previously coated surfaces. To completely strip previous coatings, use BEHR® NO. 992 Concrete & Masonry Paint Stripper. Follow all label instructions.
- For proper penetration and adhesion of primer, use BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch the surface. Follow all label instructions.

APPLICATIONS

- **DO NOT THIN.** Stir primer thoroughly before and occasionally during application.
- Use product when air and surface temperatures are between 50-90°F (10-32°C).
- Apply using a high quality 3/8-1/2" nap roller, nylon/polyester brush, pad applicator or airless sprayer (.015 spray tip) at a spread rate of 350-400 sq. ft. (33-37 m²) per gallon. Initial foaming will disappear upon drying.

DRY TIME

- Dries to touch in 2 hours. Longer dry time required in cooler temperatures and in higher humidity. **Must apply a topcoat after at least 8 hours, but before 30 days. Primer will remain tacky until topcoat is applied.**

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 2/08

CLEAN UP AND STORAGE

- Use any commercial brush cleaner. Note: Do not use soap and water to clean brushes or other applicators as they will become gummy. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of product in your community call 1-800-CLEANUP or visit www.Earth911.org.
- † **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



1-PART EPOXY Concrete & Garage Floor Paint

- Easy, No-Mix Formula
- Resists Chemicals & Hot Tire Pick-up
- Slip-Resistant Satin Finish
- Interior/Exterior

NO. 900 White
NO. 901 Silver Gray
NO. 902 Slate Gray
NO. 910 Clear
NO. 930 Deep Base

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.
FOR TINT BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

WHERE TO USE

- Interior or Exterior surfaces such as: Porous Concrete, Masonry, Stone and Brick. Ideal for horizontal surfaces such as: Garage Floors, Driveways, Basements, Porches and Pool Decks.
- DO NOT use on vertical surfaces or areas subject to hydrostatic pressure. NOT for industrial use. DO NOT use on areas subject to fork-lifts.

CAUTION: Painted surfaces may become slippery when wet. Adding BEHR® NO. 970 NON-SKID FLOOR FINISH ADDITIVE will help prevent slip. Follow all label instructions.

PREPARATION† (The following steps are recommended for best results.)

New and Uncoated Concrete or Masonry Surfaces:

- New concrete must cure for a minimum of 30 days.
- For proper penetration and adhesion of topcoat, use BEHR® NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch the surface. Follow all label instructions.
- Apply BEHR NO. 880 CONCRETE & MASONRY BONDING PRIMER to increase adhesion of topcoat to the surface. Follow all label instructions.

Painted, Stained or Sealed Concrete:

- **Option 1-** To completely strip the entire surface, use BEHR NO. 992 Concrete & Masonry Paint Stripper. Follow all label instructions.
- **Option 2-** To recoat over an existing coating, remove any loose or peeling paint and scuff sand the surface.
- Use BEHR NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER to clean previously coated surfaces in sound condition.
- Use BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch any bare concrete area. Follow all label instructions.
- Spot prime all bare concrete areas with BEHR NO. 880 CONCRETE & MASONRY BONDING PRIMER to increase adhesion of topcoat to the surface. Follow all label instructions.

APPLICATIONS

- DO NOT THIN. Intermix all cans of same product to ensure color uniformity. Stir before applying. Use product when air and surface temperatures are between 50-90°F (10-32°C).

- Apply a thin, even coat using a 3/8" nap roller cover, pad applicator or a nylon/polyester brush at a spread rate of 400-500 sq. ft. (37-46 m²) per gallon on smooth surfaces and 300-400 sq. ft. (28-37 m²) per gallon on rough surfaces.
- Allow first coat to dry 24 hours before deciding if a second coat is necessary. For uniformity apply a second coat (in a criss-cross direction).
- DO NOT APPLY MORE THAN TWO COATS. An annual touch-up may be required in areas subject to tire traffic.

DRY TIME

- Dries to touch in 2 hours. Longer dry time required in cooler temperatures and in higher humidity.
- The floor may be subjected to light foot traffic after 24 hours. Allow 72 hours before subjecting surface to heavy foot traffic or repositioning furniture. Allow 7 days before subjecting to automotive tires. Premature heavy traffic will cause paint failure requiring spot recoating. If necessary, corrugated cardboard may be used underneath automobile tires after 72 hours.
- Wait at least 30 days before rinsing or cleaning. Use a mild detergent as needed.
- Abrasive cleaners and pressure-washers should be used carefully to avoid premature paint failure.

CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <250 g/L • REV. 2/08



Premium 2-Part Epoxy Garage Floor Coating

No. 950 Silver Gray

- Custom Colors!
- No Waiting After Mixing
- Drive on After Only 3 Days!
- Durable Semi-Gloss Non-Skid Finish

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

WHERE TO USE

- Interior Garage Floors protected from the sun and other interior concrete surfaces. **Not for use on exterior surfaces.**

WHERE NOT TO USE

- **DO NOT** apply on surfaces subject to hydrostatic pressure. All interior concrete floors are subject to possible moisture vapor rising from under the concrete, which may cause coating failure. Test for moisture by taping a 3' x 3' (1 x 1 m) piece of plastic directly to the concrete using duct tape on all edges. Allow the plastic to sit for 24 hours. If water droplets appear on the inside of the plastic after 24 hours or if the concrete is damp, the surface contains moisture and the floor should not be painted. Moisture problem must be corrected before coating.
- **DO NOT** apply over surfaces that have been treated with a concrete sealer or waterproofer. Test the surface by dripping a small amount of water onto the surface. If water beads and continues to stay on top, it indicates that a sealer is present and the BEHR PREMIUM 2-PART EPOXY may not adhere. The sealer must be removed before using this product. After stripping, re-test the surface for water absorbency.
- **DO NOT** use over loose or peeling previously painted surfaces. Test for loose, flaking paint by cutting an "X" in the paint with a single edge razor blade. Apply a piece of duct tape over the "X" and press firmly, then pull it off with an abrupt action. If the tape does not pull the paint from the surface, it can be coated. If the existing paint is removed, the loose paint should be removed down to a sound substrate using BEHR NO. 992 CONCRETE & MASONRY PAINT STRIPPER.
- **DO NOT** use over loose or damaged concrete or if concrete dust is present. If the concrete is loose, chipping (spalled), or has concrete dust present, the coating will not adhere properly. Test for loose, flaking concrete by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the concrete from the surface, it can be coated. If the existing concrete is removed, the loose concrete must be removed down to a sound substrate. Loose or damaged concrete and cracks must be filled with a suitable concrete based patching material. Remove concrete dust using BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER. Follow all label instructions.

PREPARATION† (The following steps are recommended for best results.)

For New or Uncoated Concrete

- New concrete must cure for a minimum of 30 days.
- The surface must be clean, dry and free of dust, dirt, grease, oil, curing agents and all other contaminants.
- For proper penetration and adhesion of topcoat, use BEHR® NO. K-109924 CONCRETE CLEANER & ETCHER (included in kit). Wear protective clothing, eye goggles and acid resistant rubber gloves and footwear. Dissolve all concentrated powder with 1 gallon (4 litres) of warm water in a plastic container and stir. Pre-wet the surface with water. Apply all solution using a plastic watering can. One gallon of dissolved solution will etch and clean approximately 200-250 sq. ft. (19-23 m²). Allow product to stand for 10 minutes, then scrub vigorously using a stiff plastic brush.
- Rinse surface thoroughly using a garden hose with the nozzle set in a stream pattern or pressure wash for best results. Allow the surface to dry completely.

For Previously Coated Concrete (Oil or Water Base Finishes)

- Previously painted concrete may be repainted only if it has excellent adhesion to the floor.
- Remove any loose or peeling paint by sanding (medium grit paper) or wire brushing the surface. To completely remove all existing coating, use BEHR NO. 992 CONCRETE & MASONRY PAINT STRIPPER.
- Dull glossy surfaces by scuff-sanding or using a chemical deglosser.

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **This guarantee excludes (1) labor and the costs of labor for the application or removal of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <50 g/L When mixed • REV. 2/08

- The surface must be clean, dry and free of dust, dirt, grease, oil or other contaminants. Use BEHR® NO. K-109924 CONCRETE CLEANER & ETCHER to clean the surface. Follow all label instructions.
- Rinse surface thoroughly using a garden hose with the nozzle set in a stream pattern. Allow the surface to dry completely.

IMPORTANT:

- Excess residue may interfere with the adhesion of the BEHR® PREMIUM 2-PART EPOXY GARAGE FLOOR COATING. Wipe your fingers over the clean floor to check for dust or powder. If residue is visible on your fingers, repeat the rinsing step. Remove excess water with a squeegee or mop.
- Remove any remaining oil or grease spots on your concrete using BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER. Follow all label instructions.
- Note: The floor must be thoroughly cleaned, completely rinsed and dry for the coating to adhere properly to the surface.

MIXING OF FLOOR COATING

- Remove all the items from inside the container.
- Pour Activator into liquid side of container and stir thoroughly for at least 5 minutes or until you achieve a uniform color.
- DO NOT leave container in direct sunlight and keep lid closed when product is not in use.
- DO NOT mix color flakes with epoxy. Toss color flakes onto wet film.
- This product must be used within 8 hours of initial mixing (pot life).

APPLICATION

- DO NOT THIN PRODUCT.
- Use product when air and surface temperatures are between 50-95°F.
- Do all trim areas first using the 2" (50 mm) trim brush provided.
- Apply an even coat using a 3/8" nap roller cover at a spread rate not to exceed 200-250 sq. ft. per gallon (19-23 m²).
- Maintain a wet edge to avoid lap marks.
- While only one coat is recommended for most applications, a second coat may be applied for increased sheen and optimum performance (apply second coat in the opposite direction from the first coat).
- **Optional (Use of Decorative Color Flakes):** If planning to use the color decorative flakes, apply BEHR® PREMIUM 2-PART EPOXY GARAGE FLOOR COATING in 3' X 3' (1 x 1 m) sections. Immediately toss the color flakes randomly like "rain fall" directly onto the wet painted surface. Be careful not to over-apply the amount of flakes in any one area.

DRY TIME

- Dries to touch in two hours at 77°F and 50% humidity.
- The floor may be subjected to light foot traffic after 6-8 hours. Allow 24 hours before subjecting surface to heavy foot traffic or repositioning furniture. Allow at least 3 days drying before subjecting painted surface to automobile tires.
- Additional dry time is needed in cooler temperatures and higher humidity.
- Premature heavy traffic will cause coating failure, which may require spot recoating.
- Wait 7 days before rinsing or cleaning with a mild detergent.

CLEAN UP

- Clean up brushes, roller covers and tools immediately after use with soap and water. Properly dispose of all soiled rags. For disposal of empty containers and unused paint, contact your household refuse collection service.

DANGER! CONTAINS SULFAMIC ACID. CAN BURN EYES AND SKIN. SEVERELY HARMFUL IF SWALLOWED. HARMFUL IF INHALED. AVOID BREATHING IN DUST, MIST OR VAPORS. USE ONLY IN A WELL VENTILATED AREA. MAY CAUSE COUGHING, WHEEZING, THROAT IRRITATION, SHORTNESS OF BREATH, HEADACHE, NAUSEA OR VOMITING. DO NOT MIX CONTENTS WITH CHLORINE BLEACH OR ANY OTHER CLEANING PRODUCT OR DETERGENT. TO DO SO MAY EXPOSE YOU TO DANGEROUS GASES. MIX ONLY IN PLASTIC CONTAINERS.

Wear protective clothing, eye goggles and acid resistant rubber gloves and footwear. Avoid contact with eyes and skin. **FIRST AID: If Swallowed:** Do not induce vomiting. Have victim drink lots of milk or water if conscious. Get medical attention immediately! **Eye and Skin Contact:** Flush immediately with plenty of water for at least 15 minutes; spread eyelids and occasionally flush underneath them. **Get medical attention immediately!** Remove contaminated clothing and shoes immediately. Wash contaminated clothing before reuse. If experiencing Respiratory Discomfort (e.g., throat irritation, coughing, wheezing): Remove victim to fresh air. Get medical attention immediately!

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



Premium 2-Part Epoxy Garage Floor Coating

No. 955 Tan

- Custom Colors!
- No Waiting After Mixing
- Drive on After Only 3 Days!
- Durable Semi-Gloss Non-Skid Finish

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

WHERE TO USE

- Interior Garage Floors protected from the sun and other interior concrete surfaces. **Not for use on exterior surfaces.**

WHERE NOT TO USE

- **DO NOT** apply on surfaces subject to hydrostatic pressure. All interior concrete floors are subject to possible moisture vapor rising from under the concrete, which may cause coating failure. Test for moisture by taping a 3' x 3' (1 x 1 m) piece of plastic directly to the concrete using duct tape on all edges. Allow the plastic to sit for 24 hours. If water droplets appear on the inside of the plastic after 24 hours or if the concrete is damp, the surface contains moisture and the floor should not be painted. Moisture problem must be corrected before coating.
- **DO NOT** apply over surfaces that have been treated with a concrete sealer or waterproofer. Test the surface by dripping a small amount of water onto the surface. If water beads and continues to stay on top, it indicates that a sealer is present and the BEHR PREMIUM 2-PART EPOXY may not adhere. The sealer must be removed before using this product. After stripping, re-test the surface for water absorbency.
- **DO NOT** use over loose or peeling previously painted surfaces. Test for loose, flaking paint by cutting an "X" in the paint with a single edge razor blade. Apply a piece of duct tape over the "X" and press firmly, then pull it off with an abrupt action. If the tape does not pull the paint from the surface, it can be coated. If the existing paint is removed, the loose paint should be removed down to a sound substrate using BEHR NO. 992 CONCRETE & MASONRY PAINT STRIPPER.
- **DO NOT** use over loose or damaged concrete or if concrete dust is present. If the concrete is loose, chipping (spalled), or has concrete dust present, the coating will not adhere properly. Test for loose, flaking concrete by pressing a piece of masking or cellophane tape at various places, then pull it off with an abrupt action. If the tape does not pull the concrete from the surface, it can be coated. If the existing concrete is removed, the loose concrete must be removed down to a sound substrate. Loose or damaged concrete and cracks must be filled with a suitable concrete based patching material. Remove concrete dust using BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER. Follow all label instructions.

PREPARATION† (The following steps are recommended for best results.)

For New or Uncoated Concrete

- New concrete must cure for a minimum of 30 days.
- The surface must be clean, dry and free of dust, dirt, grease, oil, curing agents and all other contaminants.
- For proper penetration and adhesion of topcoat, use BEHR® NO. K-109924 CONCRETE CLEANER & ETCHER (included in kit). Wear protective clothing, eye goggles and acid resistant rubber gloves and footwear. Dissolve all concentrated powder with 1 gallon (4 litres) of warm water in a plastic container and stir. Pre-wet the surface with water. Apply all solution using a plastic watering can. One gallon of dissolved solution will etch and clean approximately 200-250 sq. ft. (19-23 m²). Allow product to stand for 10 minutes, then scrub vigorously using a stiff plastic brush.
- Rinse surface thoroughly using a garden hose with the nozzle set in a stream pattern or pressure wash for best results. Allow the surface to dry completely.

For Previously Coated Concrete (Oil or Water Base Finishes)

- Previously painted concrete may be repainted only if it has excellent adhesion to the floor.
- Remove any loose or peeling paint by sanding (medium grit paper) or wire brushing the surface. To completely remove all existing coating, use BEHR NO. 992 CONCRETE & MASONRY PAINT STRIPPER.
- Dull glossy surfaces by scuff-sanding or using a chemical deglosser.

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **This guarantee excludes (1) labor and the costs of labor for the application or removal of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <50 g/L When mixed • REV. 2/08

- The surface must be clean, dry and free of dust, dirt, grease, oil or other contaminants. Use BEHR® NO. K-109924 CONCRETE CLEANER & ETCHER to clean the surface. Follow all label instructions.
- Rinse surface thoroughly using a garden hose with the nozzle set in a stream pattern. Allow the surface to dry completely.

IMPORTANT:

- Excess residue may interfere with the adhesion of the BEHR® PREMIUM 2-PART EPOXY GARAGE FLOOR COATING. Wipe your fingers over the clean floor to check for dust or powder. If residue is visible on your fingers, repeat the rinsing step. Remove excess water with a squeegee or mop.
- Remove any remaining oil or grease spots on your concrete using BEHR® NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER. Follow all label instructions.
- Note: The floor must be thoroughly cleaned, completely rinsed and dry for the coating to adhere properly to the surface.

MIXING OF FLOOR COATING

- Remove all the items from inside the container.
- Pour Activator into liquid side of container and stir thoroughly for at least 5 minutes or until you achieve a uniform color.
- DO NOT leave container in direct sunlight and keep lid closed when product is not in use.
- DO NOT mix color flakes with epoxy. Toss color flakes onto wet film.
- This product must be used within 8 hours of initial mixing (pot life).

APPLICATION

- DO NOT THIN PRODUCT.
- Use product when air and surface temperatures are between 50-95°F.
- Do all trim areas first using the 2" (50 mm) trim brush provided.
- Apply an even coat using a 3/8" nap roller cover at a spread rate not to exceed 200-250 sq. ft. per gallon (19-23 m²).
- Maintain a wet edge to avoid lap marks.
- While only one coat is recommended for most applications, a second coat may be applied for increased sheen and optimum performance (apply second coat in the opposite direction from the first coat).
- **Optional (Use of Decorative Color Flakes):** If planning to use the color decorative flakes, apply BEHR® PREMIUM 2-PART EPOXY GARAGE FLOOR COATING in 3' X 3' (1 x 1 m) sections. Immediately toss the color flakes randomly like "rain fall" directly onto the wet painted surface. Be careful not to over-apply the amount of flakes in any one area.

DRY TIME

- Dries to touch in two hours at 77°F and 50% humidity.
- The floor may be subjected to light foot traffic after 6-8 hours. Allow 24 hours before subjecting surface to heavy foot traffic or repositioning furniture. Allow at least 3 days drying before subjecting painted surface to automobile tires.
- Additional dry time is needed in cooler temperatures and higher humidity.
- Premature heavy traffic will cause coating failure, which may require spot recoating.
- Wait 7 days before rinsing or cleaning with a mild detergent.

CLEAN UP

- Clean up brushes, roller covers and tools immediately after use with soap and water. Properly dispose of all soiled rags. For disposal of empty containers and unused paint, contact your household refuse collection service.

DANGER! CONTAINS SULFAMIC ACID. CAN BURN EYES AND SKIN. SEVERELY HARMFUL IF SWALLOWED. HARMFUL IF INHALED. AVOID BREATHING IN DUST, MIST OR VAPORS. USE ONLY IN A WELL VENTILATED AREA. MAY CAUSE COUGHING, WHEEZING, THROAT IRRITATION, SHORTNESS OF BREATH, HEADACHE, NAUSEA OR VOMITING. DO NOT MIX CONTENTS WITH CHLORINE BLEACH OR ANY OTHER CLEANING PRODUCT OR DETERGENT. TO DO SO MAY EXPOSE YOU TO DANGEROUS GASES. MIX ONLY IN PLASTIC CONTAINERS.

Wear protective clothing, eye goggles and acid resistant rubber gloves and footwear. Avoid contact with eyes and skin. **FIRST AID: If Swallowed:** Do not induce vomiting. Have victim drink lots of milk or water if conscious. Get medical attention immediately! **Eye and Skin Contact:** Flush immediately with plenty of water for at least 15 minutes; spread eyelids and occasionally flush underneath them. **Get medical attention immediately!** Remove contaminated clothing and shoes immediately. Wash contaminated clothing before reuse. If experiencing Respiratory Discomfort (e.g., throat irritation, coughing, wheezing): Remove victim to fresh air. Get medical attention immediately!

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



Non-Skid Sand Additive

No. 970

- Ready-to-Use
- Creates a Slip-Resistant Finish
- Provides Subtle Textured Finish
- Simply Pour into a Finish Product Container

BEHR® NON-SKID FLOOR FINISH ADDITIVE is a unique texture additive, which, when mixed with a finish product container of paint or solid color stain creates a slip-resistant coating for all types of interior and exterior floor surfaces. This product will not change the color of the floor coating. For a high-quality finish use one of the many BEHR floor coating products: PORCH & FLOOR PAINT, EPOXY CONCRETE FLOOR PAINT, SOLID COLOR CONCRETE STAIN

WHERE TO USE

- Garage Floors, Patios, Stairs, Basements, Driveway, Decks, Walkways, Pool Decks

MIXING INSTRUCTIONS

Finish Product Container Size	1 QUART	1 GALLON	5 GALLON
Amount of Additive Needed	1/4 Pouch	1 Pouch	5 Pouch

APPLICATIONS

- Add the proper amount of **BEHR NON-SKID FLOOR FINISH ADDITIVE** to any latex or oil-based floor coating finish product container and stir thoroughly until dispersed uniformly. Stir occasionally during application. Apply coating to floor surface using a brush or roller. Refer to all paint and stain manufacturer's product labels for specific instructions on surface preparation and finish application.
- If applying more than one coat of floor finish, mix **NON-SKID FLOOR FINISH ADDITIVE** into the final topcoat. Adding a non-skid additive will reduce the lifespan of the product; therefore, retain any leftover paint for periodic maintenance re-coating.

This product, if added according to label directions, helps to prevent slipping by providing a slip-resistant coating. However, Behr does not warrant that this product will prevent accidents as described in the limited warranty below.

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).



Concrete & Masonry Waterproofer

No. 980 Natural Finish

- Interior/Exterior
- Silicone Enhanced To Keep Water Out
- For Brick, Concrete, Stucco & Tile
- Lasts Up to 10 Years

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

WHERE TO USE

- Horizontal and Vertical uncoated Concrete and Masonry surfaces such as: Concrete Block, Pavers, Stucco, Brick, Unglazed Tiles, Exposed Aggregate Concrete, Sandstone and Slate.
- Not recommended for use on areas subject to hydrostatic pressure such as basement walls or floors.

CAUTION: Sealed surfaces may become slippery when wet.

Use caution when walking on surface when moisture is present.

PREPARATION† (The following steps are recommended for best results.)

- New concrete must cure for a minimum of 30 days.
- Remove old coating or sealer, if present, using BEHR® NO. 992 CONCRETE & MASONRY PAINT STRIPPER. Follow all label instructions.
- For proper penetration and adhesion, use BEHR NO. 991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch the surface. Follow all label instructions.
- **TEST:** Sprinkle a few drops of water onto the surface. If water is quickly absorbed, the surface is ready. If not absorbed, re-etch.
- Remove mildew stains with BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER. Follow all label instructions.

APPLICATIONS

- DO NOT THIN. Stir or shake before applying.
- Use product when temperature is between 50–90°F (10–32°C).
- Apply until saturated by brush, roller or garden sprayer to a dry surface at the spread rate of about 250 sq. ft. per gallon.
- Remove any puddles by spreading product to drier areas or by wiping up excess with a clean cloth.
- On vertical surfaces, apply from the bottom up and saturate well.

DRY TIME

- Allow surface to dry 24-48 hours, depending on temperature and humidity.
- Once dried, rough, vertical surfaces may be coated with an oil or latex-based paint or primer. Follow all label instructions. Do not paint horizontal surfaces after applying this product.

***LIMITED WARRANTY:** BEHR PROCESS CORPORATION warrants customer satisfaction with this product for 10 years on vertical and horizontal surfaces from date of purchase, when applied to a properly prepared surface in accordance with the label directions. If you are not satisfied with this product, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. This warranty is made to the original residential purchaser and is not transferable. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 2/08

CLEAN UP AND STORAGE

- Clean all equipment immediately with warm, soapy water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP (U.S.A. only) or visit www.Earth911.org.
- † **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. **USE WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air and use a properly fitted respirator (NIOSH approved for organic vapor with P Series particulate prefilter). Obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN—DO NOT TAKE INTERNALLY.



Wet-Look Sealer

No. 985 Hi-Gloss

- High-Gloss Clear Finish
- Excellent Topcoat Over Paints & Stains
- 100% Acrylic for Maximum Durability
- Interior/Exterior & Vertical/Horizontal

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.
PRODUCT WILL APPEAR MILKY IN CONTAINER BUT WILL DRY TO A CLEAR FINISH.

WHERE TO USE

- Use on Previously Coated or Uncoated, Vertical or Horizontal, Interior or Exterior surfaces such as: Pavers, Concrete, Mexican and Unglazed Tiles, Brick, Aggregate, Natural and Artificial Stone, Masonry and Stucco. Not recommended for use on wood, metal, granite, marble, terrazzo, travertine, areas immediately adjacent to pools or areas subject to hydrostatic pressure. Do not use over Oil-Based products.

CAUTION: Sealed surfaces may become slippery when wet. Use caution when walking on surface when moisture is present. Apply in sections so wet material does not have to be walked on during application.

PREPARATION† (The following steps are recommended for best results.)

- New concrete must cure for a minimum of 30 days. For proper penetration and adhesion of sealer on new or smooth concrete floors, use BEHR® NO.991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch the surface. Follow all label instructions. Use BEHR NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER to clean previously coated surface in sound condition. Scrape and remove any loose or peeling coating. To completely strip the surface use BEHR NO. 992 CONCRETE & MASONRY PAINT STRIPPER. Follow all label instructions. Scrape and remove any loose or peeling coating.

APPLICATIONS

- **DO NOT THIN.** Stir or shake before applying. Use product when temperature is between 50-80°F (10-27°C). Do not apply in direct sunlight. Do not apply to wet surfaces or if rain or heavy dew is expected within 24 hours. Apply a thin coat using a nylon/polyester brush, 3/8-1/2" nap roller or a high quality pump sprayer with an adjustable tip at a spread rate of 150-300 sq. ft. (14-28 m²) per gallon. Spread rate is highly dependent on surface roughness and porosity. If sprayed, backroll for uniform thickness. Allow first coat to dry 4 hours, then apply a second coat at a spread rate of 300-400 sq. ft. (28-37 m²) per gallon. Additional coats (no more than 4) may be added for a higher gloss and added protection.

Note: Horizontal surfaces may be subject to excessive wear. Therefore, periodic touch-ups may be necessary.

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 2/08

DRY TIME

- Dries to touch in 1 hour. Longer dry time required in cooler temperatures and in higher humidity. Floors may be subjected to light foot traffic after 24 hours. Allow 72 hours before repositioning furniture or subjecting surface to heavy foot or automotive traffic. Park tires on corrugated cardboard for 14 days after applying product. Wait at least 30 days before cleaning with a mild, non-abrasive liquid detergent.

CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



Low-Lustre Sealer

No. 986 Low-Gloss

- Low-Gloss Clear Finish
- Excellent Topcoat Over Paints & Stains
- 100% Acrylic for Maximum Durability
- Interior/Exterior & Vertical/Horizontal

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.
PRODUCT WILL APPEAR MILKY IN CONTAINER BUT WILL DRY TO A CLEAR FINISH.

WHERE TO USE

- Use on Previously Coated or Uncoated, Vertical or Horizontal, Interior or Exterior surfaces such as: Pavers, Concrete, Mexican and Unglazed Tiles, Brick, Aggregate, Natural and Artificial Stone, Masonry and Stucco. Not recommended for use on wood, metal, granite, marble, terrazzo, travertine, areas immediately adjacent to pools or areas subject to hydrostatic pressure. Do not use over Oil-Based products.

CAUTION: Sealed surfaces may become slippery when wet. Use caution when walking on surface when moisture is present. Apply in sections so wet material does not have to be walked on during application.

PREPARATION† (The following steps are recommended for best results.)

- New concrete must cure for a minimum of 30 days. For proper penetration and adhesion of sealer on new or smooth concrete floors, use BEHR® NO.991 CONCRETE & MASONRY CLEANER/ETCHER to clean and etch the surface. Follow all label instructions. Use BEHR NO. 990 CONCRETE & MASONRY CLEANER/DEGREASER to clean previously coated surface in sound condition. Scrape and remove any loose or peeling coating. To completely strip the surface use BEHR NO. 992 CONCRETE & MASONRY PAINT STRIPPER. Follow all label instructions. Scrape and remove any loose or peeling coating.

APPLICATIONS

- **DO NOT THIN.** Stir or shake before applying. Use product when temperature is between 50-80°F (10-27°C). Do not apply in direct sunlight. Do not apply to wet surfaces or if rain or heavy dew is expected within 24 hours. Apply a thin coat using a nylon/polyester brush, 3/8-1/2" nap roller or a high quality pump sprayer with an adjustable tip at a spread rate of 150-300 sq. ft. (14-28 m²) per gallon. Spread rate is highly dependent on surface roughness and porosity. If sprayed, backroll for uniform thickness. Allow first coat to dry 4 hours, then apply a second coat at a spread rate of 300-400 sq. ft. (28-37 m²) per gallon. Additional coats (no more than 4) may be added for a higher gloss and added protection.

Note: Horizontal surfaces may be subject to excessive wear. Therefore, periodic touch-ups may be necessary.

LIMITED WARRANTY BEHR PROCESS CORPORATION warrants that this product meets BEHR'S manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 2/08

DRY TIME

- Dries to touch in 1 hour. Longer dry time required in cooler temperatures and in higher humidity. Floors may be subjected to light foot traffic after 24 hours. Allow 72 hours before repositioning furniture or subjecting surface to heavy foot or automotive traffic. Park tires on corrugated cardboard for 14 days after applying product. Wait at least 30 days before cleaning with a mild, non-abrasive liquid detergent.

CLEAN UP AND STORAGE

- Use soap and water. Properly dispose of all soiled rags and protect unused product from freezing. To recycle or properly dispose of paint in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



Decorative Color Flakes

No. F-50 Gray Blend

No. F-55 Tan Blend

- Achieve the look of granite or terrazzo on ordinary concrete
- Hides dirt and surface imperfections
- Ideal for 1-Part & 2-Part Epoxies, Solid Color Concrete Stain, Porch & Floor Paints and other acrylic floor coatings

Transform your concrete floor into a beautiful surface that has the look of granite or terrazzo. BEHR® DECORATIVE COLOR FLAKES are available in a variety of color combinations to match any décor, adding beauty and elegance to residential and commercial floors. Ideal for Interior/Exterior surfaces such as: Garage Floors, Driveways, Basements, Patios, Sidewalks, Laundry Rooms and Pool Decks. BEHR Color Flakes help to hide dirt and surface imperfections and can be used with water and oil-based coatings.

APPLICATION INSTRUCTIONS

1. **IMPORTANT:** For a light chip pattern toss the color flakes evenly over a 250 sq. ft. area. For a heavy chip pattern toss the color chips evenly over a 125 sq. ft. area.
2. Work in 3' x 3' (1 x 1 m) sections to ensure that the color flakes are evenly distributed.
3. Apply color flakes directly onto the wet painted surface.
4. Throw the color flakes up into the air and let them distribute evenly on the wet painted surface.
5. Repeat these steps until you have finished the entire area.
6. After the surface is completely dry, sweep up any loose flakes remaining on the surface.

CAUTION: May cause eye and skin irritation.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
REV. 2/08