



## Flooring Adhesive Remover

No. 995

- Strips the Toughest Adhesives
- Contains No Methylene Chloride
- Biodegradable & Easy Water Clean-Up
- Interior & Exterior Surfaces

**IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.**

### WHERE TO USE

- Use on most Interior or Exterior surfaces including Concrete, Metal, Wood and Some Plastics.
- Removes carpet underlay, black mastic, linoleum & tile glue, wood glue, tape residue, contact cement, tire marks, label adhesives and a wide variety of glue residue.

**CAUTION:** Stained surfaces may become slippery when wet.

### PREPARATION† (The following steps are recommended for best results.)

- Remove all loose carpet and carpet pad prior to application.
- Make sure that the floor is free of loose debris prior to applying BEHR® NO. 995 FLOORING ADHESIVE REMOVER.
- **Test Patch:** Conduct a small test patch in an inconspicuous area to ensure product performance. Some sub-floors are moisture sensitive and may swell when rinsed with water.
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Prevent all rinse solution from entering storm drains.

### APPLICATIONS

- DO NOT DILUTE PRODUCT.
- Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air-purifying respirator with an organic vapor cartridge.
- Spread rate is approximately 100 sq. ft. per gallon depending on thickness of adhesive.
- Note: When removing linoleum, pre-cut the surface into approximately 2 inch squares to allow product to penetrate to the glue beneath.
- Apply BEHR® FLOORING ADHESIVE REMOVER to the floor by pouring it out and spreading with a roller, brush, mop, sponge or rag.
- Make sure that sufficient product is being used to thoroughly penetrate the mastic or glue residue.
- Allow the product to work for 15 minutes or until the glue is soft. For tougher ceramic tile mastics, up to 2 hours may be required and agitation with a stiff brush is recommended.
- Use a scraper, squeegee, pressure washer or wet vacuum suction to remove softened glue. Some stubborn areas may require an additional application to remove all layers.
- The stripped surface must be rinsed with water thoroughly to remove all chemical residue.

**\*LIMITED WARRANTY:** BEHR PROCESS CORPORATION warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) 4.0 WT.% • REV. 2/08

### DRY TIME

- Surface dry time will vary, depending on air & surface temperature.
- Make sure surface is visually and completely dry to touch prior to putting new flooring down.

### CLEAN UP AND STORAGE

- Thoroughly rinse all surfaces, clothing and tools with fresh water after use.
- Collect lifted material and dispose of it in accordance with local government regulations.
- For disposal of empty containers and unused product call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**DANGER! CORROSIVE! WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED.** CONTAINS DIPROPYLENE GLYCOL N-BUTYL ETHER. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**



## Premium Paint Stripper

No. 999

- Removes Oil & Water based Paints, Lacquers, Sealants and Various Coatings
- Vertical & Horizontal Surfaces
- Biodegradable & Easy Water Clean-Up
- Removes Multiple Layers of Coatings

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Use on painted Masonry, Concrete, Brick, Metal, Aluminum and Wood surfaces.
- Removes coatings such as: Oil and Water-Base Paint including 100% Acrylic, Urethanes, Lacquers, Sealants, Alkyds, Epoxies and Elastomers.
- DO NOT USE ON MARBLE, GRANITE, TERRAZZO, COLORED CONCRETE, BRASS, BRONZE or COPPER.

**CAUTION:** Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

#### PREPARATION† (The following steps are recommended for best results.)

- SHAKE WELL PRIOR TO USE.
- For vertical and glossy or greasy surfaces, scuff-sand the surface lightly with a medium grit sand paper prior to application to prevent sagging of paint stripper.
- Pour the BEHR® NO. 999 PREMIUM PAINT STRIPPER into a paint tray or bucket. If water seems to have separated out, stir product until uniform.
- Test Patch: A test area will indicate the time required to lift coating and the suitability of the product for the paint and substrate.
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Prevent all rinse solution from entering storm drains.

#### APPLICATIONS

- Use product when air and surface temperatures are between 50-90°F (10-32°C).
- Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air-purifying respirator with an organic vapor cartridge.
- Apply a thick, even layer of stripper onto the surface using a paint brush, roller or an airless sprayer (.019" tip size). Stripper thickness should be such that the original coated surface is completely covered.
- Once applied, leave the stripper alone, as agitation slows down penetration.
- Note: When trying to build up a thick film on a glossy or greasy vertical surface, use two separate applications. First apply a light coat and allow it to sit for about 30 minutes and then build the rest of the stripper film thickness in a second application (thick enough to hide the original paint color).

**\*LIMITED WARRANTY:** BEHR Process Corporation warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) 40.6 WT.% • REV. 2/08

- Spread rate is approximately 60-75 sq. ft. per gallon.
- Penetration varies according to coating type, thickness and temperature. COATING WILL WRINKLE WHEN THE JOB IS DONE. Most coatings will take between 1 – 6 hours to lift.
- Check periodically during the waiting period, to ensure that the coating is completely covered with the stripper. If the coated surface becomes visible again, re-apply a light coating.
- The stripper should remain wet and active until the coating wrinkles. If hot or windy conditions cause drying, re-apply a light coating.
- Use a scraper, wire brush, squeegee or pressure washer to remove all coating and residue.
- The stripper is formulated to remove several layers of coating in one application. Some areas however, may require an additional application to remove all layers.
- The stripped surface must be rinsed with water thoroughly to remove all chemical residues before recoating.

#### SURFACE DRY TIME

- Surface dry time will vary, depending on air & surface temperature.
- Make sure surface is visually and completely dry to touch prior to recoating.

#### CLEAN UP AND STORAGE

- If product comes in contact with painted or finished surfaces not intended to be stripped, rinse immediately with fresh water.
- Thoroughly rinse all surfaces, clothing and tools with fresh water after use.
- Collect lifted coating and dispose of in accordance with local government regulations.
- For disposal of empty containers and unused product call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org)

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**CAUTION! IRRITANT! MAY CAUSE MODERATE EYE IRRITATION. HARMFUL IF SWALLOWED. CONTAINS GLYCOLIC ACID. MAY CAUSE SLIGHT SKIN IRRITATION AND MODERATE TO SEVERE GASTROINTESTINAL AND RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION.** Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN—DO NOT TAKE INTERNALLY.**



## Concrete & Masonry Paint Stripper

No. 992

- Ideal for Removing Paint, Stain, Epoxy and Sealers
- Vertical & Horizontal Surfaces
- Biodegradable & Easy Water Clean-Up
- Removes Multiple Layers

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Use on painted or stained Interior/Exterior Concrete, Masonry, Stone, Brick and Metal Surfaces such as: Garage Floors, Driveways, Walkways, Patios, Pool/Cool Decks, Basement Floors and Concrete Walls.
- Removes coatings such as: stains, epoxies, urethanes, elastomeric, alkyds, sealants, latex and most industrial and architectural paints.
- DO NOT USE ON MARBLE, GRANITE, TERRAZZO, COLORED CONCRETE, BRASS, BRONZE or COPPER.

**CAUTION:** Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

#### PREPARATION† (The following steps are recommended for best results.)

- SHAKE WELL PRIOR TO USE.
- Pour the BEHR® NO. 992 Concrete & Masonry Paint Stripper into a paint tray or bucket. If water seems to have separated out, stir product until uniform.
- For vertical and glossy or greasy surfaces, scuff sand the surface lightly with a medium grit sand paper prior to application to prevent sagging of paint stripper.
- Test Patch: A test area will indicate the time required to lift coating and the suitability of the product for the paint and substrate.
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Prevent all rinse solution from entering storm drains.

#### APPLICATIONS

- Use product when air and surface temperatures are between 50-90°F (10-32°C).
- Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge.
- Apply a thick, even layer of stripper onto the surface using a paintbrush or an airless sprayer. Stripper thickness should be such that the original coated surface is completely covered.
- Spread rate is approximately 60-75 sq. ft. per gallon.
- Penetration varies according to coating type, thickness and temperature. COATING WILL WRINKLE WHEN THE JOB IS DONE. Most coatings will take between 1 – 6 hours to lift.

- Check periodically during the waiting period, to ensure that the coating is completely covered with the stripper. If the coated surface becomes visible again, re-apply a light coating.
- The stripper should remain wet and active until the coating wrinkles. If hot or windy conditions cause drying, re-apply a light coating.
- Use a scraper, squeegee or pressure washer to remove all coating and residue.
- The stripper is formulated to remove several layers of coating in one application. Some areas however, may require an additional application to remove all layers.
- The stripped surface must be rinsed with water thoroughly to remove all chemical residues before recoating.

#### SURFACE DRY TIME

- Surface dry time will vary, depending on air & surface temperature.
- Make sure surface is visually and completely dry to touch prior to recoating.

#### CLEAN UP AND STORAGE

- If product comes in contact with painted or finished surfaces not intended to be stripped, rinse immediately with fresh water.
- Thoroughly rinse all surfaces, clothing and tools with fresh water after use.
- Collect lifted coating and dispose of in accordance with local government regulations.
- For disposal of empty containers and unused product call 1-800-CLEANUP or visit [www.Earth911.org](http://www.Earth911.org)

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**\*LIMITED WARRANTY:** BEHR Process Corporation warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**CAUTION! IRRITANT! MAY CAUSE MODERATE EYE IRRITATION. HARMFUL IF SWALLOWED. CONTAINS GLYCOLIC ACID. MAY CAUSE SLIGHT SKIN IRRITATION AND MODERATE TO SEVERE GASTROINTESTINAL AND RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION.** Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN—DO NOT TAKE INTERNALLY.**

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (C.O.V.) 40.6 WT.% • REV. 2/08



## Premium Deck, Fence & Siding Stain & Finish Stripper

No. 64

- Removes Oil & Latex Finishes, Including Sealers, Waterproofers and 100% Acrylic Stains
- Biodegradable
- Easy Water Clean-Up

### IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

#### WHERE TO USE

- Exterior latex, oil-based and 100% acrylic coatings on Wood Decks, Siding, Fences, Shakes and Shingles.
- Removes loose wood fibers without sanding.
- Ideal for unsightly stains caused by oil or rusty water on uncoated Tile, Concrete, Masonry, Stucco, Stone, and Brick.  
Not for interior use or on aluminum surfaces. May harm bare metal or painted surfaces

**CAUTION:** Stained surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

#### PREPARATION† (The following steps are recommended for best results.)

- STIR OR SHAKE WELL BEFORE USE. DO NOT THIN PRODUCT.
- Be sure to have the following: source for tap water, garden hose with nozzle, plastic sprayer or disposable brush, stiff bristle broom or brush and BEHR® NO. 63 PREMIUM 2-IN-1 WOOD PREP.
- Surface must be dry. Do not apply in direct sunlight or on hot surfaces. Use product when air and surface temperatures are between 50-90°F (10-32°C).
- Protect grass and any nearby plants by dampening these areas with water and covering with plastic drop cloths.
- Wear protective clothing, goggles, acid resistant gloves, and a NIOSH approved air purifying respirator with an organic vapor cartridge.
- Test in a small area for effectiveness, rinse and let dry before continuing.
- Prevent all rinse solution from entering storm drains.

#### APPLICATIONS

- Apply BEHR NO. 64 PREMIUM STAIN & FINISH STRIPPER liberally using a nylon/poly brush or roller. Natural bristle brushes or lambs wool applicators are not recommended.
- Do not allow product to dry on wood; keep surface wet by misting with water and re-apply BEHR NO. 64 PREMIUM STAIN & FINISH STRIPPER if drying occurs. Finish will begin to lift from the surface. Repeat process as needed to keep the surface wet during the removal period. Most deteriorated finishes will start to lift after about 5-45 minutes. The coating should easily rinse off when ready.
- When the finish starts to lift, lightly scrub the surface using a stiff bristle broom or brush.

**\*LIMITED WARRANTY:** BEHR Process Corporation warrants that this product meets BEHR's manufacturing specifications. If this product does not meet these specifications, BEHR will, at its option and upon proof-of-purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2008 BEHR PROCESS CORPORATION  
Santa Ana, CA 92704 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. (G.O.V.) 3.4 WT. % • REV. 2/08

- Rinse thoroughly with water from garden hose using nozzle at normal pressure, or use a pressure washer at a low setting (500-1200 PSI). **DO NOT USE HIGH PRESSURE** as this may harm the wood.
- If some of the old finish remains on the surface, repeat application procedure or spot sand as needed.
- Use at a rate of approximately 50-150 sq. ft. (4-14m<sup>2</sup>) per gallon, depending on porosity and condition of surface.
- Some woods may darken after stripping. Use BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP on all wood surfaces to remove stains caused by mildew, rejuvenate natural wood color and neutralize the stripping action. Follow all label instructions. This provides stability for reapplication of a new finish or sealer.
- Surface dry time will vary, depending on air & surface temperature.
- Make sure surface is visually and completely dry to touch prior to recoating.

#### DRY TIME

- Before applying a coating, allow a minimum of 24 hours in warm, dry weather or longer in cool temperatures and/or high humidity.
- Surfaces must be thoroughly dry before applying any type of new finish, except those finishes that can be applied to dampened wood.

#### CLEAN UP AND STORAGE

- Rinse all equipment with water before storage or reuse.
- Clean with soap & water.
- Properly dispose of all soiled rags and protect unused product from freezing.
- To recycle or properly dispose of product in your community call 1-800-CLEANUP (U.S.A. only) or visit [www.Earth911.org](http://www.Earth911.org).

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

† **WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**DANGER! CORROSIVE. WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS SODIUM HYDROXIDE. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE WITH ADEQUATE VENTILATION.** Only use this product outdoors. Wear protective clothing, acid resistant rubber gloves and eye goggles. Avoid breathing spray mist. If properly used, a respirator may offer additional protection. **FIRST AID:** Eye and skin contact: In case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**