



Waterproofing Wood Finish

- Durable Waterproofing Finish
- UV Protection Against Fading
- Mildew Resistant Finish

No. 400 Natural
No. 401 Cedar Naturaltone
No. 402 Redwood

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

When applied according to label instructions as described below, this product will protect wood from water damage for 2 years on horizontal surfaces, and 4 years on vertical surfaces. Color fading and slight natural graying of wood may occur during this period. A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

WHERE TO USE

- Exterior, properly prepared, unsealed wood surfaces such as: Decks, Railings, Shakes, Shingles, Siding, Roofs and Fences.

CAUTION: Stained surfaces may become slippery when wet.

PREPARATION† (The following steps are recommended for best results.)

- To remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood decks, siding, fences, shakes and shingles use BEHR® NO. 64 PREMIUM STAIN & FINISH STRIPPER.
- Use BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP to clean and brighten the wood surface and to remove **light to medium** stains caused by mold, mildew, algae & fungus. Rinse thoroughly. Allow to dry. Apply coating. On new wood use NO. 63 to remove mill glaze and open the pores of the wood.
- For **severe** stains caused by mold, mildew, algae & fungus apply BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER and rinse prior to applying BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP.

APPLICATIONS

- Do not use if temperature is below 40°F (4.5°C), above 90°F (32°C), or if rain is expected within 24 hours.
- The wood surface may be coated when damp-dry. Wipe any standing water off the surface prior to applying the finish.
- When working with more than one container of the same color, intermix to ensure color uniformity. DO NOT THIN PRODUCT.
- Stir product before and occasionally during application. Test product for penetration and color on a small hidden area before proceeding.
- Use a nylon/polyester bristle brush or pad applicator. Rolling should be limited to rough surfaces only. Use a 3/8" nap roller.

***LIMITED WARRANTY:** BEHR PROCESS CORPORATION warrants customer satisfaction with this product for 4 years on vertical surfaces and for 2 years on horizontal surfaces from date of purchase, when applied to a properly prepared surface in accordance with the label directions. Color fading and slight natural graying of the wood may occur during this period, especially in areas exposed to heavy foot traffic or excessive weather. If you are not satisfied with this product, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. This warranty is made to the original residential product purchaser and is not transferable. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <275 g/L • REV. 2/08

- A high quality pump sprayer with a variable tip can be used. However, if a pump sprayer is used, work in small sections lightly saturating the surface and back-brush/roll immediately to remove excess and evenly distribute the finish.
- Airless spray is recommended for experienced applicators only. Use a .015 tip.
- Saturate surface leaving a wet sheen. Maintain a wet edge when applying. Always back-brush during all application methods. Apply product end-to-end or to board lengths to prevent lap marks. For optimum performance, coat all six sides of wood.
- One coat is recommended. Spread rate is approximately 250-300 sq. ft. (23-28 m²) per gallon.

DRY TIME

- 24-48 hours before subjecting surface to light foot traffic, 72 hours for full cure.

CLEAN UP AND STORAGE

- Use soap and water.
- To recycle or properly dispose of stains and sealers in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



IMPORTANT! STORAGE AND DISPOSAL: DANGER! Rags, steel wool and waste soaked with this **BEHR PREMIUM WEATHERPROOFING WOOD FINISH** may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: AN OXIDIZING OIL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air and use a properly fitted respirator (NIOSH approved for organic vapor with P Series particulate prefilter). Obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air and use a properly fitted respirator (NIOSH approved for organic vapor with P Series particulate prefilter). Obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY



Premium, Deck, Fence & Siding Weatherproofing Wood Finish

- UV Protection Against Fading
- Mildew Resistant Finish
- Silicone-Enhanced Waterproofing Formula
- Easy Water Clean-Up

No. 500 Natural
No. 501 Cedar Naturaltone
No. 502 Redwood

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

WHERE TO USE

- Exterior, properly prepared, unsealed Wood Surfaces such as: Decks, Railings, Shakes, Shingles, Siding, Roofs, Fences and Furniture.

CAUTION: Stained surfaces may become slippery when wet.

PREPARATION† (The following steps are recommended for best results.)

- To remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood decks, siding, fences, shakes and shingles use BEHR® NO. 64 PREMIUM STAIN & FINISH STRIPPER.
- Use BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP to clean and brighten the wood surface and to remove **light to medium** stains caused by mold, mildew, algae & fungus. Rinse thoroughly. Allow to dry. Apply coating. On new wood use NO. 63 to remove mill glaze and open the pores of the wood.
- For **severe** stains caused by mold, mildew, algae & fungus apply BEHR NO. 62 PREMIUM MILDEW STAIN REMOVER and rinse prior to applying BEHR NO. 63 PREMIUM 2-IN-1 WOOD PREP.

APPLICATIONS

- Do not use if temperature is below 40°F (4.5°C), above 90°F (32°C), or if rain is expected within 24 hours.
- The wood surface may be coated when damp-dry. Wipe any standing water off the surface prior to applying the finish.
- When working with more than one container of the same color, intermix to ensure color uniformity.
- Stir product before and occasionally during application. Test product for penetration and color on a small hidden area before proceeding.
- Use a nylon/polyester bristle brush or pad applicator. Rolling should be limited to rough surfaces only. Use a 3/8" nap roller.

***LIMITED WARRANTY:** BEHR PROCESS CORPORATION warrants customer satisfaction with this product for 6 years on vertical surfaces and for 4 years on horizontal surfaces from date of purchase, when applied to a properly prepared surface in accordance with the label directions. Color fading and slight natural graying of the wood may occur during this period, especially in areas exposed to heavy foot traffic or excessive weather. If you are not satisfied with this product, BEHR will, at its option and upon proof of purchase, either furnish an equivalent amount of new product or refund the purchase price. This warranty is made to the original residential purchaser and is not transferable. **BEHR will not be responsible for (1) labor or the cost of labor for removal or application of any product or (2) any incidental or consequential damages, whether based upon breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2008 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • www.behr.com
V.O.C. (C.O.V.) <275 g/L • REV. 2/08

- A high quality pump sprayer with a variable tip or an airless sprayer with a .015 tip may be used. Work in small sections lightly saturating the surface and immediately back brush/roll to remove excess and evenly distribute the finish.
- Saturate surface leaving a wet sheen. Maintain a wet edge when applying. Always back-brush during all application methods. Apply product end-to-end or to board lengths to prevent lap marks. For optimum performance, coat all six sides of wood.
- Two coats are required for optimal appearance and durability. Spread rate of the first coat is approximately 300-350 sq. ft. (28-32 m²) per gallon. Apply a thinner second coat at a spread rate of approximately 600-700 sq. ft. (56-64 m²) per gallon.

DRY TIME

- 1-2 hours dry time before applying the second coat. Apply the second coat no later than 48 hours after first coat. Allow 72 hours for full cure.

CLEAN UP AND STORAGE

- Use soap and water.
- To recycle or properly dispose of stains and sealers in your community call 1-800-CLEANUP or visit www.Earth911.org.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.



IMPORTANT! STORAGE AND DISPOSAL: DANGER! Rags, steel wool and waste soaked with this BEHR PREMIUM WEATHERPROOFING WOOD FINISH may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ALKYD RESIN. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air and use a properly fitted respirator (NIOSH approved for organic vapor with P Series particulate prefilter). Obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY