



PRO LGR 7000XLI PORTABLE DEHUMIDIFIER



HOW TO USE:

Place unit in center of space. If drying with airmovers, position the dehumidifier so that its front outlet is close to the inlet of an airmover to maximize the drying effect. Use dehumidifier with the High Airflow Filter installed under the top inlet grill. Check the filter often for excessive dust buildup, especially in dusty areas. Remove and vacuum the filter up to 3 times before replacing it with a new High Airflow Filter (F502). **DO NOT WASH FILTER** – replace filter if it becomes wet.

F502
High Air Flow Filters
from 3M™

RENTER SHOULD ALWAYS REMOVE, BAG AND DISPOSE OF ALL USED FILTERS BEFORE RETURNING THE DEHUMIDIFIER TO HOME DEPOT.

WHAT IT DOES:

The Dri-Eaz® LGR 7000XLI dehumidifier reduces humidity after leaks, spills and floods, or when humidity levels are too high for comfort or safety. This professional-grade LGR dehumidifier continues to dry even after humidity levels have dropped which helps prevent mold and mildew.

WHEN TO USE:

- Reduce humidity in water damaged areas after leaks, spills or floods.
- Prevent mildew, mold and musty smells.
- Control humidity during remodels, repairs, or when HVAC systems are temporarily disabled.
- Reduce humidity for faster drying of drywall mud, plaster or paint.
- One unit can remove moisture from an enclosed space up to 13,000 cubic feet (368 cubic meters).

OPERATING THE 7000XLI

1 Position the unit in closed room

Don't block the airflow into and out of the unit.



2. Set up drain hose

Unwrap the entire hose, attach the end with the connector to the "quick disconnect" on the back of the unit, then place the unattached end in a sink, drain, toilet or outdoors.



3. Plug unit in

4. Turn the unit on

FOR WATER DAMAGE DEHUMIDIFICATION

Just turn the unit on. Unit will provide maximum dehumidification.



TO MAINTAIN A SET HUMIDITY LEVEL

Use the **Humidistat Mode**. See Owner's Manual.



At end of the job

Press the **PURGE** key. When the purge cycle is complete, press **ON/OFF** to turn the unit off. Leave the unit plugged in and let it sit for 15 min., then press **PURGE** again.

The unit may now be moved to a new location.

See Owner's Manual for important safety information and detailed operating instructions



Proudly
BUILT IN USA

Go to HD.driez.com
for instructional videos and user guides.
Or call **800-932-3030** for technical support

